



1122-T Series 中重型 中重負載系列

- 支架一體成型，流線美觀，堅固耐用，荷重高，適用於講究美觀、又強調荷重的環境。
- Pressed steel yoke with good outlook and added strength; ideal for application requiring both aesthetic and heavy load.

載重 Load
150-350 kg



特色區 Features



中剎
Center Lock Brake



側剎
Side Lock Brake



輪子可附防塵蓋
Thread guard

輪子選項 Wheel Options



底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

編號 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
1	100 x 115 mm (4" x 4-1/2")	75 x 80 mm (2-5/8"~3"x3-5/8")	9.5 mm (3/8")



輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
100mm×38mm (4"x1-1/2")	200 kgs (440 lbs)	鐵芯聚氨酯 PU on Cast	1122-04-33-1-T	1122-04-33-2-T	1122-04-33-4-T	滾珠 Ball Bearing	167mm (6-9/16")	活動87mm 煞車87mm Swivel 87mm Swivel W/Brake 87mm
	150 kgs (330 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1122-04-04-1-T	1122-04-04-2-T	1122-04-04-4-T			
	200 kgs (440 lbs)	尼龍輪 Nylon	1122-04-07-1-T	1122-04-07-2-T	1122-04-07-4-T			
	150 kgs (330 lbs)	CPD輪 CPD	1122-04-49-1-T	1122-04-49-2-T	1122-04-49-4-T			
	150 kgs (330 lbs)	高彈力橡膠輪 Resilient Rubber on PA core	1122-04-10-1-T	1122-04-10-2-T	1122-04-10-4-T			
	150 kgs (330 lbs)	三星輪 Rubber on Cast	1122-04-03-1-T	1122-04-03-2-T	1122-04-03-4-T			
	140 kgs (308 lbs)	W全效輪 W Resolute	1122-04-64-1-T	1122-04-64-2-T	1122-04-64-4-T			
125mm×38mm (5"x1-1/2")	220 kgs (485 lbs)	鐵芯聚氨酯 PU on Cast	1122-05-33-1-T	1122-05-33-2-T	1122-05-33-4-T	滾珠 Ball Bearing	192mm (7-1/2")	活動110mm 煞車110mm Swivel 110mm Swivel W/Brake 110mm
	170 kgs (375 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1122-05-04-1-T	1122-05-04-2-T	1122-05-04-4-T			
	220 kgs (485 lbs)	尼龍輪 Nylon	1122-05-07-1-T	1122-05-07-2-T	1122-05-07-4-T			
	170 kgs (375 lbs)	CPD輪 CPD	1122-05-49-1-T	1122-05-49-2-T	1122-05-49-4-T			
	170 kgs (375 lbs)	高彈力橡膠輪 Resilient Rubber on PA core	1122-05-10-1-T	1122-05-10-2-T	1122-05-10-4-T			
	170 kgs (375 lbs)	三星輪 Rubber on Cast	1122-05-03-1-T	1122-05-03-2-T	1122-05-03-4-T			
	160 kgs (352 lbs)	W全效輪 W Resolute	1122-05-64-1-T	1122-05-64-2-T	1122-05-64-4-T	滾針 Roller Bearing		
150mm×42mm (6" x1-5/8")	240 kgs (525 lbs)	鐵芯聚氨酯 PU on Cast	1122-06-33-1-T	1122-06-33-2-T	1122-06-33-4-T	滾珠 Ball Bearing	242mm (9-9/16")	活動113mm 煞車113mm Swivel 113mm Swivel W/Brake 113mm
	190 kgs (415 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1122-06-04-1-T	1122-06-04-2-T	1122-06-04-4-T			
	240 kgs (525 lbs)	尼龍輪 Nylon	1122-06-07-1-T	1122-06-07-2-T	1122-06-07-4-T			
	190 kgs (415 lbs)	CPD輪 CPD	1122-06-49-1-T	1122-06-49-2-T	1122-06-49-4-T			
	190 kgs (415 lbs)	高彈力橡膠輪 Resilient Rubber on PA core	1122-06-10-1-T	1122-06-10-2-T	1122-06-10-4-T			
	190 kgs (415 lbs)	三星輪 Rubber on Cast	1122-06-03-1-T	1122-06-03-2-T	1122-06-03-4-T			
	180 kgs (396 lbs)	W全效輪 W Resolute	1122-06-64-1-T	1122-06-64-2-T	1122-06-64-4-T			
200mm×48mm (8"x2)	350kgs (660 lbs)	鐵芯聚氨酯 PU on Cast	1122-08-33-1-T	1122-08-33-2-T	1122-08-33-4-T	滾珠 Ball Bearing	293mm (11-1/2")	活動143mm 煞車143mm Swivel 143mm Swivel W/Brake 143mm
	350 kgs (660 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1122-08-04-1-T	1122-08-04-2-T	1122-08-04-4-T			
	350 kgs (770 lbs)	尼龍輪 Nylon	1122-08-07-1-T	1122-08-07-2-T	1122-08-07-4-T			
	300 kgs (660 lbs)	CPD輪 CPD	1122-08-49-1-T	1122-08-49-2-T	1122-08-49-4-T			
	300 kgs (660 lbs)	高彈力橡膠輪 Resilient Rubber on PA core	1122-08-10-1-T	1122-08-10-2-T	1122-08-10-4-T			
	260 kgs (570 lbs)	三星輪 Rubber on Cast	1122-08-03-1-T	1122-08-03-2-T	1122-08-03-4-T			
	306 kgs (675 lbs)	W全效輪 W Resolute	1122-08-64-1-T	1122-08-64-2-T	1122-08-64-4-T			

