



1108-M Duty Series 中型 日式轮系列

- 转动灵活宁静，有双刹与侧刹可供选择。
- Easy swivel, quiet operation. Total lock and side lock brake are available.

载重 Load
140-180kg



特色区 Features

双刹
Total Lock Brake



侧刹(限4",136.5mm总高)
Side Lock Brake
For 4"(136.5mm height only)



波盘防尘盖
Swivel Dust Cover



轮子可附金属防尘盖(供选择)
Metal Thread Guard(Optional)



轮子选项 Wheel Options



铝芯AQPU
QPU on AL Core



铝芯橡胶轮
Rubber on AL Core



铝芯QQ橡胶轮
Recilent rubber on AL Core



尼龙轮
Nylon



W全效轮
W Resolute



活动底板规格 SWIVEL TOP PLATE SIZE AND BOLT HOLE SPACING

| 脚轮尺寸 Caster Size | 底板尺寸 Top Plate Size | 底板孔距 Bolt Hole Spacing | 安装尼帽尺寸 Attaching Bolt Size |
|---------------------------------|-----------------------------|-------------------------------|-------------------------------|
| 4" 5"活动底板 4" 5" Swivel plate | 92 x 92 mm (3-5/8"x 3-5/8") | 70 x 70 mm (2-3/4"x 2-3/4") | 8 mm (5/16") |
| 4" 5"活动底板 4" 5" Swivel plate | 101x101 mm (4"x 4") | 78 x 78 mm (3-1/16"x 3-1/16") | 10 mm (3/8") |

固定底板规格 RIGID TOP PLATE SIZE AND BOLT HOLE SPACING

| 脚轮尺寸 Caster Size | 底板尺寸 Top Plate Size | 底板孔距 Bolt Hole Spacing | 安装尼帽尺寸 Attaching Bolt Size |
|--------------------------------|-----------------------------|-----------------------------|-------------------------------|
| 4" 5"固定底板 4" 5" Rigid plate | 92 x 92 mm (3-5/8"x 3-5/8") | 70 x 70 mm (2-3/4"x 2-3/4") | 8 mm (5/16") |



| 轮径×轮宽 Diameter×Width | 载重 Load | 材质 Material | 型号 Item No. | | | 轴承 Bearing | 总高 Overall Height | 回旋半径 Swivel radius |
|--------------------------------|---------------------------------------|---------------------------------------|--------------------|---------------------------------------|---------------------------------------|-------------------|--------------------------|---|
| | | | 固定 Fixed | 活动 Swivel | 刹车 Brake | | | |
| 100mm x 32mm (4" x 1-1/4") | 160 kgs(352 lbs) | 尼龙轮 Nylon | 1108-M-04-07-1 | 1108-M-04-07-2 | 1108-M-04-07-4 (Total lock 双刹) | 滚珠Ball Bearing | 134.5mm (5-1/4") | 活动 85.5mm 双刹 117mm Swivel 85.5mm Swivel W/Total Lock Brake 117mm |
| | 160 kgs(352 lbs) | | | | | 中管Plain Bearing | | |
| | 140 kgs(308 lbs) | 铝芯QQ橡胶轮 Recilent rubber on AL Core | 1108-M-04-89-1 | 1108-M-04-89-2 | 1108-M-04-89-4 (Total lock 双刹) | | | |
| 140 kgs(308 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-04-87-1 | 1108-M-04-87-2 | 1108-M-04-87-4 (Total lock 双刹) | | | | |
| 140 kgs(308 lbs) | W全效轮 W Resolute Wheel | 1108-M-04(36)-64-1 | 1108-M-04(36)-64-2 | 1108-M-04(36)-64-4 (Total lock 双刹) | | | | |
| 160 kgs(352 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-04(36)-87-1 | 1108-M-04(36)-87-2 | 1108-M-04(36)-87-4 (Total lock 双刹) | 滚珠Ball Bearing | | | |
| 100mm x 36mm (4" x 1-7/16") | 140 kgs(308 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-04(40)-87-1 | 1108-M-04(40)-87-2 | 1108-M-04(40)-87-4 (Total lock 双刹) | | 136.5mm (5-3/8") | 活动 93.5mm 侧刹 93.5mm Swivel 93.5mm Swivel W/Side Brake 93.5mm |
| | 160 kgs(352 lbs) | 铝芯QQ橡胶轮 Recilent rubber on AL Core | 1108-M-04(40)-89-1 | 1108-M-04(40)-89-2 | 1108-M-04(40)-89-4 (Total lock 双刹) | | | |
| | 160 kgs(352 lbs) | 铝芯橡胶轮 Rubber on AL Core | 1108-M-04(40)-22-1 | 1108-M-04(40)-22-2 | 1108-M-04(40)-22-4 (Total lock 双刹) | | | |
| 140 kgs(308 lbs) | W全效轮 W Resolute Wheel | 1108-M-04(36)-64-1 | 1108-M-04(36)-64-2 | 1108-M-04(36)-64-4 (Side Brake 侧刹) | | | | |
| 160 kgs(352 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-04(36)-87-1 | 1108-M-04(36)-87-2 | 1108-M-04(36)-87-4 (Side Brake 侧刹) | 滚珠Ball Bearing | | | |
| 160 kgs(352 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-04(40)-87-1 | 1108-M-04(40)-87-2 | 1108-M-04(40)-87-4 (Side Brake 侧刹) | | | | |
| 100mm x 40mm (4" x 1-9/16") | 160 kgs(352 lbs) | 铝芯QQ橡胶轮 Recilent rubber on AL Core | 1108-M-04(40)-89-1 | 1108-M-04(40)-89-2 | 1108-M-04(40)-89-4 (Side Brake 侧刹) | | 159.5mm (6-1/4") | 活动 99.5mm 双刹 117mm Swivel 99.5mm Swivel W/Total Lock Brake 117mm |
| | 160 kgs(352 lbs) | 铝芯橡胶轮 Rabber on AL Core | 1108-M-04(40)-22-1 | 1108-M-04(40)-22-2 | 1108-M-04(40)-22-4 (Side Brake 侧刹) | | | |
| | 160 kgs(352 lbs) | 尼龙轮 Nylon | 1108-M-05(38)-07-1 | 1108-M-05(38)-07-2 | 1108-M-05(38)-07-4 (Total lock 双刹) | 中管Plain Bearing | | |
| 160 kgs(352 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-05-87-1 | 1108-M-05-87-2 | 1108-M-05-87-4 (Total lock 双刹) | 滚珠Ball Bearing | | | |
| 150 kgs(330 lbs) | 铝芯QQ橡胶轮 Recilent rubber on AL Core | 1108-M-05-89-1 | 1108-M-05-89-2 | 1108-M-05-89-4 (Total lock 双刹) | | | | |
| 160 kgs(352 lbs) | W全效轮 W Resolute Wheel | 1108-M-05(38)-64-1 | 1108-M-05(38)-64-2 | 1108-M-05(38)-64-4 (Total lock 双刹) | | | | |
| 125mm x 31mm (5" x 1-1/4") | 160 kgs(352 lbs) | 尼龙轮 Nylon | 1108-M-05(38)-07-1 | 1108-M-05(38)-07-2 | 1108-M-05(38)-07-4 (Total lock 双刹) | | 159.5mm (6-1/4") | 活动 99.5mm 双刹 117mm Swivel 99.5mm Swivel W/Total Lock Brake 117mm |
| | 160 kgs(352 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-05(40)-89-1 | 1108-M-05(40)-89-2 | 1108-M-05(40)-89-4 (Total lock 双刹) | | | |
| | 180 kgs(396 lbs) | 铝芯橡胶轮 Rubber on AL Core | 1108-M-05(40)-22-1 | 1108-M-05(40)-22-2 | 1108-M-05(40)-22-4 (Total lock 双刹) | | | |
| | 180 kgs(396 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-05(40)-87-1 | 1108-M-05(40)-87-2 | 1108-M-05(40)-87-4 (Total lock 双刹) | 滚珠Ball Bearing | | |
| 180 kgs(396 lbs) | 尼龙轮 Nylon | 1108-M-05(40)-07-1 | 1108-M-05(40)-07-2 | 1108-M-05(40)-07-4 (Total lock 双刹) | | | | |
| 180 kgs(396 lbs) | 铝芯AQPU QPU on AL Core | 1108-M-05(40)-87-1 | 1108-M-05(40)-87-2 | 1108-M-05(40)-87-4 (Total lock 双刹) | | | | |