



1115-L Series TW 特轻弹簧轮系列 Light Duty Spring-loaded Caster

- 属得胜专利产品，高避震力，针对电子产业与需要高度防震产品市场。
- Institutional version of spring-loaded caster. Ideal for chip industry and tool cart.

载重 Load
60-150 kg



特色区 Features



铝制
Total Lock Brake
with Aluminum Alloy Pedal



轮子可附防尘盖
Thread guard

轮子选项 Wheel Options



导电轮
E-Conductive



超级人造胶
TPR on PP Core



W全效轮
W Resolute Wheel



全效轮
Resolute



铝芯AQPU
QPU on AL Core



滚珠轴承
Ball Bearing

底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

脚轮尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
4", 5"	91 x 91 mm (3-9/16"x 3-9/16")	68 x 68 mm (2-11/16"x 2-11/16")	10 mm (3/8")

轮径X轮宽 Diameter×Width	载重 Load	材质 Material	型号 Item No.			轴承 Bearing	总高 Overall Height	回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
100mm×32mm (4"×1-1/4")	60 kgs (130 lbs)	导电轮 E-Conductive	--	1115-04-17-2-L	1115-04-17-4-L	滚珠 Ball Bearing	155.5mm (6-1/8")	活动82.5mm 刹车105mm Swivel 82.5mm Swivel W/Center lock 105mm
	90 kgs (198 lbs)	超级人造胶 TPR on PP Core	--	1115-04-75-2-L	1115-04-75-4-L			
	130 kgs (286 lbs)	W全效轮 W Resolute Wheel	--	1115-04-48-2-L	1115-04-48-4-L			
	120 kgs (264 lbs)	全效轮 Resolute	--	1115-04-68-2-L	1115-04-68-4-L			
	140 kgs (308 lbs)	铝芯AQPU QPU on AL Core	--	1115-04-87-2-L	1115-04-87-4-L			
125mm×32mm (5"×1-1/4")	70 kgs (150 lbs)	导电轮 E-Conductive	--	1115-05-17-2-L	1115-05-17-4-L	滚珠 Ball Bearing	193 mm (7-5/8")	活动91.5mm 刹车105mm Swivel 91.5mm Swivel W/Center lock 105 mm
	100 kgs (200 lbs)	超级人造胶 TPR on PP Core	--	1115-05-75-2-L	1115-05-75-4-L			
	147 kgs (323 lbs)	W全效轮 W Resolute Wheel	--	1115-05-48-2-L	1115-05-48-4-L			
	140 kgs (308 lbs)	全效轮 Resolute	--	1115-05-68-2-L	1115-05-68-4-L			
	150 kgs (330 lbs)	铝芯AQPU QPU on AL Core	--	1115-05-87-2-L	1115-05-87-4-L			