



1204 Series

空心胎/实心胎割草机轮 Semi-Pneumatic & Solid Rubber Wheel

- 适用于割草机, 木工机械, 高压清洗机, 发电机, 搬运车与氧气车等
胎纹可选择直纹(R)、钻纹(D)或齿纹(L)
轮框材质有铁框(可做烤漆或电镀处理)及塑框可供选择
各种OEM尺寸及设计可以依据产品设计需求生产
- Good for lawn mowers, wooden machinery, generators, two-wheeled carts, etc.
Various Tread patterns available: Rib, Diamond, and Gear
Rims can be plastic or steel (painted or zinc-plated)
OEM requests and tailored-made wheels in all sizes are welcome.

载重 Load
25-115 kg



实心胎橡胶轮 Solid Rubber Wheel

	轮径 Wheel diameter	轮宽 Width	荷重 Load (lbs.)	轴长 Hub Length	胎纹 Tread Pattern	型号 Item No.	轴承 Bearing
铁框 Steel Rim	6"	1-1/2"	60 kgs (130 lbs)	正心 centered: 1-3/4"	直纹 Rib	1204SS-6-15-C-R	1/2", 5/8", 3/4" hole flanged ball bearing
				偏心 offset: 1-3/8"		1204SS-6-15-OFF-R	
	7"	1-1/2"	70 kgs (150 lbs)	正心 centered: 2"	直纹 Rib	1204SS-7-15-C-R	1/2", 5/8", 3/4" hole flanged ball bearing
				偏心 offset: 1-3/8"		1204SS-7-15-OFF-R	
	8"	1-3/4"	70 kgs (150 lbs)	正心 centered: 2"	直纹 Rib	1204SS-8-175-C-R	1/2", 5/8", 3/4" hole flanged ball bearing
				偏心 offset: 1-3/8"		1204SS-8-175-OFF-R	
10"	1-3/4"	70 kgs (150 lbs)	正心 centered: 2"	直纹 Rib	1204SS-10-175-C-R	1/2", 3/4", 5/8" hole flanged ball bearing	
			偏心 offset: 1-3/8"		1204SS-10-175-OFF-R		
	2-3/4"	115 kgs (250 lbs)	正心 centered: 2"	直纹 Rib	1204SS-10-275-C-R	1/2", 3/4", 5/8" hole flanged ball bearing	
		偏心 offset: 2-1/4"			1204SS-10-275-OFF-R		
塑框 Plastic Rim	6"	1-1/2"	55 kgs (120 lbs)	正心 centered: 1-3/4"	直纹 Rib	1204SP-6-15-C-R	1/2" bore
				偏心 offset: 1-3/8"		1204SP-6-15-OFF-R	
	7"	1-1/2"	55 kgs (120 lbs)	正心 centered: 2"	直纹 Rib	1204SP-7-15-C-R	1/2" bore or 1/2" flanged ball bearing
				偏心 offset: 1-3/8"		1204SP-7-15-OFF-R	
	8"	1-3/4"	55 kgs (120 lbs)	正心 centered: 2"	直纹 Rib	1204SP-8-175-C-R	1/2" bore or 1/2" flanged ball bearing
				偏心 offset: 1-3/8"		1204SP-8-175-OFF-R	
	10"	1-3/4"	65 kgs (140 lbs)	正心 centered: 2"	直纹 Rib	1204SP-10-175-C-R	1/2" bore
				偏心 offset: 1-3/8"		1204SP-10-175-OFF-R	
	2-3/4"	100 kgs (220 lbs)	正心 centered: 2"	直纹 Rib	1204SP-10-275-C-R	5/8" hole flanged ball bearing	
		偏心 offset: 2-1/4"			1204SP-10-275-OFF-R		



空心胎橡胶轮 Semi-Pneumatic Rubber Wheel

	轮径 Wheel diameter	轮宽 Width	荷重 Load (lbs.)	轴长 Hub Length	胎纹 Tread Pattern	型号 Item No.	轴承 Bearing	
铁框 Steel Rim	6"	1-1/2"	25 kgs (50 lbs)	正心 centered: 1-3/4"	直纹 Rib	1204HS-6-15-C-R (直纹Rib)	1/2", 5/8", 3/4" hole flanged ball bearing	
					钻石纹 Diamond	1204HS-6-15- C-D (钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Rib	1204HS-6-15-OFF-R (直纹Rib)		
					钻石纹 Diamond	1204HS-6-15-OFF-D(钻纹Diamond)		
	7"	1-1/2"	30 kgs (60 lbs)	正心 centered: 2"	直纹 Rib	1204HS-7-15-C-R (直纹Rib)	1/2", 5/8", 3/4" hole flanged ball bearing	
					钻石纹 Diamond	1204HS-7-15-C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Rib	1204HS-7-15-OFF-R (直纹Rib)		
					钻石纹 Diamond	1204HS-7-15-OFF-D(钻纹Diamond)		
	8"	1-3/4"	35 kgs (80 lbs)	正心 centered: 2"	直纹 Rib	1204HS-8-175-C-R (直纹Rib)	1/2", 5/8", 3/4" hole flanged ball bearing	
					钻石纹 Diamond	1204HS-8-175-C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Gear	1204HS-8-175-C-G(横纹 Gear)		
					直纹 Rib	1204HS-8-175-OFF-R (直纹Rib)		
		2-1/2"	35 kgs (80 lbs)	正心 centered: 2"	直纹 Rib	1204HS-8-215-C-R (直纹Rib)		5/8" hole flanged ball bearing
					偏心 offset: 2-1/4"	直纹 Rib		
	10"	1-3/4"	45 kgs (100 lbs)	正心 centered: 2"	直纹 Rib	1204HS-10-175-C-R (直纹Rib)	1/2", 3/4", 5/8" hole flanged ball bearing	
					钻石纹 Diamond	1204HS-10-175-C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Rib	1204HS-10-175-OFF-R (直纹Rib)		
					钻石纹 Diamond	1204HS-10-175-OFF-D(钻纹Diamond)		
2-3/4"		70 kgs (160 lbs)	正心 centered: 2"	直纹 Rib	1204HS-10-275-C-R (直纹Rib)	1/2", 3/4", 5/8" hole flanged ball bearing		
				偏心 offset: 2-1/4"	直纹 Rib		1204HS-10-275-OFF-R (直纹Rib)	
3" (260*85)		90 kgs (200 lbs)	正心 centered: 2"	横纹 Gear	1204HS-10-30-C-G(横纹 Gear)	1/2", 3/4", 5/8" hole flanged ball bearing		
				偏心 offset: 2-1/4"	横纹 Gear		1204HS-10-30-OFF-G(横纹 Gear)	
12"	1-3/4"	35 kgs (80 lbs)	正心 centered: 2-1/4"	直纹 Rib	1204HS-12-175-C-R (直纹Rib)	1/2", 3/4", 5/8" hole flanged ball bearing		
塑框 Plastic Rim	6"	1-1/2"	25 kgs (50 lbs)	正心 centered: 1-3/16"	直纹 Rib	1204HP-6-15-C-R (直纹Rib)	1/2" bore	
					钻石纹 Diamond	1204HP-6-15-C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Rib	1204HP-6-15-OFF-R (直纹Rib)		
					钻石纹 Diamond	1204HP-6-15-OFF-D(钻纹Diamond)		
	7"	1-1/2"	30 kgs (60 lbs)	正心 centered: 2"	直纹 Rib	1204HP-7-15-C-R (直纹Rib)	1/2" bore or 1/2" flanged ball bearing	
					钻石纹 Diamond	1204HP-7-15-C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	直纹 Rib	1204HP-7-15-OFF-R (直纹Rib)		
					钻石纹 Diamond	1204HP-7-15-OFF-D(钻纹Diamond)		
	8"	1-3/4"	35 kgs (80 lbs)	正心 centered: 2"	直纹 Rib	1204HP-8-175-C-R (直纹Rib)	1/2" bore or 1/2" flanged ball bearing	
					钻石纹 Diamond	1204HP-8-175- C-D(钻纹Diamond)		
				偏心 offset: 1-3/8"	横纹 Gear	1204HP-8-175-C-G(横纹 Gear)		
					直纹 Rib	1204HP-8-175-OFF-R (直纹Rib)		
		2-1/2"	35 kgs (80 lbs)	正心 centered: 2"	直纹 Rib	1204HP-8-215-C-R (直纹Rib)		5/8" hole flanged ball bearing
					偏心 offset: 2-1/4"	直纹 Rib		
	10"	1-3/4"	45 kgs (100 lbs)	正心 centered: 2"	直纹 Rib	1204HP-10-175-C-R (直纹Rib)	1/2" bore	
					钻石纹 Diamond	1204HP-10-175-C-D(钻纹Diamond)		
		偏心 offset: 1-3/8"	直纹 Rib	1204HP-10-175-OFF-R (直纹Rib)				
			钻石纹 Diamond	1204HP-10-175-OFF-D(钻纹Diamond)				
2-3/4"	70 kgs (160 lbs)	正心 centered: 2"	直纹 Rib	1204HP-10-275-C-R (直纹Rib)	1/2", 3/4", 5/8" hole flanged ball bearing			
			偏心 offset: 2-1/4"	直纹 Rib		1204HP-10-275-OFF-R (直纹Rib)		