



# 1103 Series 重型 C型系列

- 高負載且旋轉靈活，普遍適用於一般工廠搬運，另可附防纏絲及防塵蓋，屬得勝專利產品，可以有效防止腳輪因灰塵或纏絲而無法轉動，提高腳輪使用壽命。
- Swivel easily under heavy load, for workshop carts. Patented thread guards prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.

載重 Load  
200-420 kg



## ▶▶ 特色區 Features



中剎  
Center Lock Brake



輪子可附防塵蓋  
Tread guard



輪子可附防纏絲蓋  
Tread guard specially  
for textile industry

## ▶▶ 輪子選項 Wheel Options









滾珠軸承  
Ball Bearing

## ▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

| 腳輪尺寸<br>Caster Size | 底板尺寸<br>Top Plate Size            | 底板孔距<br>Bolt Hole Spacing     | 安裝尼帽尺寸<br>Attaching Bolt Size |
|---------------------|-----------------------------------|-------------------------------|-------------------------------|
| 4"C型架<br>4"Caster   | 100 x 115 mm (3-15/16"x 4-1/2")   | 75 x 75 mm (3"x 3")           | 10 mm (3/8")                  |
| 5"C型架<br>5"Caster   | 100 x 115 mm (3-15/16"x 4-1/2")   | 75 x 75 mm (3"x 3")           | 10 mm (3/8")                  |
| 6"C型架<br>6"Caster   | 125 x 125 mm (4-15/16"x 4-15/16") | 105 x 105 mm (4-1/8"x 4-1/8") | 10 mm (3/8")                  |
| 8"C型架<br>8"Caster   | 125 x 125 mm (4-15/16"x 4-15/16") | 105 x 105 mm (4-1/8"x 4-1/8") | 10 mm (3/8")                  |



| <br>輪徑×輪寬<br>Diameter×Width | <br>載重<br>Load | <br>材質<br>Material |  型號 Item No. |              |              | <br>軸承<br>Bearing | <br>總高<br>Overall Height |
|--|---|---|---|--------------|--------------|--|---|
|  |   |   | 固定<br>Fixed   | 活動<br>Swivel | 剎車<br>Brake  |  |   |
| 100mm×38mm<br>(4"×1-1/2")  | 200 kgs (440 lbs)   | 鐵芯聚氨酯<br>PU on Cast   | 1103-04-33-1  | 1103-04-33-2 | 1103-04-33-4 | 滾珠<br>Ball Bearing   | 145mm<br>(5-11/16")   |
|  | 200 kgs (440 lbs)   | 三星輪<br>Rubber on Cast   | 1103-04-03-1  | 1103-04-03-2 | 1103-04-03-4 |  |   |
|  | 200 kgs (440 lbs)   | TPO 輪<br>TPO  | 1103-04-41-1  | 1103-04-41-2 | 1103-04-41-4 |  |   |
|  | 250 kgs (550 lbs)   | 尼龍輪<br>Nylon  | 1103-04-07-1  | 1103-04-07-2 | 1103-04-07-4 |  |   |
|  | 250 kgs (550 lbs)   | 銑輪<br>Cast Iron   | 1103-04-14-1  | 1103-04-14-2 | 1103-04-14-4 |  |   |
| 125mm×42mm<br>(5"×1-5/8")  | 250 kgs (550 lbs)   | 鐵芯聚氨酯<br>PU on Cast   | 1103-05-33-1  | 1103-05-33-2 | 1103-05-33-4 | 滾珠<br>Ball Bearing   | 167mm<br>(6-9/16")  |
|  | 220 kgs (485 lbs)   | 三星輪<br>Rubber on Cast   | 1103-05-03-1  | 1103-05-03-2 | 1103-05-03-4 |  |   |
|  | 250 kgs (550 lbs)   | TPO 輪<br>TPO  | 1103-05-41-1  | 1103-05-41-2 | 1103-05-41-4 |  |   |
|  | 300 kgs (660 lbs)   | 尼龍輪<br>Nylon  | 1103-05-07-1  | 1103-05-07-2 | 1103-05-07-4 |  |   |
|  | 300 kgs (660 lbs)   | 銑輪<br>Cast Iron   | 1103-05-14-1  | 1103-05-14-2 | 1103-05-14-4 |  |   |
| 150mm×48mm<br>(6"×1-7/8")  | 410 kgs (900 lbs)   | 高科技耐磨聚氨酯(圓弧形)<br>PU on PP Core (Round Shape)  | 1103-06-43-1  | 1103-06-43-2 | 1103-06-43-4 | 滾珠<br>Ball Bearing   | 197mm<br>(7-3/4")   |
|  | 300 kgs (660 lbs)   | 鐵芯聚氨酯<br>PU on Cast   | 1103-06-33-1  | 1103-06-33-2 | 1103-06-33-4 |  |   |
|  | 260 kgs (570 lbs)   | 三星輪<br>Rubber on Cast   | 1103-06-03-1  | 1103-06-03-2 | 1103-06-03-4 |  |   |
|  | 300 kgs (660 lbs)   | TPO 輪<br>TPO  | 1103-06-41-1  | 1103-06-41-2 | 1103-06-41-4 |  |   |
|  | 350 kgs (770 lbs)   | 尼龍輪<br>Nylon  | 1103-06-07-1  | 1103-06-07-2 | 1103-06-07-4 |  |   |
|  | 260 kgs (570 lbs)   | 鐵芯聚氨酯(圓弧形)<br>PU on Cast (Round Shape)  | 1103-06-42-1  | 1103-06-42-2 | 1103-06-42-4 |  |   |
|  | 350 kgs (770 lbs)   | 銑輪<br>Cast Iron   | 1103-06-14-1  | 1103-06-14-2 | 1103-06-14-4 |  |   |
| 200mm×48mm<br>(8"×1-7/8")  | 420 kgs (925 lbs)   | 高科技耐磨聚氨酯(圓弧形)<br>PU on PP Core (Round Shape)  | 1103-08-43-1  | 1103-08-43-2 | 1103-08-43-4 | 滾珠<br>Ball Bearing   | 243mm<br>(9-9/16")  |
|  | 350 kgs (770 lbs)   | 鐵芯聚氨酯<br>PU on Cast   | 1103-08-33-1  | 1103-08-33-2 | 1103-08-33-4 |  |   |
|  | 300 kgs (660 lbs)   | 三星輪<br>Rubber on Cast   | 1103-08-03-1  | 1103-08-03-2 | 1103-08-03-4 |  |   |
|  | 350 kgs (770 lbs)   | TPO 輪<br>TPO  | 1103-08-41-1  | 1103-08-41-2 | 1103-08-41-4 |  |   |
|  | 400 kgs (880 lbs)   | 尼龍輪<br>Nylon  | 1103-08-07-1  | 1103-08-07-2 | 1103-08-07-4 |  |   |
|  | 300 kgs (660 lbs)   | 鐵芯聚氨酯(圓弧形)<br>PU on Cast (Round Shape)  | 1103-08-42-1  | 1103-08-42-2 | 1103-08-42-4 |  |   |
|  | 400 kgs (880 lbs)   | 銑輪<br>Cast Iron   | 1103-08-14-1  | 1103-08-14-2 | 1103-08-14-4 |  |   |

