



1103 Series 重型 C型系列

- 高負載且旋轉靈活，普遍適用於一般工廠搬運，另可附防纏絲及防塵蓋，屬得勝專利產品，可以有效防止腳輪因灰塵或纏絲而無法轉動，提高腳輪使用壽命。
- Swivel easily under heavy load, for workshop carts. Patented thread guards prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.

載重 Load
200-420 kg



▶▶ 特色區 Features



中剎
Center Lock Brake



輪子可附防塵蓋
Tread guard



輪子可附防纏絲蓋
Tread guard specially
for textile industry

▶▶ 輪子選項 Wheel Options



滾珠軸承
Ball Bearing

▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4"C型架 4"Caster	100 x 115 mm (3-15/16"x 4-1/2")	75 x 75 mm (3"x 3")	10 mm (3/8")
5"C型架 5"Caster	100 x 115 mm (3-15/16"x 4-1/2")	75 x 75 mm (3"x 3")	10 mm (3/8")
6"C型架 6"Caster	125 x 125 mm (4-15/16"x 4-15/16")	105 x 105 mm (4-1/8"x 4-1/8")	10 mm (3/8")
8"C型架 8"Caster	125 x 125 mm (4-15/16"x 4-15/16")	105 x 105 mm (4-1/8"x 4-1/8")	10 mm (3/8")



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height
			固定 Fixed	活動 Swivel	剎車 Brake		
100mm×38mm (4"×1-1/2")	200 kgs (440 lbs)	鐵芯聚氨酯 PU on Cast	1103-04-33-1	1103-04-33-2	1103-04-33-4	滾珠 Ball Bearing	145mm (5-11/16")
	200 kgs (440 lbs)	三星輪 Rubber on Cast	1103-04-03-1	1103-04-03-2	1103-04-03-4		
	200 kgs (440 lbs)	TPO 輪 TPO	1103-04-41-1	1103-04-41-2	1103-04-41-4		
	250 kgs (550 lbs)	尼龍輪 Nylon	1103-04-07-1	1103-04-07-2	1103-04-07-4		
	250 kgs (550 lbs)	銑輪 Cast Iron	1103-04-14-1	1103-04-14-2	1103-04-14-4		
125mm×42mm (5"×1-5/8")	250 kgs (550 lbs)	鐵芯聚氨酯 PU on Cast	1103-05-33-1	1103-05-33-2	1103-05-33-4	滾珠 Ball Bearing	167mm (6-9/16")
	220 kgs (485 lbs)	三星輪 Rubber on Cast	1103-05-03-1	1103-05-03-2	1103-05-03-4		
	250 kgs (550 lbs)	TPO 輪 TPO	1103-05-41-1	1103-05-41-2	1103-05-41-4		
	300 kgs (660 lbs)	尼龍輪 Nylon	1103-05-07-1	1103-05-07-2	1103-05-07-4		
	300 kgs (660 lbs)	銑輪 Cast Iron	1103-05-14-1	1103-05-14-2	1103-05-14-4		
150mm×48mm (6"×1-7/8")	410 kgs (900 lbs)	高科技耐磨聚氨酯(圓弧形) PU on PP Core (Round Shape)	1103-06-43-1	1103-06-43-2	1103-06-43-4	滾珠 Ball Bearing	197mm (7-3/4")
	300 kgs (660 lbs)	鐵芯聚氨酯 PU on Cast	1103-06-33-1	1103-06-33-2	1103-06-33-4		
	260 kgs (570 lbs)	三星輪 Rubber on Cast	1103-06-03-1	1103-06-03-2	1103-06-03-4		
	300 kgs (660 lbs)	TPO 輪 TPO	1103-06-41-1	1103-06-41-2	1103-06-41-4		
	350 kgs (770 lbs)	尼龍輪 Nylon	1103-06-07-1	1103-06-07-2	1103-06-07-4		
	260 kgs (570 lbs)	鐵芯聚氨酯(圓弧形) PU on Cast (Round Shape)	1103-06-42-1	1103-06-42-2	1103-06-42-4		
	350 kgs (770 lbs)	銑輪 Cast Iron	1103-06-14-1	1103-06-14-2	1103-06-14-4		
200mm×48mm (8"×1-7/8")	420 kgs (925 lbs)	高科技耐磨聚氨酯(圓弧形) PU on PP Core (Round Shape)	1103-08-43-1	1103-08-43-2	1103-08-43-4	滾珠 Ball Bearing	243mm (9-9/16")
	350 kgs (770 lbs)	鐵芯聚氨酯 PU on Cast	1103-08-33-1	1103-08-33-2	1103-08-33-4		
	300 kgs (660 lbs)	三星輪 Rubber on Cast	1103-08-03-1	1103-08-03-2	1103-08-03-4		
	350 kgs (770 lbs)	TPO 輪 TPO	1103-08-41-1	1103-08-41-2	1103-08-41-4		
	400 kgs (880 lbs)	尼龍輪 Nylon	1103-08-07-1	1103-08-07-2	1103-08-07-4		
	300 kgs (660 lbs)	鐵芯聚氨酯(圓弧形) PU on Cast (Round Shape)	1103-08-42-1	1103-08-42-2	1103-08-42-4		
	400 kgs (880 lbs)	銑輪 Cast Iron	1103-08-14-1	1103-08-14-2	1103-08-14-4		

