



# 1117 Series 重型 藍架系列

- 高負載，適用於水泥路面或凹凸不平的地面，所配風輪、風硬輪，採用優質橡膠製成，荷重高，耐磨耐衝擊。
- Heavy-duty, good for cement ground and uneven floor. Wheel options include pneumatic wheels and solid rubber wheels, made of quality rubber to withstand abrasion and impact under heavy load.

載重 Load  
150-250 kg



## ▶ 特色區 Features ▶ 輪子選項 Wheel Options



中剎  
Center Lock Brake



風輪(烤漆鐵框)  
Pneumatic with painted steel rim



風輪(塑框)  
Pneumatic with plastic rim



風輪(鍍鋅鐵框)  
Pneumatic with plated steel rim



風硬輪(烤漆鐵框)  
Solid Rubber wheel with painted steel rim



風硬輪(鍍鋅鐵框)  
Solid Rubber wheel with plated steel rim



滾珠軸承  
Ball Bearing

## ▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
8" 藍架 8"Caster	100 x 144 mm (3-15/16"x 4-1/2")	75 x 120 mm (3"x 4-3/4")	12 mm (1/2")
10" 藍架 10"Caster	130 x 170 mm (5-1/8"x 6-13/16")	100 x 140 mm (3-15/16"x 5-1/2")	12 mm (1/2")
12" 藍架 12"Caster	130 x 170 mm (5-1/8"x 6-13/16")	100 x 140 mm (3-15/16"x 5-1/2")	12 mm (1/2")

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	輪子樣式
			固定 Fixed	活動 Swivel	剎車 Brake			
200mm x 45mm (8" x 1-13/16")	150 kgs (330 lbs)	風輪 Pneumatic	1117-08-01-1	1117-08-01-2	1117-08-01-4	滾珠 Ball Bearing	250mm (10")	
	180 kgs (400 lbs)	風硬輪 Solid Rubber	1117-08-02-1	1117-08-02-2	1117-08-02-4			
250mm x 42mm (10" x 1-5/8")	200 kgs (440 lbs)	風輪 Pneumatic	1117-10-01-1	1117-10-01-2	1117-10-01-4	滾珠 Ball Bearing	306mm (12")	
	220 kgs (480 lbs)	風硬輪 Solid Rubber	1117-10-02-1	1117-10-02-2	1117-10-02-4			
300mm x 85mm (12" x 3-1/3")	250 kgs (550 lbs)	風輪 Pneumatic	1117-12-01-1	1117-12-01-2	1117-12-01-4	滾珠 Ball Bearing	365mm (14-3/8")	