



1119 Series Scaffolding Caster

○ Design for Scaffolds.

Load
350-420 kg



» Features



Center Lock Brake


» Wheel Options



NBR Rubber on Cast



PU on PP Core



Roller Bearing

Ball Bearing

» STEM SIZE AND BOLT HOLE SPACING

Suffix	Stem Size	Stem Height x Hole Height	Bore Size
1	35 mm (1-3/8")	100 mm x 60 mm (3-15/16x 2-3/8")	11 mm (7/16")

Diameter×Width 	Load 	Material 	Item No. 			Bearing 	Swivel radius
			Fixed	Swivel	Brake		
150mm×50mm (6"×2")	350 kgs (770 lbs)	NBR Rubber on Cast	--	--	1119-06-04-4	Roller Bearing	Swivel W/Center lock 120mm
	350 kgs (770 lbs)	PU on PP Core	--	--	1119-06-31-4		
200mm×45mm (8"×1-3/4")	420 kgs (925 lbs)	NBR Rubber on Cast	--	-	1119-08-04-4	Ball Bearing	Swivel W/Center lock 143.5mm
200mm×50mm (8"×2")	420 kgs (925 lbs)	NBR Rubber on Cast	--	-	1119-08-04-4	Roller Bearing	Swivel W/Center lock 152mm
	420 kgs (925 lbs)	PU on PP Core	--	-	1119-08-31-4		