



1124 Series 1-1/2" Wide General Purposes Caster (American Style)

- Swivel easily under heavy load, for workshop carts. Patented thread guards prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.

Load
140-400 kg



Features



Side Lock Brake



Center Lock Brake



Thread guard



Different PU tread hardness available

Wheel Options

NBR Rubber on Cast



PU on Cast



Rubber on Cast



Non-marking Rubber on Cast



W Resolute



WCPD



QPU



Ball Bearing



Nylon



Cast Iron



CPD



Resolute



WMRC



EPU



EQPU










QPU on AL Core








TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	100 x 115 mm (4"x 4-1/2")	75 x 80 mm (2-5/8"~3"x3-5/8")	9.5 mm (3/8")
2	115 x 159 mm (4-1/2"x 6-1/4")	75 x 130 mm (2-7/16"~3-3/8" x4-15/16"~5-1/4")	12.7 mm (1/2")



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
93mm x 28mm (3-21/32" x 1-3/32")	175 kgs(385 lbs)	Cast Iron	1124-04-14-1	1124-04-14-2	—	Ball Bearing	138.5mm	Swivel 71.5mm
100mm x 32mm (4" x 1-1/4")	200 kgs(440 lbs)	Nylon	1124-04-07-1	1124-04-07-2	1124-04-07-4	Ball Bearing	142mm (5-5/8")	Swivel 75mm Swivel W/Side Brake 75mm Swivel W/Center lock 115mm
	150 kgs(330 lbs)	CPD	1124-04-49-1	1124-04-49-2	1124-04-49-4			
100mm x 34mm (4" x 1-1/3")	200 kgs(440 lbs)	PU on Cast	1124-04-33-1	1124-04-33-2	1124-04-33-4			
	300 kgs(660 lbs)	QPU	1124-04-80-1	1124-04-80-2	1124-04-80-4			
	150 kgs(330 lbs)	NBR Rubber on Cast	1124-04-04-1	1124-04-04-2	1124-04-04-4			
	150 kgs(330 lbs)	Non-marking Rubber on Cast	1124-04-11-1	1124-04-11-2	1124-04-11-4			
100mm x 35mm (4" x 1-1/8")	150 kgs(330 lbs)	Rubber on Cast	1124-04-03-1	1124-04-03-2	1124-04-03-4			
100mm x 36mm (4" x 1-7/16")	325 kgs(715 lbs)	QPU on AL Core (Round)	1124-04-87-1	1124-04-87-2	1124-04-87-4			
100mm x 37.5mm (4" x 1-1/2")	140 kgs(308 lbs)	W Resolute	1124-04-64-1	1124-04-64-2	1124-04-64-4			
100mm x 40mm (4" x 1-9/16")	350 kgs(770 lbs)	QPU on AL Core (Round)	1124-04(40)-87-1	1124-04(40)-87-2	1124-04(40)-87-4			
122mm x 36mm (4-13/16" x 1-7/16")	250 kgs(550 lbs)	Cast Iron	1124-05-14-1	1124-05-14-2	—	Ball Bearing	165.5mm	Swivel 91.5mm
125mm x 37.5mm (5" x 1-1/2")	250 kgs(550 lbs)	W Resolute	1124-05-64-1	1124-05-64-2	1124-05-64-4	Ball Bearing	167mm (6-1/2")	Swivel 93mm Swivel W/Side Brake 93mm Swivel W/Center lock 112mm
125mm x 40mm (5" x 1-9/16")	250 kgs(550 lbs)	PU on Cast	1124-05-33-1	1124-05-33-2	1124-05-33-4			
	350 kgs(770 lbs)	QPU	1124-05-80-1	1124-05-80-2	1124-05-80-4			
	350 kgs(770 lbs)	QPU on AL Core (Round)	1124-05-87-1	1124-05-87-2	1124-05-87-4			
	250 kgs(550 lbs)	EPU	1124-05-78-1	1124-05-78-2	1124-05-78-4			
	300 kgs(660 lbs)	EQPU	1124-05-81-1	1124-05-81-2	1124-05-81-4			
	200 kgs(440 lbs)	Rubber on Cast	1124-05-03-1	1124-05-03-2	1124-05-03-4			
	200 kgs(440 lbs)	NBR Rubber on Cast	1124-05-04-1	1124-05-04-2	1124-05-04-4			
	200 kgs(440 lbs)	Non-marking Rubber on Cast	1124-05-11-1	1124-05-11-2	1124-05-11-4			
125mm x 41mm (5" x 1-5/8")	250 kgs(550 lbs)	Nylon	1124-05-07-1	1124-05-07-2	1124-05-07-4			
	200 kgs(440 lbs)	CPD	1124-05-49-1	1124-05-49-2	1124-05-49-4			
138mm x 42mm (5-7/16" x 1-5/8")	300 kgs(660 lbs)	Cast Iron	1124-06-14-1	1124-06-14-2	—	Ball Bearing	184mm	Swivel 104mm
150mm x 37.5mm (6" x 1-1/2")	180 kgs(396 lbs)	W Resolute	1124-06-64-1	1124-06-64-2	1124-06-64-4	Ball Bearing	190mm (7-1/2")	Swivel 110mm Swivel W/Side Brake 110mm Swivel W/Center lock 160mm
150mm x 40mm (6" x 1-9/16")	250 kgs(550 lbs)	NBR Rubber on Cast	1124-06-04-1	1124-06-04-2	1124-06-04-4			
	250 kgs(550 lbs)	Non-marking Rubber on Cast	1124-06-11-1	1124-06-11-2	1124-06-11-4			
	350 kgs(770 lbs)	Nylon	1124-06-07-1	1124-06-07-2	1124-06-07-4			
	250 kgs(550 lbs)	CPD	1124-06-49-1	1124-06-49-2	1124-06-49-4			
	350 kgs(770 lbs)	WMRC	1124-06-45-1	1124-06-45-2	1124-06-45-4			
	250 kgs(550 lbs)	WCPD	1124-06-79-1	1124-06-79-2	1124-06-79-4			



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
150mm x 42mm (6" x 1-5/8")	350 kgs(770 lbs)	PU on Cast	1124-06-33-1	1124-06-33-2	1124-06-33-4	Ball Bearing	190mm (7-1/2")	Swivel 110mm Swivel W/Side Brake 110mm Swivel W/Center lock 160mm
	400 kgs(880 lbs)	QPU	1124-06-80-1	1124-06-80-2	1124-06-80-4			
	350 kgs(770 lbs)	EPU	1124-06-78-1	1124-06-78-2	1124-06-78-4			
	400 kgs(880 lbs)	EQPU	1124-06-81-1	1124-06-81-2	1124-06-81-4			
	400 kgs(880 lbs)	QPU on AL Core (Round)	1124-06-87-1	1124-06-87-2	1124-06-87-4			
150mm x 45.5mm (6" x 1-13/16")	220 kgs(485 lbs)	Rubber on Cast	1124-06-03-1	1124-06-03-2	1124-06-03-4			
200mm x 44mm (8" x 1-3/4")	300 kgs(660 lbs)	NBR Rubber on Cast	1124-08-04-1	1124-08-04-2	1124-08-04-4	Ball Bearing	240mm (9-1/2")	Swivel 145mm Swivel W/Side Brake 145mm Swivel W/Center lock 162.5mm
	300 kgs(660 lbs)	Non-marking Rubber on Cast	1124-08-11-1	1124-08-11-2	1124-08-11-4			
200mm x 45mm (8" x 1-13/16")	350 kgs(770 lbs)	Cast Iron	1124-08-14-1	1124-08-14-2	1124-08-14-4			
200mm x 50mm (8" x 2")	400 kgs(880 lbs)	PU on Cast	1124-08-33-1	1124-08-33-2	1124-08-33-4			
	400 kgs(880 lbs)	QPU	1124-08-80-1	1124-08-80-2	1124-08-80-4			
	400 kgs(880 lbs)	EPU	1124-08-78-1	1124-08-78-2	1124-08-78-4			
	400 kgs(880 lbs)	EQPU	1124-08-81-1	1124-08-81-2	1124-08-81-4			
	260 kgs(570 lbs)	Rubber on Cast	1124-08-03-1	1124-08-03-2	1124-08-03-4			
	300 kgs(660 lbs)	NBR Rubber on Cast	1124-08-04-1	1124-08-04-2	1124-08-04-4			
	300 kgs(660 lbs)	Non-marking Rubber on Cast	1124-08-11-1	1124-08-11-2	1124-08-11-4			
	400 kgs(880 lbs)	Nylon	1124-08-07-1	1124-08-07-2	1124-08-07-4			
	300 kgs(660 lbs)	CPD	1124-08-49-1	1124-08-49-2	1124-08-49-4			
	180 kgs(396 lbs)	Resolute	1124-08-53-1	1124-08-53-2	1124-08-53-4			
	400 kgs(880 lbs)	WMRC	1124-08-45-1	1124-08-45-2	1124-08-45-4			
	300 kgs(660 lbs)	WCPD	1124-08-79-1	1124-08-79-2	1124-08-79-4			
	400 kgs(880 lbs)	QPU on AL Core (Round)	1124-08-87-1	1124-08-87-2	1124-08-87-4			
400 kgs(880 lbs)	QPU on AL Core (Flat)	1124-08-87-1	1124-08-87-2	1124-08-87-4				