



# 1126 Series

## Light Duty General Purposes Caster (European Style)

○ Light-medium duty, for various logistic equipments. Special yoke design with easy swivel.

Load  
70 -120 kg



### » Wheel Options

PU on PP Core



TPR on PP Core



Nylon



WMRC



WPP



Ball Bearing

Ball Bearing

Plain Bearing



WRPR



NPPR



Rubber on Aluminum Core



Rubber



PP



E-Conductive



Hi-temp



W Resolute



Resolute



WHDR



CPD



Blue Resilient Rubber Wheel



TPR on PP Core



QPU on AL Core










Resolute

### » TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	85 x 105 mm (3-5/16" x 4-1/8")	60 x 80 mm 2-3/8" x 3-1/8" (European Plate)	8 mm (5/16")



 Diameter*Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
100mmx32mm (4"x1-1/4")	100kgs (220lbs)	PU on PP Core	1126-04-31-1	1126-04-31-2	--	Ball Bearing	128mm (5-1/16")	Swivel 90mm
	100kgs (220lbs)	TPR on PP Core	1126-04-75-1	1126-04-75-2	--	Plain Bearing		
	100kgs (220lbs)	Resolute	1126-04-68-1	1126-04-68-2	--			
	80kgs (176lbs)	E-Conductive	1126-04-17-1	1126-04-17-2	--			
	100kgs (220lbs)	WMRC	1126-04-45-1	1126-04-45-2	--			
	100kgs (220lbs)	WPP	1126-04-46-1	1126-04-46-2	--			
	100kgs (220lbs)	WPPR	1126-04-47-1	1126-04-47-2	--			
	100kgs (220lbs)	W Resolute	1126-04-48-1	1126-04-48-2	--			
	100kgs (220lbs)	WHDR	1126-04-66-1	1126-04-66-2	--			
	100kgs (220lbs)	Rubber on Aluminum Core	1126-04-22-1	1126-04-22-2	--			
	120kgs (264lbs)	QPU on AL Core	1126-04-87-1	1126-04-87-2	--			
	70kgs (154lbs)	NPPR	1126-04-67-1	1126-04-67-2	--			
	100kgs (220lbs)	Nylon	1126-04-07-1	1126-04-07-2	--			
	80kgs (176lbs)	Rubber	1126-04-06-1	1126-04-06-2	--	Plain Bearing		
	90kgs (198lbs)	PP	1126-04-29-1	1126-04-29-2	--			
	100kgs (220lbs)	Hi-temp	1126-04-25-1	1126-04-25-2	--			
100mmx36mm (4"x1-1/2")	100 kgs (220 lbs)	CPD	1126-04-71-1	1126-04-71-2	--	Ball Bearing	128mm (5-1/16")	Swivel 90mm
	100 kgs (220 lbs)	Blue Resilient Rubber Wheel	1126-04-50-1	1126-04-50-2	--			
	120kgs (264lbs)	TPR on PP Core	1126-04-77-1	1126-04-77-2	--			
	120kgs (264lbs)	Resolute	1126-04-76-1	1126-04-76-2	--			
	120kgs (264lbs)	QPU on AL Core	1126-04-87-1	1126-04-87-2	--			
125mmx32mm (5"x1-1/4")	120kgs (264lbs)	PU on PP Core	1126-05-31-1	1126-05-31-2	--	Ball Bearing	149.5mm (5-15/16")	Swivel 91mm
	110kgs (240lbs)	TPR on PP Core	1126-05-75-1	1126-05-75-2	--	Plain Bearing		
	120kgs (264lbs)	Resolute	1126-05-68-1	1126-05-68-2	--			
	90kgs (198lbs)	E-Conductive	1126-05-17-1	1126-05-17-2	--			
	120kgs (264lbs)	WMRC	1126-05-45-1	1126-05-45-2	--			
	120kgs (264lbs)	WPP	1126-05-46-1	1126-05-46-2	--			
	110kgs (240lbs)	WPPR	1126-05-47-1	1126-05-47-2	--			
	120kgs (264lbs)	W Resolute	1126-05-48-1	1126-05-48-2	--			
	120kgs (264lbs)	WHDR	1126-05-66-1	1126-05-66-2	--			
	120kgs (264lbs)	QPU on AL Core	1126-05-87-1	1126-05-87-2	--			
	120kgs (264lbs)	Nylon	1126-05-07-1	1126-05-07-2	--			
	90kgs (198lbs)	Rubber	1126-05-06-1	1126-05-06-2	--	Plain Bearing		
	100kgs (220lbs)	PP	1126-05-29-1	1126-05-29-2	--			
125mmx36mm (5"x1-1/2")	120kgs (264 lbs)	CPD	1126-05-71-1	1126-05-71-2	--	Ball Bearing	149.5mm (5-15/16")	Swivel 91mm
	120kgs (264 lbs)	Blue Resilient Rubber Wheel	1126-05-50-1	1126-05-50-2	--			
	120kgs (264 lbs)	TPR on PP Core	1126-05-77-1	1126-05-77-2	--			
	120kgs (264 lbs)	Resolute	1126-05-76-1	1126-05-76-2	--			