



1149 Series 中型 美國抗衝擊系列

- 採用高耐磨尼龍製成，輪寬較大是小輪中負載高的系列，具抗衝性能，在搬運過程可避免腳架變形扭曲，適合荷重高、移動較少的商業機械設備。其中大底板附支撐腳的款式，可增大荷重，其支撐腳可調整高度並可隨意穩固地停放台車。
- Wheel made of synthetic material with excellent abrasion resistance. Wide tread withstands heavy loads, suitable for business machines equipment and computer racks. Kingpinless design with fabricated steel frame for greater impact resistance to avoid distortions under heavy load. Item with floor lock is designed for extra heavy load and immobility function. Height is also adjustable for model with floor lock.

載重 Load
300-350kg



▶▶ 特色區 Features



無錐釘設計
Kingpinless

▶▶ 輪子選項 Wheel Options



尼龍輪
Nylon



滾珠軸承
Ball Bearing

▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
2-1/2" 美國輪 2-1/2"x1-15/16"	70 x 95 mm (2-3/4"x 3-3/4")	45 x 75 mm (1-3/4"x 3")	8 mm (5/16")
2-1/2" 美國輪大底板 2-1/2"x 1-15/16" Caster with floor Lock	120 x 120 mm (4-23/32"x 4-23/32")	95 x 95 mm (3-3/4"x 3-3/4")	10 mm (3/8")
3" 美國輪 3"x1-15/16"	80 x 105 mm (3-1/8"x 4-1/8")	58 x 80 mm (2-9/32"x 3-1/8")	8 mm (5/16")
3" 美國輪大底板 3"x1-15/16" Caster with floor Lock	120 x 120 mm (4-23/32"x 4-23/32")	95 x 95 mm (3-3/4"x 3-3/4")	10 mm (3/8")

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
64mm×49mm (2-1/2"x1-15/16")	300 kgs (660 lbs)	尼龍輪 Nylon	1149-25-07-1	1149-25-07-2	1149-25-07-4	滾珠軸承 Ball Bearing	89mm (3-1/2")	活動59mm 煞車75mm Swivel 59mm Swivel W/Brake 75mm
75mm×49mm (3"x1-15/16")	350 kgs (770 lbs)	尼龍輪 Nylon	1149-03-07-1	1149-03-07-2	1149-03-07-4	滾珠軸承 Ball Bearing	101mm (4")	活動71mm 煞車81mm Swivel 71mm Swivel W/Brake 81mm