



1202 Series Pneumatic Wheel

○ Heavy-duty with a cushion ride, ideal for uneven ground condition.

Load
100-200 kg



Wheel Options



Pneumatic with painted steel rim



Pneumatic with plastic rim




Pneumatic with plated steel rim



Solid Rubber wheel with painted steel rim



Solid Rubber wheel with plated steel rim



Size	Rim	Hub length	Load	Item No.	Bearing	輪子樣式
8"	Steel rim (painted)	95 mm (3" Centered)	100 kg (220 lbs)	1202-08-SA	1/2", 3/4", 5/8" Ball Bearing 3/4" Roller Bearing	
	Steel rim (zinc-plated)			1202-08-SB		
	Plastic rim	57 mm (2-1/4" Offset)		1202-08-P		
10"	Steel rim (painted)	95 mm (3" Centered)	150 kg (330 lbs)	1202-10-SA	1/2", 3/4", 5/8" Ball Bearing 3/4" Roller Bearing	
	Steel rim (zinc-plated)			1202-10-SB		
	Plastic rim	57 mm (2-1/4" Offset)		1202-10-P		
11"	Steel rim (painted)	95 mm (3" Centered)	170 kg (375 lbs)	1202-11-SA	1/2", 3/4", 5/8" Ball Bearing	
	Steel rim (zinc-plated)			1202-11-SB		
	Plastic rim			1202-11-P		
12"	Steel rim (painted)	100 mm (4" Centered)	190 kg (415 lbs)	1202-12-SA	1/2", 3/4", 5/8" Ball Bearing	
	Steel rim (zinc-plated)			1202-12-SB		
	Plastic rim			1202-12-P		
14"	Steel rim (painted)	100 mm (4" Centered)	200 kg (440 lbs)	1202-14-SA	1/2", 3/4", 5/8" Ball Bearing	
	Steel rim (zinc-plated)			1202-14-SB		
	Plastic rim			1202-14-P		