



# 1204 Series Semi-Pneumatic & Solid Rubber Wheel

- Good for lawn mowers, wooden machinery, generators, two-wheeled carts, etc.
- Various Tread patterns available: Rib, Diamond, and Gear
- Rims can be plastic or steel (painted or zinc-plated)
- OEM requests and tailored-made wheels in all sizes are welcome.



## Solid Rubber Wheel

	Wheel diameter	Width	Load (lbs.)	Hub Length	Tread Pattern	Item No.	Bearing
Steel Rim	6"	1-1/2"	60 kgs (130 lbs)	centered: 1-3/4"	Rib	1204SS-6-15-C-R	1/2" , 5/8", 3/4" hole flanged ball bearing
				offset: 1-3/8"		1204SS-6-15-OFF-R	
	7"	1-1/2"	70 kgs (150 lbs)	centered: 2"	Rib	1204SS-7-15-C-R	1/2" , 5/8", 3/4" hole flanged ball bearing
				offset: 1-3/8"		1204SS-7-15-OFF-R	
	8"	1-3/4"	70 kgs (150 lbs)	centered: 2"	Rib	1204SS-8-175-C-R	1/2" , 5/8", 3/4" hole flanged ball bearing
				offset: 1-3/8"		1204SS-8-175-OFF-R	
	10"	1-3/4"	70 kgs (150 lbs)	centered: 2"	Rib	1204SS-10-175-C-R	1/2" , 3/4" , 5/8" hole flanged ball bearing
				offset: 1-3/8"		1204SS-10-175-OFF-R	
		2-3/4"	115 kgs (250 lbs)	centered: 2"	Rib	1204SS-10-275-C-R	1/2" , 3/4" , 5/8" hole flanged ball bearing
				offset: 2-1/4"		1204SS-10-275-OFF-R	
12"	1-3/4"	70 kgs (150 lbs)	centered: 2-1/4"	Rib	1204SS-12-175-C-R	1/2" , 3/4" , 5/8" hole flanged ball bearing	
Plastic Rim	6"	1-1/2"	55 kgs (120 lbs)	centered: 1-3/4"	Rib	1204SP-6-15-C-R	1/2" bore
				offset: 1-3/8"		1204SP-6-15-OFF-R	
	7"	1-1/2"	55 kgs (120 lbs)	centered: 2"	Rib	1204SP-7-15-C-R	1/2" bore or 1/2" flanged ball bearing
				offset: 1-3/8"		1204SP-7-15-OFF-R	
	8"	1-3/4"	55 kgs (120 lbs)	centered: 2"	Rib	1204SP-8-175-C-R	1/2" bore or 1/2" flanged ball bearing
				offset: 1-3/8"		1204SP-8-175-OFF-R	
	10"	1-3/4"	65 kgs (140 lbs)	centered: 2"	Rib	1204SP-10-175-C-R	1/2" bore
				offset: 1-3/8"		1204SP-10-175-OFF-R	
		2-3/4"	100 kgs (220 lbs)	centered: 2"	Rib	1204SP-10-275-C-R	5/8" hole flanged ball bearing
				offset: 2-1/4"		1204SP-10-275-OFF-R	



## Semi-Pneumatic Rubber Wheel

	Wheel diameter	Width	Load (lbs.)	Hub Length	Tread Pattern	Item No.	Bearing
Steel Rim	6"	1-1/2"	25 kgs (50 lbs)	centered: 1-3/4"	Rib	1204HS-6-15-C-R ( Rib )	1/2" , 5/8", 3/4" hole flanged ball bearing
					Diamond	1204HS-6-15- C-D ( Diamond )	
				offset: 1-3/8"	Rib	1204HS-6-15-OFF-R ( Rib )	
					Diamond	1204HS-6-15-OFF-D( Diamond )	
	7"	1-1/2"	30 kgs (60 lbs)	centered: 2"	Rib	1204HS-7-15-C-R ( Rib )	1/2" , 5/8", 3/4" hole flanged ball bearing
					Diamond	1204HS-7-15-C-D( Diamond )	
				offset: 1-3/8"	Rib	1204HS-7-15-OFF-R ( Rib )	
					Diamond	1204HS-7-15-OFF-D( Diamond )	
	8"	1-3/4"	35 kgs (80 lbs)	centered: 2"	Rib	1204HS-8-175-C-R ( Rib )	1/2" , 5/8", 3/4" hole flanged ball bearing
					Diamond	1204HS-8-175-C-D( Diamond )	
					Gear	1204HS-8-175-C-G( Gear )	
				offset: 1-3/8"	Rib	1204HS-8-175-OFF-R ( Rib )	
					Diamond	1204HS-8-175-OFF-D( Diamond )	
					Gear	1204HS-8-175-OFF-G( Gear )	
	2-1/2"	35 kgs (80 lbs)	centered: 2"	Rib	1204HS-8-215-C-R ( Rib )	5/8" hole flanged ball bearing	
				offset: 2-1/4"	Rib		1204HS-8-215-OFF-R ( Rib )
	10"	1-3/4"	45 kgs (100 lbs)	centered: 2"	Rib	1204HS-10-175-C-R ( Rib )	1/2" , 3/4", 5/8" hole flanged ball bearing
					Diamond	1204HS-10-175-C-D( Diamond )	
				offset: 1-3/8"	Rib	1204HS-10-175-OFF-R ( Rib )	
					Diamond	1204HS-10-175-OFF-D( Diamond )	
2-3/4"		70 kgs (160 lbs)	centered: 2"	Rib	1204HS-10-275-C-R ( Rib )	1/2" , 3/4", 5/8" hole flanged ball bearing	
				offset: 2-1/4"	Rib		1204HS-10-275-OFF-R ( Rib )
3" (260*85)		90 kgs (200 lbs)	centered: 2"	Gear	1204HS-10-30-C-G( Gear )	1/2" , 3/4", 5/8" hole flanged ball bearing	
				offset: 2-1/4"	Gear		1204HS-10-30-OFF-G( Gear )
12"	1-3/4"	35 kgs (80 lbs)	centered: 2-1/4"	Rib	1204HS-12-175-C-R ( Rib )	1/2" , 3/4", 5/8" hole flanged ball bearing	
Plastic Rim	6"	1-1/2"	25 kgs (50 lbs)	centered: 1-3/16"	Rib	1204HP-6-15-C-R ( Rib )	1/2" bore
					Diamond	1204HP-6-15-C-D( Diamond )	
				offset: 1-3/8"	Rib	1204HP-6-15-OFF-R ( Rib )	
					Diamond	1204HP-6-15-OFF-D( Diamond )	
	7"	1-1/2"	30 kgs (60 lbs)	centered: 2"	Rib	1204HP-7-15-C-R ( Rib )	1/2" bore or 1/2" flanged ball bearing
					Diamond	1204HP-7-15-C-D( Diamond )	
				offset: 1-3/8"	Rib	1204HP-7-15-OFF-R ( Rib )	
					Diamond	1204HP-7-15-OFF-D( Diamond )	
	8"	1-3/4"	35 kgs (80 lbs)	centered: 2"	Rib	1204HP-8-175-C-R ( Rib )	1/2" bore or 1/2" flanged ball bearing
					Diamond	1204HP-8-175- C-D( Diamond )	
					Gear	1204HP-8-175-C-G( Gear )	
				offset: 1-3/8"	Rib	1204HP-8-175-OFF-R ( Rib )	
					Diamond	1204HP-8-175- OFF-D( Diamond )	
					Gear	1204HP-8-175-OFF-G( Gear )	
	2-1/2"	35 kgs (80 lbs)	centered: 2"	Rib	1204HP-8-215-C-R ( Rib )	5/8" hole flanged ball bearing	
				offset: 2-1/4"	Rib		1204HP-8-215-OFF-R ( Rib )
	10"	1-3/4"	45 kgs (100 lbs)	centered: 2"	Rib	1204HP-10-175-C-R ( Rib )	1/2" bore
					Diamond	1204HP-10-175-C-D( Diamond )	
				offset: 1-3/8"	Rib	1204HP-10-175-OFF-R ( Rib )	
					Diamond	1204HP-10-175-OFF-D( Diamond )	
2-3/4"	70 kgs (160 lbs)	centered: 2"	Rib	1204HP-10-275-C-R ( Rib )	1/2" , 3/4", 5/8" hole flanged ball bearing		
			offset: 2-1/4"	Rib		1204HP-10-275-OFF-R ( Rib )	