



# 1102 Series 重型

## B型系列 B Type Caster

- 超高負載且轉動靈活，適用於汽車廠、汽車裝配廠、玻璃廠、紡織廠等負載重的車間，另可附防纏絲及防塵蓋，屬得勝專利產品，可以有效防止腳輪因灰塵或纏絲而無法轉動，提高腳輪使用壽命。
- Swivel easily under heavy load; ideal for heavy-duty workshop trucks in automobile, glass, textile industries, etc. Patented thread guards and dust covers prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.

載重 Load  
200-2500 kg




### 特色區 Features




中煞  
Center Lock Brake



輪子可附防纏絲蓋(供選擇)  
Thread guard specially  
for textile industry(optional)



輪子可附金屬防塵蓋(供選擇)  
Metal Thread Guard(optional)



AK煞  
Swivel W/Center lock(AK type)  
另輪子可附塑膠防塵蓋(供選擇)  
Plastic Thread Guard(optional)



PU輪面可以變化硬度  
Different PU  
tread hardness available

### 輪子選項 Wheel Options



鐵芯聚氨酯  
PU on Cast



三星輪  
Rubber on Cast




鐵芯NBR橡膠輪  
NBR Rubber on Cast



尼龍輪  
Nylon



WMRC輪  
WMRC



QPU輪  
QPU



滾珠軸承  
Ball Bearing



APU輪  
PU on AL Core



CPD輪  
CPD



銑輪  
Cast Iron



環保NBR橡膠輪  
Non-marking Rubber on Cast



EQPU輪  
EQPU



鐵芯聚氨酯(2050A/2050B)  
PU on Cast(2050A/2050B)



ZQPU輪(雙輪)  
ZQPU(Dual Wheels)



VPU輪  
VPU



EPU輪  
EPU



VQPU輪  
VQPU



鐵芯VXPU  
VXPU on Iron Core



鋁芯QQ橡膠輪  
Recilcent rubber on AL Core



環保牽引NBR  
Non - marking NBR Rubber  
on Cast



鋁芯AQPU  
QPU on AL Core



▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4"	90 x 120 mm (3-17/32" x 4-23/32")	60 x 90 mm (2-3/8" x 3-17/32")	11 mm (7/16")
5,6,8"	110 x 140 mm (4-11/32" x 5-1/2")	75 x 110 mm(常規標準底板) (2-15/16" x 4-11/32")	12 mm (1/2")
	110 x 140 mm (4-11/32" x 5-1/2")	80 x 105 mm(歐洲底板) (3-5/32" x 4-1/8")	12 mm (1/2")
	130 x 130 mm (5-1/8" x 5-1/8")	105 x 105 mm (4-1/8" x 4-1/8")	9 mm (3/8")
	130 x 130 mm (5-1/8" x 5-1/8")	105 x 105 mm (4-1/8" x 4-1/8")	12 mm (1/2")
	130 x 165 mm (5-1/8" x 6-1/2")	100 x 130 mm (3-15/16" x 5-1/8")	12 mm (1/2")
	114 x 159 mm (4-1/2" x 6-1/4")	73.8 x 129.4 mm (2-29/32" x 5-3/32")	12 mm (1/2")
10"	130 x 167 mm (5-1/8" x 6-9/16")	85 x 140 mm(大陸常規底板) (3-11/32" x 5-1/2")	12 mm (1/2")
	110 x 175 mm (4-11/32" x 6-7/8")	65 x 140 mm(台灣常規底板) (2-9/16" x 5-1/2")	12 mm (1/2")
12"	130 x 167 mm (5-1/8" x 6-9/16")	85 x 140 mm (3-11/32" x 5-1/2")	12 mm (1/2")

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	煞車 Brake			
93mm x 28mm (3-21/32"x1-3/32")	400 kgs (880 lbs)	鑄輪 Cast Iron	1102-04-14-1	1102-04-14-2	1102-04-14-4	滾珠軸承 Ball Bearing	143.5mm (5-21/32")	活動 87mm Swivel 87mm
100mm x 32mm (4"x1-1/4")	250 kgs (550 lbs)	尼龍輪 Nylon	1102-04-07-1	1102-04-07-2	1102-04-07-4	滾珠軸承 Ball Bearing	147mm (5-25/32")	活動 92 mm Swivel 92mm  AK煞 148 mm Swivel W/AK Lock Brake 148mm
	200 kgs (440 lbs)	CPD輪 CPD	1102-04-49-1	1102-04-49-2	1102-04-49-4			
100mm x 34mm (4"x1-3/8")	335 kgs (735 lbs)	QPU輪(圓弧) QPU (Round)	1102-04-80-1	1102-04-80-2	1102-04-80-4			
	385 kgs (845 lbs)	QPU輪(平面) QPU (Flat)	1102-04-80-1	1102-04-80-2	1102-04-80-4			
100mm x 36mm (4"x1-7/16")	250 kgs (550 lbs)	鐵芯聚氨酯 PU on Cast	1102-04-33-1	1102-04-33-2	1102-04-33-4			
	200 kgs (440 lbs)	三星輪 Rubber on Cast	1102-04-03-1	1102-04-03-2	1102-04-03-4			
	250 kgs (550 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-04-108-1	1102-04-108-2	1102-04-108-4			
	300 kgs (660 lbs)	鋁芯AQPUL輪(圓弧) QPU on AL Core (Round)	1102-04-87-1	1102-04-87-2	1102-04-87-4			
100mm x 38mm (4"x1-1/2")	200 kgs (440 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-04-04-1	1102-04-04-2	1102-04-04-4			
	200 kgs (440 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-04-11-1	1102-04-11-2	1102-04-11-4			
	200 kgs (440 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-04-90-1	1102-04-90-2	1102-04-90-4			
100mm x 40mm (4"x1-9/16")	275 kgs (600 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-04-108-1	1102-04-108-2	1102-04-108-4			
	200 kgs (440 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1102-04-89-1	1102-04-89-2	1102-04-89-4			
	325 kgs (715 lbs)	鋁芯AQPUL輪(圓弧) QPU on AL Core (Round)	1102-04-87-1	1102-04-87-2	1102-04-87-4			
100mm x 46.5mm (4"x1-13/16")	335 kgs (735 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1102-04-101-1	1102-04-101-2	1102-04-101-4			
122mm x 36.5mm (4-13/16"x1-7/16")	600 kgs (1320 lbs)	鑄輪 Cast Iron	1102-05-14-1	1102-05-14-2	1102-05-14-4	滾珠軸承 Ball Bearing	168.5mm (6-5/8")	活動 103 mm Swivel 103mm



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	煞車 Brake			
125mm x 40mm (5" x 1-9/16")	340 kgs (750 lbs)	鐵芯聚氨酯 PU on Cast	1102-05-33-1	1102-05-33-2	1102-05-33-4	滾珠軸承 Ball Bearing	170mm (6-11/16")	活動 107 mm Swivel 107mm  AK煞 158 mm Swivel W/AK Lock Brake 158mm
	220 kgs (485 lbs)	三星輪 Rubber on Cast	1102-05-03-1	1102-05-03-2	1102-05-03-4			
	300 kgs (660 lbs)	尼龍輪 Nylon	1102-05-07-1	1102-05-07-2	1102-05-07-4			
	300 kgs (660 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-05-108-1	1102-05-108-2	1102-05-108-4			
	350 kgs (770 lbs)	鋁芯AQP輪(圓弧) QPU on AL Core (Round)	1102-05-87-1	1102-05-87-2	1102-05-87-4			
	250 kgs (550 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-05-04-1	1102-05-04-2	1102-05-04-4			
	250 kgs (550 lbs)	CPD輪 CPD	1102-05-49-1	1102-05-49-2	1102-05-49-4			
	250 kgs (550 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-05-11-1	1102-05-11-2	1102-05-11-4			
	250 kgs (550 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-05-90-1	1102-05-90-2	1102-05-90-4			
	300 kgs (660 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1102-05-89-1	1102-05-89-2	1102-05-89-4			
	450 kgs (990 lbs)	QPU輪(圓弧) QPU (Round)	1102-05-80-1	1102-05-80-2	1102-05-80-4			
	500 kgs (1100 lbs)	QPU輪(平面) QPU (Flat)	1102-05-80-1	1102-05-80-2	1102-05-80-4			
	340 kgs (750 lbs)	EPU輪(圓弧) EPU (Round Shape)	1102-05-78-1	1102-05-78-2	1102-05-78-4			
	390 kgs (860 lbs)	EPU輪(平面) EPU (Flat Shape)	1102-05-78-1	1102-05-78-2	1102-05-78-4			
	450 kgs (990 lbs)	EQPU輪(圓弧) EQPU (Round Shape)	1102-05-81-1	1102-05-81-2	1102-05-81-4			
	500 kgs (1100 lbs)	EQPU輪(平面) EQPU (Flat Shape)	1102-05-81-1	1102-05-81-2	1102-05-81-4			
125mm x 50mm (5" x 2")	400 kgs (880 lbs)	APU輪(平面) PU on AL Core (Flat)	1102-05-108-1	1102-05-108-2	1102-05-108-4	滾珠軸承 Ball Bearing	170mm (6-11/16")	活動 107 mm Swivel 107mm  AK煞 158 mm Swivel W/AK Lock Brake 158mm
	450 kgs (990 lbs)	鋁芯AQP輪(平面) QPU on AL Core (Flat)	1102-05-87-1	1102-05-87-2	1102-05-87-4			
125mm x 51mm (5" x 2")	450 kgs (990 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1102-05-101-1	1102-05-101-2	1102-05-101-4	滾珠軸承 Ball Bearing	191mm (7-17/32")	活動 111 mm Swivel 111mm
138mm x 36.5mm (5-7/16" x 1-7/16")	700 kgs (1540 lbs)	銑輪 Cast Iron	1102-06-14-1	1102-06-14-2	—	滾珠軸承 Ball Bearing	191mm (7-17/32")	活動 111 mm Swivel 111mm
150mm x 40mm (6" x 1-9/16")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-06-04-1	1102-06-04-2	1102-06-04-4	滾珠軸承 Ball Bearing	197mm (7-3/4")	活動 119 mm Swivel 119mm  AK煞 160 mm Swivel W/AK Lock Brake 160mm
	400 kgs (880 lbs)	尼龍輪 Nylon	1102-06-07-1	1102-06-07-2	1102-06-07-4			
	350 kgs (770 lbs)	CPD輪 CPD	1102-06-49-1	1102-06-49-2	1102-06-49-4			
	300 kgs (660 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-06-11-1	1102-06-11-2	1102-06-11-4			
	300 kgs (660 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-06-90-1	1102-06-90-2	1102-06-90-4			
	350 kgs (770 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1102-06-89-1	1102-06-89-2	1102-06-89-4			
	400 kgs (880 lbs)	WMRC輪 WMRC	1102-06-45-1	1102-06-45-2	1102-06-45-4			



輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	煞車 Brake			
150mm x 42mm (6"x1-5/8")	410 kgs (900 lbs)	鐵芯聚氨酯 PU on Cast	1102-06-33-1	1102-06-33-2	1102-06-33-4	滾珠軸承 Ball Bearing	197mm (7-3/4")	活動 119 mm Swivel 119mm  AK煞 160 mm Swivel W/AK Lock Brake 160mm
	400 kgs (880 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-06-108-1	1102-06-108-2	1102-06-108-4			
	450 kgs (990 lbs)	鋁芯AQPUP輪(圓弧) QPU on AL Core (Round)	1102-06-87-1	1102-06-87-2	1102-06-87-4			
	550 kgs (1200 lbs)	QPU輪(圓弧) QPU (Round)	1102-06-80-1	1102-06-80-2	1102-06-80-4			
	600 kgs (1320 lbs)	QPU輪(平面) QPU(Flat)	1102-06-80-1	1102-06-80-2	1102-06-80-4			
	500 kgs (1100 lbs)	VPU輪(圓弧) VPU (Round)	1102-06-82-1	1102-06-82-2	1102-06-82-4			
	670 kgs (1475 lbs)	VQPU輪(圓弧) VQPU (Round Shape)	1102-06-83-1	1102-06-83-2	1102-06-83-4			
	800 kgs (1760 lbs)	鐵芯VXPU輪(圓弧) XPU on Iron Core (Round)	1102-06-91-1	1102-06-91-2	1102-06-91-4			
	410 kgs (900 lbs)	EPU輪(圓弧) EPU (Round)	1102-06-78-1	1102-06-78-2	1102-06-78-4			
	460 kgs (1010 lbs)	EPU輪(平面) EPU (Flat)	1102-06-78-1	1102-06-78-2	1102-06-78-4			
	550 kgs (1200 lbs)	EQPU輪(圓弧) EQPU (Round)	1102-06-81-1	1102-06-81-2	1102-06-81-4			
	600 kgs (1320 lbs)	EQPU輪(平面) EQPU (Flat)	1102-06-81-1	1102-06-81-2	1102-06-81-4			
150mm x 45.5mm (6"x1-13/16")	260 kgs (570 lbs)	三星輪 Rubber on Cast	1102-06-03-1	1102-06-03-2	1102-06-03-4			
150mm x 50mm (6" x 2")	450 kgs (990 lbs)	APU輪(平面) PU on AL Core (Flat)	1102-06(50)-108-1	1102-06(50)-108-2	1102-06(50)-108-4			
	500 kgs (1100 lbs)	鋁芯AQPUP輪(平面) QPU on AL Core (Flat)	1102-06(50)-87-1	1102-06(50)-87-2	1102-06(50)-87-4			
150mm x 51mm	550 kgs (1210 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1102-06-101-1	1102-06-101-2	1102-06-101-4			
180mm x 44mm (7" x 1-3/4")	450 kgs (990 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-07-108-1	1102-07-108-2	1102-07-108-4			
	600 kgs (1320 lbs)	鋁芯AQPUP輪(圓弧) QPU on AL Core (Round)	1102-07-87-1	1102-07-87-2	1102-07-87-4			
180mm x 50mm (7" x 2")	450 kgs (990 lbs)	鐵芯聚氨酯 PU on Cast	1102-07-33-1	1102-07-33-2	1102-07-33-4	滾珠軸承 Ball Bearing	238mm (9-3/8")	活動 154 mm Swivel 154mm  AK煞 179 mm Swivel W/AK Lock Brake 179mm
	600 kgs (1320 lbs)	QPU輪(圓弧) QPU(Round)	1102-07-80-1	1102-07-80-2	1102-07-80-4			
	650 kgs (1430 lbs)	VPU輪(圓弧) VPU (Round)	1102-07-82-1	1102-07-82-2	1102-07-82-4			
	650 kgs (1430 lbs)	鐵芯VXPU輪(圓弧) VXPU on Iron Core (Round)	1102-07-91-1	1102-07-91-2	1102-07-91-4			
	650 kgs (1430 lbs)	VQPU輪(圓弧) VQPU (Round Shape)	1102-07-83-1	1102-07-83-2	1102-07-83-4			
193mm x 46mm (7-3/5"x1-13/16")	300 kgs (660 lbs)	三星輪 Rubber on Cast	1102-08-03-1	1102-08-03-2	—	滾珠軸承 Ball Bearing	244.5mm (9-5/8")	活動 159 mm Swivel 159mm
200mm x 44mm (8"x1-3/4")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-08-04-1	1102-08-04-2	1102-08-04-4	滾珠軸承 Ball Bearing	248mm (9-3/4")	活動 164 mm Swivel 164mm  AK煞 184 mm Swivel W/AK Lock Brake 184mm
	350 kgs (770 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-08-11-1	1102-08-11-2	1102-08-11-4			
	350 kgs (770 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-08-90-1	1102-08-90-2	1102-08-90-4			
	400 kgs (880 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1102-08-89-1	1102-08-89-2	1102-08-89-4			
200mm x 45.5mm (8"x1-13/16")	550 kgs (1200 lbs)	純輪 Cast Iron	1102-08-14-1	1102-08-14-2	1102-08-14-4			



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	煞車 Brake			
200mm x 50mm (8" x 2")	450 kgs (990 lbs)	鐵芯聚氨酯 PU on Cast	1102-08-33-1	1102-08-33-2	1102-08-33-4	滾珠軸承 Ball Bearing	248mm (9-3/4")	活動 164 mm Swivel 164mm  AK煞 184 mm Swivel W/AK Lock Brake 184mm
	450 kgs (990 lbs)	尼龍輪 Nylon	1102-08-07-1	1102-08-07-2	1102-08-07-4			
	750 kgs (1650 lbs)	鐵芯聚氨酯(2050A/2050B) PU on Cast (2050A/2050B)	1102-08-62-1	1102-08-62-2	1102-08-62-4			
	400 kgs (880 lbs)	CPD輪 CPD	1102-08-49-1	1102-08-49-2	1102-08-49-4			
	450 kgs (990 lbs)	WMRC輪 WMRC	1102-08-45-1	1102-08-45-2	1102-08-45-4			
	500 kgs (1100 lbs)	APU輪(圓弧) PU on AL Core (Round)	1102-08-108-1	1102-08-108-2	1102-08-108-4			
	550 kgs (1200 lbs)	APU輪(平面) PU on AL Core (Flat)	1102-08-108-1	1102-08-108-2	1102-08-108-4			
	650 kgs (1430 lbs)	鋁芯AQPU輪(平面) QPU on AL Core (Flat)	1102-08-87-1	1102-08-87-2	1102-08-87-4			
	700 kgs (1540 lbs)	鋁芯AQPU輪(圓弧) QPU on AL Core (Round)	1102-08-87-1	1102-08-87-2	1102-08-87-4			
	670 kgs (1475 lbs)	QPU輪(圓弧) QPU (Round)	1102-08-80-1	1102-08-80-2	1102-08-80-4			
	720 kgs (1580 lbs)	QPU輪(平面) QPU (Flat)	1102-08-80-1	1102-08-80-2	1102-08-80-4			
	670 kgs (1475 lbs)	VPU輪(圓弧) VPU (Round)	1102-08-82-1	1102-08-82-2	1102-08-82-4			
	800 kgs (1760 lbs)	VQPU輪(圓弧) VQPU (Round)	1102-08-83-1	1102-08-83-2	1102-08-83-4			
	1100 kgs (2420 lbs)	鐵芯VXPU輪(圓弧) VXPU on Iron Core (Round)	1102-08-91-1	1102-08-91-2	1102-08-91-4			
	650 kgs (1430 lbs)	EPU輪(圓弧) EPU (Round Shape)	1102-08-78-1	1102-08-78-2	1102-08-78-4			
	700 kgs (1540 lbs)	EPU輪(平面) EPU (Flat Shape)	1102-08-78-1	1102-08-78-2	1102-08-78-4			
	750 kgs (1650 lbs)	EQPU輪(圓弧) EQPU (Round Shape)	1102-08-81-1	1102-08-81-2	1102-08-81-4			
	800 kgs (1760 lbs)	EQPU輪(平面) EQPU (Flat Shape)	1102-08-81-1	1102-08-81-2	1102-08-81-4			
200mm x 51mm (8" x 2")	650 kgs (1430 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1102-08-101-1	1102-08-101-2	1102-08-101-4			



輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	煞車 Brake			
250mm x 50mm (10" x 2")	400 kgs (880 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-10-04-1	1102-10-04-2	1102-10-04-4	滾珠軸承 Ball Bearing	305mm (12")	活動 175.5 mm Swivel 175.5 mm AK煞 187 mm Swivel W/AK Lock Brake 187mm
	400 kgs (880 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-10-11-1	1102-10-11-2	1102-10-11-4			
	600 kgs (1320 lbs)	鐵芯聚氨酯 PU on Cast	1102-10-33-1	1102-10-33-2	1102-10-33-4			
	800 kgs (1760 lbs)	尼龍輪 Nylon	1102-10-07-1	1102-10-07-2	1102-10-07-4			
250mm x 62mm (10"x2-7/16")	400 kgs (880 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-10(62)-04-1	1102-10(62)-04-2	1102-10(62)-04-4	滾珠軸承 Ball Bearing	305mm (12")	活動 175.5 mm Swivel 175.5 mm AK煞 187 mm Swivel W/AK Lock Brake 187mm
	400 kgs (880 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1102-10(62)-11-1	1102-10(62)-11-2	1102-10(62)-11-4			
	600 kgs (1320 lbs)	鐵芯聚氨酯 PU on Cast	1102-10-33-1	1102-10-33-2	1102-10-33-4			
	400 kgs (880 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-10-90-1	1102-10-90-2	1102-10-90-4			
	900 kgs (1980 lbs)	QPU輪(圓弧) QPU (Round)	1102-10-80-1	1102-10-80-2	1102-10-80-4			
	900 kgs (1980 lbs)	QPU輪(平面) QPU (Flat)	1102-10-80-1	1102-10-80-2	1102-10-80-4			
	1000 kgs (2200 lbs)	VPU輪(圓弧) VPU (Round)	1102-10-82-1	1102-10-82-2	1102-10-82-4			
	1200 kgs (2640 lbs)	VQPU輪(圓弧) VQPU (Round)	1102-10-83-1	1102-10-83-2	1102-10-83-4			
	1500 kgs (3300 lbs)	鐵芯VXPU輪 XPU on Iron Core	1102-10-91-1	1102-10-91-2	1102-10-91-4			
300mm x 76mm (12" x 3")	650 kgs (1430 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1102-12-04-1	1102-12-04-2	—	滾珠軸承 Ball Bearing	352mm (13-27/32")	活動 222 mm Swivel 222 mm
	550 kgs (1200 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1102-12-90-1	1102-12-90-2	—			
300mm x 90mm (12"x3-17/32")	1250 kgs (2750 lbs)	VPU輪(圓弧) VPU (Round)	1102-12-82-1	1102-12-82-2	—	滾珠軸承 Ball Bearing	352mm (13-27/32")	活動 222 mm Swivel 222 mm
	1500 kgs (3300 lbs)	VPU輪(平面) VPU (Flat)	1102-12-82-1	1102-12-82-2	—			
	1500 kgs (3300 lbs)	VQPU輪(圓弧) VQPU (Round)	1102-12-83-1	1102-12-83-2	—			
	1800 kgs (3960 lbs)	VQPU輪(平面) VQPU (Flat)	1102-12-83-1	1102-12-83-2	—			
	2000 kgs (4400 lbs)	鐵芯VXPU輪(圓弧) VXPU on Iron	1102-12-91-1	1102-12-91-2	—			
	2500 kgs (5500 lbs)	鐵芯VXPU輪(平面) VXPU on Iron Core(Flat)	1102-12-91-1	1102-12-91-2	—			
305mm x 70mm (12"x2-3/4")	1000 kgs (2200 lbs)	鐵芯聚氨酯 PU on Cast	1102-12-33-1	1102-12-33-2	—	滾珠軸承 Ball Bearing	354.5mm (13-31/32")	活動 224 mm Swivel 224 mm
	1250 kgs (2750 lbs)	QPU輪(平面) QPU (Flat)	1102-12-80-1	1102-12-80-2	—			