



1108-H Series 重型

日式輪系列(重型)

Heavy Duty General Purposes Caster (Japanese Style)

- 轉動靈活寧靜，腳架已有特殊加強，強度大幅度提升及抗衝擊，另有側剎可供選擇
- Reinforce fork design to further improve load rating and impact resistance, Side lock brake is available.

載重 Load
140-300kg



▶▶ 特色區 Features



側剎
Side Lock Brake



波盤防塵蓋
Swivel Dust Cover



輪子可附金屬防塵蓋
Metal Thread Guard

▶▶ 輪子選項 Wheel Options



鐵芯日式橡膠輪
Rubber on Steel Core



尼龍輪
Nylon



高科技耐磨聚氨酯(尼龍芯)
PU on PA Core



W全效輪
W Resolute



滾珠軸承
Ball Bearing



鋁芯AQP
QPU on AL Core



EQPU輪
EQPU



鋁芯橡膠輪
Rubber on AL Core



WMRC輪
WMRC



▶▶ 活動底板規格 SWIVEL TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4", 5", 6"活動底板 4", 5", 6" Swivel plate	101x101 mm (4"x 4")	78 x 78 mm (3-1/16"x 3-1/16")	10 mm (3/8")

▶▶ 固定底板規格 RIGID TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
5", 6"固定底板 5", 6" Rigid plate	91 x 140 mm (3-9/16"x5-1/2")	55 x 105 mm (2-1/8"x 4-1/8")	10 mm (3/8")

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
100mmx32mm (4"x1-1/4")	250 kgs(550 lbs)	尼龍輪 Nylon	-	1108-H-04-07-2	1108-H-04-07-4	滾珠軸承 Ball Bearing	138mm (5-7/16")	活動87.5mm Swivel 87.5mm 側剎87.5mm Swivel W/Side brake 87.5mm
100mmx36mm (4"x1-7/16")	270 kgs(594 lbs)	鋁芯AQPU(圓弧) QPU on AL Core (Round)	-	1108-H-04-87-2	1108-H-04-87-4			
	140 kgs(308 lbs)	W全效輪 W Resolute	-	1108-H-04-64-2	1108-H-04-64-4			
100mmx40mm (4"x1-9/16")	300 kgs(660 lbs)	鋁芯AQPU(圓弧) QPU on AL Core (Round)	-	1108-H-04-87(40)-2	1108-H-04-87(40)-4			
	200 kgs(440 lbs)	鋁芯橡膠輪 Rubber on AL Core	-	1108-H-04-22-2	1108-H-04-22-4			
125mmx38mm (5"x1-1/2")	160 kgs(352 lbs)	W全效輪 W Resolute	1108-H-05-64-1	1108-H-05-64-2	1108-H-05-64-4	滾珠軸承 Ball Bearing	168mm (6-5/8")	活動98.5mm Swivel 98.5mm 側剎98.5mm Swivel W/Side brake 98.5mm
125mmx40mm (5"x1-9/16")	300 kgs(660 lbs)	尼龍輪 Nylon	1108-H-05-07-1	1108-H-05-07-2	1108-H-05-07-4			
	300 kgs(660 lbs)	鋁芯AQPU(圓弧) QPU on AL Core (Round)	1108-H-05-87-1	1108-H-05-87-2	1108-H-05-87-4			
	300 kgs(660 lbs)	EQPU(圓弧) EQPU (Round)	1108-H-05-81-1	1108-H-05-81-2	1108-H-05-81-4			
	250 kgs(550 lbs)	鋁芯橡膠輪 Rubber on AL Core	1108-H-05-22-1	1108-H-05-22-2	1108-H-05-22-4			
150mmx38mm (6"x1-1/2")	180 kgs(396 lbs)	W全效輪 W Resolute	1108-H-06-64-1	1108-H-06-64-2	1108-H-06-64-4	滾珠軸承 Ball Bearing	191mm (7-1/2")	活動113mm Swivel 113mm 側剎113mm Swivel W/Side brake 113mm
150mmx40mm (6"x1-9/16")	160 kgs(352 lbs)	鐵芯日式橡膠輪 Rubber on Steel Core	1108-H-06-18-1	1108-H-06-18-2	1108-H-06-18-4			
	300 kgs(660 lbs)	WMRC輪 WMRC	1108-H-06-45-1	1108-H-06-45-2	1108-H-06-45-4			
	280 kgs(616 lbs)	鋁芯橡膠輪 Rubber on AL Core	1108-H-06-22-1	1108-H-06-22-2	1108-H-06-22-4			
150mmx42mm (6"x1-5/8")	300 kgs(660 lbs)	鋁芯AQPU(圓弧) QPU on AL Core (Round)	1108-H-06-87-1	1108-H-06-87-2	1108-H-06-87-4			
	300 kgs(660 lbs)	EQPU(圓弧) EQPU (Round)	1108-H-06-81-1	1108-H-06-81-2	1108-H-06-81-4			
150mmx44mm (6"x1-3/4")	200 kgs(440 lbs)	高科技耐磨聚脲脂(尼龍芯) PU on PA Core	1108-H-06-34-1	1108-H-06-34-2	1108-H-06-34-4			