



1110-2 Series

傢俱水晶輪系列

Caster For Furniture



- 腳架採用沖壓式支架結構，荷重高、轉動靈活，有中煞可供選擇，輪子搭配透明水晶輪，硬度為 80 ± 5 Shore A，主要用於辦公椅與辦公家具用輪，能適用於各種辦公室或居家地板，提供靜音與滑順的滾動。
- Pressed steel caster horn/housing designed to swivel easily under load. Good performance center brake that lock the wheel securely. Equipped with high resilient Polyurethane wheel with hardness rated at 80 ± 5 Shore A, these casters are mainly used on the office chair and other office equipments. These casters enable the chair/equipments glide smoothly on various floor surfaces.

載重 Load
30 - 50 kg



特色區 Features



插桿
Cylindrical



絲扣
Threaded



中煞
Center Brake



輪子可附防塵蓋(供選擇)
Thread Guard (optional)



多種顏色可供選擇
Various Color Available



應用區 Application

適用於各種地板 Apply to various floor surfaces



木地板
Wood Floor

環氧樹脂地板
Epoxy Floor

地毯
Carpets

水泥地板
Concrete Floor

大理石地板
Marble Floor

磁磚地板
Tile Floor

- 荷重高
- 超靜音
- 轉動靈活
- 適用於各種辦公/居家地板
- 多種顏色可供選擇
- 另有中煞可供選擇
- Swivel easily under load
- Quiet Rolling
- Smooth and easy rolling
- Apply to various floor surfaces
- The wheel comes in six colors.
- Center Lock Brake also available.



輪子選項 Wheel Options



水晶輪(內仁黑)
PU Wheel (Black)



水晶輪(內仁灰)
PU Wheel (Grey)



水晶輪(內仁白)
PU Wheel (White)



水晶輪(內仁藍)
PU Wheel (Blue)



水晶輪(內仁紅)
PU Wheel (Red)



水晶輪(內仁粉紅)
PU Wheel (Pink)



滾珠軸承
Ball Bearing








插桿規格 CYLINDRICAL STEM SPECIFICATION

編號 Suffix	插桿直徑 X 長度 Diameter x Length	孔位高度 Hole Height	孔尺寸 Bore Size
2", 2.5", 3"	11 x 22 mm	—	C型環

絲扣規格 THREADED STEM SPECIFICATION

編號 Suffix	絲扣牙徑 X 長度 Threaded Size
2", 2.5", 3"	M8 x 15 mm



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
48mm x 23.5mm (1-7/8" x 7/8")	30 kgs (66 lbs)	水晶輪(內仁黑) PU Wheel(Black)	-	1110-2-02-116-2-BK	1110-2-02-116-3-BK	滾珠軸承 Ball Bearing	絲扣總高 68 mm 插桿總高 65 mm Total height (Threaded stem) 68 mm Total height (Cylindrical stem) 65 mm	活動 44 mm 剎車 72 mm Swivel 44 mm Swivel W/Side Brake 72 mm
		水晶輪(內仁灰) PU Wheel(Grey)	-	1110-2-02-116-2-G	1110-2-02-116-3-G			
		水晶輪(內仁白) PU Wheel(White)	-	1110-2-02-116-2-W	1110-2-02-116-3-W			
		水晶輪(內仁藍) PU Wheel(Blue)	-	1110-2-02-116-2-BL	1110-2-02-116-3-BL			
		水晶輪(內仁紅) PU Wheel(Red)	-	1110-2-02-116-2-R	1110-2-02-116-3-R			
		水晶輪(內仁粉紅) PU Wheel(Pink)	-	1110-2-02-116-2-P	1110-2-02-116-3-P			
64mm x 23.5mm (2-1/2" x 7/8")	40 kgs (88 lbs)	水晶輪(內仁黑) PU Wheel(Black)	-	1110-2-25-116-2-BK	1110-2-25-116-3-BK	滾珠軸承 Ball Bearing	絲扣總高 83 mm 插桿總高 80 mm Total height (Threaded stem) 83 mm Total height (Cylindrical stem) 80 mm	活動 53 mm 剎車 72 mm Swivel 53 mm Swivel W/Side Brake 72 mm
		水晶輪(內仁灰) PU Wheel(Grey)	-	1110-2-25-116-2-G	1110-2-25-116-3-G			
		水晶輪(內仁白) PU Wheel(White)	-	1110-2-25-116-2-W	1110-2-25-116-3-W			
		水晶輪(內仁藍) PU Wheel(Blue)	-	1110-2-25-116-2-BL	1110-2-25-116-3-BL			
		水晶輪(內仁紅) PU Wheel(Red)	-	1110-2-25-116-2-R	1110-2-25-116-3-R			
		水晶輪(內仁粉紅) PU Wheel(Pink)	-	1110-2-25-116-2-P	1110-2-25-116-3-P			
76mm x 23.5mm (3" x 7/8")	50 kgs (110 lbs)	水晶輪(內仁黑) PU Wheel(Black)	-	1110-2-03-116-2-BK	1110-2-03-116-3-BK	滾珠軸承 Ball Bearing	絲扣總高 97 mm 插桿總高 94 mm Total height (Threaded stem) 97 mm Total height (Cylindrical stem) 94 mm	活動 60 mm 剎車 76 mm Swivel 60 mm Swivel W/Side Brake 76 mm
		水晶輪(內仁灰) PU Wheel(Grey)	-	1110-2-03-116-2-G	1110-2-03-116-3-G			
		水晶輪(內仁白) PU Wheel(White)	-	1110-2-03-116-2-W	1110-2-03-116-3-W			
		水晶輪(內仁藍) PU Wheel(Blue)	-	1110-2-03-116-2-BL	1110-2-03-116-3-BL			
		水晶輪(內仁紅) PU Wheel(Red)	-	1110-2-03-116-2-R	1110-2-03-116-3-R			
		水晶輪(內仁粉紅) PU Wheel(Pink)	-	1110-2-03-116-2-P	1110-2-03-116-3-P			

