



# 1112 Series 重型

## 長珠系列

2" Wide General Purposes Caster (American Style)

載重 Load  
120-450 kg

- 高負載且旋轉靈活，普遍適用於一般工廠搬運，另可附防塵蓋，屬得勝專利產品，可以有效防止腳輪因灰塵或纏絲而無法轉動，提高腳輪使用壽命。
- Swivel easily under heavy load, good for workshop carts. Patented thread guards and dust covers prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.



### ▶ 特色區 Features



### ▶ 輪子選項 Wheel Options



### ▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

編號 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
1	100 x 115 mm (4"x 4-1/2")	70 x 85 mm (2-5/8"~3"x3"~3-5/8")	9.5 mm (3/8")
2	115 x 159 mm (4-1/2"x 6-1/4")	75 x 130mm (2-7/16"~3-3/8" x4-15/16"~5-1/4")	12.7 mm (1/2")



▶ 絲扣規格 THREADED STEM SPECIFICATION

編號 Suffix	絲扣牙徑 X 長度 Threaded Size
4" 5" 6" 8"	M24 x 150mm

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
100mm×50mm (4" × 2")	270 kgs (600 lbs)	高科技耐腐聚氨基酯(圓弧形) PU on PP Core(Round Shape)	1112-04-43-1	1112-04-43-2	1112-04-43-4	滾珠 Ball Bearing	142mm (5-5/8")	活動 74.5mm 側剎 78.5mm AK剎 136.5mm  Swivel 74.5mm Swivel W/Side Brake 78.5mm AK Total Lock Brake 136.5mm
	200 kgs (440 lbs)	鐵芯聚氨基酯(圓弧形) PU on Cast (Round Shape)	1112-04-42-1	1112-04-42-2	1112-04-42-4			
	150 kgs (325 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1112-04-04-1	1112-04-04-2	1112-04-04-4	滾針 Roller Bearing		
	270 kgs (600 lbs)	鐵芯聚氨基酯 PU on Cast	1112-04-33-1	1112-04-33-2	1112-04-33-4			
	360 kgs (800 lbs)	電木輪 Phenolic	1112-04-25-1	1112-04-25-2	1112-04-25-4			
	270 kgs (600 lbs)	高科技耐腐聚氨基酯 PU on PP Core	1112-04-31-1	1112-04-31-2	1112-04-31-4			
	360 kgs (800 lbs)	SS鐵輪 Cast Iron	1112-04-21-1	1112-04-21-2	1112-04-21-4	滾針 Roller Bearing		
	360 kgs (800 lbs)	VG輪 V Groove	1112-04-28-1	1112-04-28-2	1112-04-28-4			
	120 kgs (265 lbs)	超級人造膠(圓弧形) TPR on PP Core (Round Shape)	1112-04-26-1	1112-04-26-2	1112-04-26-4			
	150 kgs (330 lbs)	超級人造膠(平面) TPR on PP Core (Flat Shape)	1112-04-52-1	1112-04-52-2	1112-04-52-4			
	150 kgs (330 lbs)	W超級人造膠 WPPR	1112-04-47-1	1112-04-47-2	1112-04-47-4			
	181 kgs (400 lbs)	W全效輪 W Resolute	1112-04-48-1	1112-04-48-2	1112-04-48-4			
	181 kgs (400 lbs)	全效輪(平面) Resolute(Flat Shape)	1112-04-51-1	1112-04-51-2	1112-04-51-4			
	136 kgs (300 lbs)	全效輪(圓弧形) Resolute(Round Shape)	1112-04-44-1	1112-04-44-2	1112-04-44-4			
	228 kgs (500 lbs)	HDR輪(圓弧形) HD Resolute Wheel(Round Shape)	1112-04-54-1	1112-04-54-2	1112-04-54-4			
	270 kgs (600 lbs)	WHDR輪 WHDR	1112-04-55-1	1112-04-55-2	1112-04-55-4			
125mm×50mm (5" × 2")	340 kgs (750 lbs)	高科技耐腐聚氨基酯(圓弧形) PU on PP Core (Round Shape)	1112-05-43-1	1112-05-43-2	1112-05-43-4	滾珠 Ball Bearing	167mm (6-1/2")	活動 92.5mm 側剎 92.5mm AK剎 140mm  Swivel 92.5mm Swivel W/Side Brake 92.5mm AK Total Lock Brake 140mm
	230 kgs (500 lbs)	鐵芯聚氨基酯(圓弧形) PU on Cast (Round Shape)	1112-05-42-1	1112-05-42-2	1112-05-42-4			
	340 kgs (750 lbs)	SPU輪 CPU on PP core	1112-05-63-1	1112-05-63-2	1112-05-63-4			
	360 kgs (790 lbs)	EPU輪 EPU	1112-05-78-1	1112-05-78-2	1112-05-78-4			
	450 kgs (990 lbs)	EQPU輪 EQPU	1112-05-81-1	1112-05-81-2	1112-05-81-4			
	200 kgs (440 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1112-05-04-1	1112-05-04-2	1112-05-04-4	滾針 Roller Bearing		
	360 kgs (790 lbs)	鐵芯聚氨基酯 PU on Cast	1112-05-33-1	1112-05-33-2	1112-05-33-4			
	400 kgs (880 lbs)	電木輪 Phenolic	1112-05-25-1	1112-05-25-2	1112-05-25-4			
	340 kgs (750 lbs)	高科技耐腐聚氨基酯 PU on PP Core	1112-05-31-1	1112-05-31-2	1112-05-31-4			
	400 kgs (880 lbs)	SS鐵輪 Cast Iron	1112-05-21-1	1112-05-21-2	1112-05-21-4			
	400 kgs (880 lbs)	VG輪 V Groove	1112-05-28-1	1112-05-28-2	1112-05-28-4			
	140 kgs (300 lbs)	超級人造膠(圓弧形) TPR on PP Core (Round Shape)	1112-05-26-1	1112-05-26-2	1112-05-26-4			
	180 kgs (396 lbs)	超級人造膠(平面) TPR on PP Core (Flat Shape)	1112-05-52-1	1112-05-52-2	1112-05-52-4			
	180 kgs (396 lbs)	W超級人造膠 WPPR	1112-05-47-1	1112-05-47-2	1112-05-47-4			
	227 kgs (500 lbs)	W全效輪 W Resolute	1112-05-48-1	1112-05-48-2	1112-05-48-4			
	227 kgs (500 lbs)	全效輪(平面) Resolute(Flat Shape)	1112-05-51-1	1112-05-51-2	1112-05-51-4			
	170 kgs (375 lbs)	全效輪(圓弧形) Resolute(Round Shape)	1112-05-44-1	1112-05-44-2	1112-05-44-4			
	261 kgs (575 lbs)	HDR輪(圓弧形) HD Resolute Wheel(Round Shape)	1112-05-54-1	1112-05-54-2	1112-05-54-4			
340 kgs (750 lbs)	WHDR輪 WHDR	1112-05-55-1	1112-05-55-2	1112-05-55-4				



輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
150mm×50mm (6" × 2")	410 kgs (900 lbs)	高科技耐磨聚氨酯(圓弧形) PU on PP Core(Round Shape)	1112-06-43-1	1112-06-43-2	1112-06-43-4	滾珠 Ball Bearing	活動 111mm 側剎 111mm AK剎 154mm  Swivel 111mm Swivel W/Side Brake 111mm AK Total Lock Brake 154mm	
	260 kgs (570 lbs)	鐵芯聚氨酯(圓弧形) PU on Cast (Round Shape)	1112-06-42-1	1112-06-42-2	1112-06-42-4			
	410 kgs (900 lbs)	SPU輪 CPU on PP core	1112-06-63-1	1112-06-63-2	1112-06-63-4			
	450 kgs (990 lbs)	EPU輪 EPU	1112-06-78-1	1112-06-78-2	1112-06-78-4			
	450 kgs (990 lbs)	EQPU輪 EQPU	1112-06-81-1	1112-06-81-2	1112-06-81-4			
	250 kgs (550 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1112-06-04-1	1112-06-04-2	1112-06-04-4			
	410 kgs (900 lbs)	鐵芯聚氨酯 PU on Cast	1112-06-33-1	1112-06-33-2	1112-06-33-4	滾針 Roller Bearing		
	420 kgs (925 lbs)	電木輪 Phenolic	1112-06-25-1	1112-06-25-2	1112-06-25-4			
	410 kgs (900 lbs)	高科技耐磨聚氨酯 PU on PP Core	1112-06-31-1	1112-06-31-2	1112-06-31-4			
	420 kgs (925 lbs)	SS鐵輪 Cast Iron	1112-06-21-1	1112-06-21-2	1112-06-21-4			
	420 kgs (925 lbs)	VG輪 V Groove	1112-06-28-1	1112-06-28-2	1112-06-28-4			
	160 kgs (350 lbs)	超級人造膠(圓弧形) TPR on PP Core(Round Shape)	1112-06-26-1	1112-06-26-2	1112-06-26-4			
	210 kgs (462 lbs)	超級人造膠(平面) TPR on PP Core(Flat Shape)	1112-06-52-1	1112-06-52-2	1112-06-52-4	滾針 Roller Bearing  精密長珠軸承 Annular ball bearing		
	210 kgs (462 lbs)	W超級人造膠 WPPR	1112-06-47-1	1112-06-47-2	1112-06-47-4			
	272 kgs (600 lbs)	W全效輪 W Resolute	1112-06-48-1	1112-06-48-2	1112-06-48-4			
	272 kgs (600 lbs)	全效輪(平面) Resolute (Flat Shape)	1112-06-51-1	1112-06-51-2	1112-06-51-4			
	204 kgs (450 lbs)	全效輪(圓弧形) Resolute (Round Shape)	1112-06-44-1	1112-06-44-2	1112-06-44-4			
	295 kgs (650 lbs)	HDR輪(圓弧形) HD Resolute Wheel(Round Shape)	1112-06-54-1	1112-06-54-2	1112-06-54-4			
410 kgs (900 lbs)	WHDR輪 WHDR	1112-06-55-1	1112-06-55-2	1112-06-55-4				
200mm×50mm (8" × 2")	420 kgs (925 lbs)	高科技耐磨聚氨酯(圓弧形) PU on PP Core(Round Shape)	1112-08-43-1	1112-08-43-2	1112-08-43-4	滾珠 Ball Bearing	活動 140mm 側剎 140mm AK剎 160mm  Swivel 140mm Swivel W/Side Brake 140mm AK Total Lock Brake 160mm	
	300 kgs (660 lbs)	鐵芯聚氨酯(圓弧形) PU on Cast (Round Shape)	1112-08-42-1	1112-08-42-2	1112-08-42-4			
	420 kgs (925 lbs)	SPU輪 CPU on PP core	1112-08-63-1	1112-08-63-2	1112-08-63-4			
	450 kgs (990 lbs)	EPU輪 EPU	1112-08-78-1	1112-08-78-2	1112-08-78-4			
	450 kgs (990 lbs)	EQPU輪 EQPU	1112-08-81-1	1112-08-81-2	1112-08-81-4			
	300 kgs (660 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1112-08-04-1	1112-08-04-2	1112-08-04-4			
	420 kgs (925 lbs)	鐵芯聚氨酯 PU on Cast	1112-08-33-1	1112-08-33-2	1112-08-33-4	滾針 Roller Bearing		
	450 kgs (990 lbs)	電木輪 Phenolic	1112-08-25-1	1112-08-25-2	1112-08-25-4			
	420 kgs (925 lbs)	高科技耐磨聚氨酯 PU on PP Core	1112-08-31-1	1112-08-31-2	1112-08-31-4			
	450 kgs (990 lbs)	SS鐵輪 Cast Iron	1112-08-21-1	1112-08-21-2	1112-08-21-4			
	450 kgs (990 lbs)	VG輪 V Groove	1112-08-28-1	1112-08-28-2	1112-08-28-4			
	185 kgs (400 lbs)	超級人造膠(圓弧形) TPR on PP Core (Round Shape)	1112-08-26-1	1112-08-26-2	1112-08-26-4			
	230 kgs (506 lbs)	超級人造膠(平面) TPR on PP Core(Flat Shape)	1112-08-52-1	1112-08-52-2	1112-08-52-4	滾針 Roller Bearing  精密長珠軸承 Annular ball bearing		
	230 kgs (506 lbs)	W超級人造膠 WPPR	1112-08-47-1	1112-08-47-2	1112-08-47-4			
	306 kgs (675 lbs)	W全效輪 W Resolute	1112-08-48-1	1112-08-48-2	1112-08-48-4			
	306 kgs (675 lbs)	全效輪(平面) Resolute (Flat Shape)	1112-08-51-1	1112-08-51-2	1112-08-51-4			
	272 kgs (600 lbs)	全效輪(圓弧形) Resolute(Round Shape)	1112-08-44-1	1112-08-44-2	1112-08-44-4			
	318 kgs (700 lbs)	HDR輪(圓弧形) HD Resolute Wheel(Round Shape)	1112-08-54-1	1112-08-54-2	1112-08-54-4			
430 kgs (950 lbs)	WHDR輪 WHDR	1112-08-55-1	1112-08-55-2	1112-08-55-4				