



1115-H Series


載重彈簧輪系列

Heavy Duty Spring-loaded Caster

- 屬得勝專利產品，避震，超重負載，多款供選擇。採用超厚板材及高級彈簧，品質、工藝明顯優於市場上同類產品。
- DERSHENG'S patented products, shock-absorbing, extreme heavy-duty, diversified selection. Made of super thick steel and high quality spring, outperforming most products from competitors.



特色區 Features



AK煞(For 4" 5" 6" 8")
Swivel W/Center Lock(AK type)




BCD煞(中煞)(For 10" only)
Swivel W/Center Lock Brake




PU輪面可以變化硬度
Different PU
tread hardness available



滾珠軸承
Ball Bearing



輪子可附金屬防塵蓋(供選擇)
Metal Thread Guard(optional)



輪子可附塑膠防塵蓋(供選擇)
Plastic Thread Guard(optional)

輪子選項 Wheel Options



鐵芯聚氨酯
PU on Cast



QPU輪
QPU



鋁芯AQP
QPU on AL Core



環保牽引NBR
Non - marking NBR Rubber
on Cast



鐵芯NBR橡膠輪(叉車料)
NBR Rubber on Cast



EQPU輪
EQPU



VPU輪
VPU



VQPU輪
VQPU



EPU輪
EPU










» 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4" 5" 6" 8"	110 x 140mm (4-11/32" x 5-1/2")	75 x 110mm(常規標準底板) (2-15/16" x 4-11/32")	12 mm (1/2")
	110 x 140mm (4-11/32" x 5-1/2")	80 x 105mm(歐規孔距) (3-5/32" x 4-1/8"(European Plate))	12 mm (1/2")
	130 x 165mm (5-1/8" x 6-1/2")	100 x 130mm (3-15/16" x 5-1/8")	12 mm (1/2")
	114 x 159mm (4-1/2" x 6-1/4")	73.8 x 129.4mm (2-29/32" x 5-3/32")	12 mm (1/2")
10"	130 x 167mm (5-1/8" x 6-9/16")	85 x 140mm (3-11/32" x 5-1/2")	12 mm (1/2")

輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
100mm x 36mm (4" x 1-7/16")	250 kgs (550 lbs)	鐵芯聚氨酯 PU on Cast	1115-H-04-33-1	1115-H-04-33-2	1115-H-04-33-4	滾珠 Ball Bearing	198mm (7-13/16")	活動 96mm AK煞 164mm Swivel 96mm Swivel W/AK lock brake 164mm
	250 kgs (550 lbs)	鐵芯AQPU QPU on AL Core	1115-H-04-87-1	1115-H-04-87-2	1115-H-04-87-4			
	300 kgs (660 lbs)	QPU輪 QPU	1115-H-04-80-1	1115-H-04-80-2	1115-H-04-80-4			
100mm x 38mm (4" x 1-1/2")	200 kgs (440 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-H-04-90-1	1115-H-04-90-2	1115-H-04-90-4	滾珠 Ball Bearing	210mm (8-9/32")	活動 132mm AK煞 194mm Swivel 132mm Swivel W/AK lock brake 194mm
	200 kgs (440 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-04-04-1	1115-H-04-04-2	1115-H-04-04-4			
125mm x 40mm (5" x 1-9/16")	250 kgs (550 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-H-05-90-1	1115-H-05-90-2	1115-H-05-90-4	滾珠 Ball Bearing	225mm (8-27/32")	活動 146mm AK煞 200mm Swivel 146mm Swivel W/AK lock brake 200mm
	250 kgs (550 lbs)	鐵芯聚氨酯 PU on Cast	1115-H-05-33-1	1115-H-05-33-2	1115-H-05-33-4			
	250 kgs (550 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-05-04-1	1115-H-05-04-2	1115-H-05-04-4			
	300 kgs (660 lbs)	鐵芯AQPU QPU on AL Core	1115-H-05-87-1	1115-H-05-87-2	1115-H-05-87-4			
	300 kgs (660 lbs)	QPU輪 QPU	1115-H-05-80-1	1115-H-05-80-2	1115-H-05-80-4			
	300 kgs (660 lbs)	EPU輪 EPU	1115-H-05-78-1	1115-H-05-78-2	1115-H-05-78-4			
	400 kgs (880 lbs)	EQPU輪 EQPU	1115-H-05-81-1	1115-H-05-81-2	1115-H-05-81-4			
150mm x 40mm (6" x 1-9/16")	300 kgs (660 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-06-90-1	1115-H-06-04-2	1115-H-06-04-4	滾珠 Ball Bearing	225mm (8-27/32")	活動 146mm AK煞 200mm Swivel 146mm Swivel W/AK lock brake 200mm
	300 kgs (660 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-H-06-04-1	1115-H-06-90-2	1115-H-06-90-4			
150mm x 42mm (6" x 1-5/8")	300 kgs (660 lbs)	鐵芯聚氨酯 PU on Cast	1115-H-06-33-1	1115-H-06-33-2	1115-H-06-33-4	滾珠 Ball Bearing	225mm (8-27/32")	活動 146mm AK煞 200mm Swivel 146mm Swivel W/AK lock brake 200mm
	350 kgs (770 lbs)	鐵芯AQPU QPU on AL Core	1115-H-06-87-1	1115-H-06-87-2	1115-H-06-87-4			
	350 kgs (770 lbs)	QPU輪 QPU	1115-H-06-80-1	1115-H-06-80-2	1115-H-06-80-4			
	350 kgs (770 lbs)	EPU輪 EPU	1115-H-06-78-1	1115-H-06-78-2	1115-H-06-78-4			
	450 kgs (990 lbs)	EQPU輪 EQPU	1115-H-06-81-1	1115-H-06-81-2	1115-H-06-81-4			
	450 kgs (990 lbs)	VPU輪 VPU	1115-H-06-82-1	1115-H-06-82-2	1115-H-06-82-4			
	550 kgs (1210 lbs)	VQPU輪 VQPU	1115-H-06-83-1	1115-H-06-83-2	1115-H-06-83-4			
150mm x 46mm (6" x 1-13/16")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-06-04-1	1115-H-06-04-2	1115-H-06-04-4	滾珠 Ball Bearing		



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius			
			固定 Fixed	活動 Swivel	剎車 Brake						
200mm x 44mm (8" x 1-3/4")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-08-04-1	1115-H-08-04-2	1115-H-08-04-4	滾珠 Ball Bearing	280mm (11-1/32")	活動 182mm AK煞 254mm Swivel 182mm Swivel W/AK lock brake 254mm			
	350 kgs (770 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-H-08-90-1	1115-H-08-90-2	1115-H-08-90-4						
200mm x 50mm (8" x 2")	350 kgs (770 lbs)	鐵芯聚氨酯 PU on Cast	1115-H-08-33-1	1115-H-08-33-2	1115-H-08-33-4						
	400 kgs (880 lbs)	QPU輪 QPU	1115-H-08-80-1	1115-H-08-80-2	1115-H-08-80-4						
	400 kgs (880 lbs)	EPU輪 EPU	1115-H-08-78-1	1115-H-08-78-2	1115-H-08-78-4						
	400 kgs (880 lbs)	鋁芯AQPU QPU on AL Core	1115-H-08-87-1	1115-H-08-87-2	1115-H-08-87-4						
	500 kgs (1100 lbs)	EQPU輪 EQPU	1115-H-08-81-1	1115-H-08-81-2	1115-H-08-81-4						
	500 kgs (1100 lbs)	VPU輪 VPU	1115-H-08-82-1	1115-H-08-82-2	1115-H-08-82-4						
600 kgs (1320 lbs)	VQPU輪 VQPU	1115-H-08-83-1	1115-H-08-83-2	1115-H-08-83-4							
250mm x 62mm (10" x 2-7/16")	550 kgs (1210 lbs)	QPU輪 QPU	1115-H-10-80-1	1115-H-10-80-2	1115-H-10-80-4				滾珠 Ball Bearing	353mm (13-29/32")	活動 213mm BCD煞 255mm Swivel 213mm Swivel W/Center lock 255mm
	550 kgs (1210 lbs)	VPU輪 VPU	1115-H-10-82-1	1115-H-10-82-2	1115-H-10-82-4				滾珠 Ball Bearing	355mm (14")	
	650 kgs (1430 lbs)	VQPU輪 VQPU	1115-H-10-83-1	1115-H-10-83-2	1115-H-10-83-4				滾珠 Ball Bearing	355mm (14")	
250mm x 63mm (10" x 2-1/2")	400 kgs (880 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1115-H-10-04-1	1115-H-10-04-2	1115-H-10-04-4	滾珠 Ball Bearing	355mm (14")				
	400 kgs (880 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1115-H-10-90-1	1115-H-10-90-2	1115-H-10-90-4	滾珠 Ball Bearing	353mm (13-29/32")				
254mm x 62mm (10" x 2-7/16")	500 kgs (1100 lbs)	鐵芯聚氨酯 PU on Cast	1115-H-10-33-1	1115-H-10-33-2	1115-H-10-33-4	滾珠 Ball Bearing	353mm (13-29/32")				