



# 1129 Series 中型

## 醫療系列(CN)

### Medical Caster

- 採用特別腳架荷重結構設計，超大波盤結構轉動靈活，剎車制動效果良好，剎車採用尼龍加纖雙踏板或鋁踏板，彈片全部採用不銹鋼製成，不會因長期使用而變形、生銹。
- Special yoke design to swivel easily. High performance total lock brake to be actiated easily and effectively. Brake pedals are made of fibre-filled plastic on strength-enhanced aluminum alloy. Stainless steel brake chips are of good rust resistance.

載重 Load  
50-250 kg



#### ▶ 特色區 Features



90度定向剎車架  
90° Directional Lock



180度定向剎車架  
180° Directional Lock



尼龍雙踏板  
Total Lock Brake  
with Dual Nylon Pedals



滾珠軸承  
Ball Bearing

滾珠軸承  
Ball Bearing

中管  
Plain Bearing



鋁剎  
Total Lock Brake  
with Aluminum Alloy Pedal



波盤防塵蓋  
Swivel Dust Cover



防塵護套  
Housing Cover

#### ▶ 輪子選項 Wheel Options



高科技耐磨聚氨酯  
PU on PP Core



鋁芯橡膠輪  
Rubber on Aluminum Core




超級人造膠(514)  
TPR on PP Core



尼龍輪  
Nylon



NPPR輪  
NPPR



W超級人造膠  
WPPR



WMRC輪  
WMRC



CPD輪  
CPD



超級人造膠(515)  
TPR on PP Core



鋁芯AQP  
QPU on AL Core



橡膠輪  
Rubber



塑料輪  
PP




導電輪  
E-Conductive



耐高溫輪  
Hi-temp




W全效輪  
W Resolute Wheel




全效輪(514)  
Resolute Wheel




WPP輪  
WPP



藍色彈力輪  
Blue Resilient Rubber Wheel



WHDR輪  
WHDR



全效輪(515)  
Resolute



超級人造膠(大圓弧)  
TPR on PP Core (Donut)



全效輪(大圓弧)  
Resolute (Donut)



### ▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

編號 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
1	64 x 64 mm (2-1/2"x 2-1/2")	48 x 48 mm (只有3"適用) 1-7/8"x1-7/8"(3"Caster only)	6 mm (3/16")
2	69 x 96 mm (2-23/32"x 3-25/32")	45 x 75 mm (高級架底板) 1-3/4"x 3"	6.35 mm (1/4")
3	72 x 91 mm (2-13/16"x 3-19/32")	53 x 72 mm (醫療/儀器架底板) 2-1/8"x 2-7/8"	6.35 mm (1/4")
4	80 x 105 mm (3-1/8"x 4-1/8")	60 x 85 mm (美規底板) 2-3/8"x 3-7/16"(American Plate)	8 mm (5/16")
5	85 x 105 mm (3-5/16"x 4-1/8")	60 x 80 mm (歐規孔距) 2-3/8"x 3-1/8"(European Plate)	8 mm (5/16")
6	93 x 110 mm (3-5/8" x 4-3/8")	70 x 85 mm (重型架底板) 2-5/8"~3" x 3"~3-5/8" (Heavy Duty Plate)	9.5 mm (3/8")

### ▶▶ 插桿規格 CYLINDRICAL STEM SPECIFICATION

編號 Suffix	插桿直徑 X 長度 Diameter x Length	編號 Suffix	插桿直徑 X 長度 Diameter x Length
3"	11 x 22mm (CN) 7/16" diameter x 7/8"	3"	11 x 50mm (CN) 7/16" diameter x 1-31/32"
4"~6"	21.6 x 56mm (CN) 0.845" diameter x 2-3/16" (For 3"~5" Casters)	4"~6"	22.8 x 45mm (CN) 0.897" diameter x 1-3/4"
4"~6"	27.2 x 45mm (CN) 1-5/64" diameter x 1-3/4"	4"~6"	28 x 30mm (CN) 1-7/64" diameter x 1-3/16"

### ▶▶ 絲扣規格 THREADED STEM SPECIFICATION

編號 Suffix	絲扣牙徑 X 長度 Threaded Size	編號 Suffix	絲扣牙徑 X 長度 Threaded Size
3"	3/8-16UNC x 25mm (CN)	3"	M10 x 15mm (CN)
3"	M10 x 25mm (CN)	3"	M12 x 25mm (CN)
4"~6"	3/8-16UNC x 25mm (CN)	4"~6"	M10 x 35mm (CN)
4"~6"	M12 x 29mm (CN)	4"~6"	1/2-12UNC x 27.5mm (CN)
4"~6"	1/2-13UNC x 25mm (CN)	4"~6"	M16 x 30mm (CN)

### ▶▶ 空鉚規格 SINGLE BOLT HOLE

編號 Suffix	孔徑 Centre Hole	編號 Suffix	孔徑 Centre Hole
3"	10.2mm (CN)	4"~6"	10.5mm (CN)
4"~6"	12.5mm (CN)		



輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius	
			固定 Fixed	活動 Swivel	剎車 Brake				
75mm×27mm (3"×1")	70 kgs (155 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-03-31-1	1129-03-31-2	1129-03-31-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 106mm (4-1/8")  絲扣類總高 Threaded Stem OAH: 110mm (4-21/64")  空心/插桿類總高 Single Bolt Hole/ Cylindrical Stem OAH: 104mm (4-3/32")	活動 67mm 雙煞 91mm  Swivel 67mm Swivel W/Total lock 91mm	
	70 kgs (155 lbs)	超級人造膠 TPR on PP Core	1129-03-75-1	1129-03-75-2	1129-03-75-4	中管 Plain Bearing			
	56 kgs (125 lbs)	全效輪 Resolute	1129-03-68-1	1129-03-68-2	1129-03-68-4	滾珠 Ball Bearing			
	60 kgs (132 lbs)	NPPR輪 NPPR	1129-03-67-1	1129-03-67-2	1129-03-67-4				
	80 kgs (175 lbs)	導電輪 E-Conductive	1129-03-17-1	1129-03-17-2	1129-03-17-4	中管 Plain Bearing			
	70 kgs (155 lbs)	尼龍輪 Nylon	1129-03-07-1	1129-03-07-2	1129-03-07-4				
	50 kgs (110 lbs)	橡膠輪 Rubber	1129-03-06-1	1129-03-06-2	1129-03-06-4				
	60 kgs (132 lbs)	塑料輪 PP	1129-03-29-1	1129-03-29-2	1129-03-29-4				
100mm x 24mm (4" x 1")	50 kgs (110 lbs)	超級人造膠 TPR on PP Core	1129-R-04-75-1	1129-R-04-75-2	1129-R-04-75-4	滾珠 Ball Bearing			
	55 kgs (121 lbs)	全效輪 Resolute	1129-R-04-68-1	1129-R-04-68-2	1129-R-04-68-4				
100mm×32mm (4"×1-1/4")	120kgs (265 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-04-31-1	1129-04-31-2	1129-04-31-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 136mm (5-3/8")  絲扣類總高 Threaded Stem OAH: 136mm (5-3/8")  空心/插桿類總高 Single Bolt Hole/ Cylindrical Stem OAH: 132mm (5-13/64")	活動 91mm 雙煞 98mm 側煞 95mm  Swivel 91mm Swivel W/Total lock 98mm Swivel W/Side Brake 95mm	
	100kgs (220 lbs)	超級人造膠 TPR on PP Core	1129-04-75-1	1129-04-75-2	1129-04-75-4				
	80kgs (175lbs)	超級人造膠(大圓弧) TPR on PP Core (Donut)	1129-04-110-1	1129-04-110-2	1129-04-110-4	中管 Plain Bearing			
	90kgs (198lbs)	全效輪(大圓弧) Resolute (Donut)	1129-04-111-1	1129-04-111-2	1129-04-111-4	滾珠 Ball Bearing			
	125kgs (275 lbs)	全效輪 Resolute	1129-04-68-1	1129-04-68-2	1129-04-68-4				
	80 kgs (176 lbs)	導電輪 E-Conductive	1129-04-17-1	1129-04-17-2	1129-04-17-4	滾珠 Ball Bearing			
	135kgs (300 lbs)	W全效輪 W Resolute	1129-04-48-1	1129-04-48-2	1129-04-48-4				
	180kgs (400 lbs)	WHDR輪 WHDR	1129-04-66-1	1129-04-66-2	1129-04-66-4				
	100kgs (220 lbs)	W超級人造膠 WPPR	1129-04-47-1	1129-04-47-2	1129-04-47-4				
	180kgs (396 lbs)	WMRC輪 WMRC	1129-04-45-1	1129-04-45-2	1129-04-45-4				
	130kgs (285 lbs)	WPP輪 WPP	1129-04-46-1	1129-04-46-2	1129-04-46-4				
	135 kgs (300 lbs)	鋁芯橡膠輪 Rubber on Aluminum Core	1129-04-22-1	1129-04-22-2	1129-04-22-4				
	200kgs (440 lbs)	鋁芯AQPU QPU on AL Core	1129-04-87-1	1129-04-87-2	1129-04-87-4				
	70kgs (154 lbs)	NPPR輪 NPPR	1129-04-67-1	1129-04-67-2	1129-04-67-4				中管 Plain Bearing
	120 kgs (265 lbs)	尼龍輪 Nylon	1129-04-07-1	1129-04-07-2	1129-04-07-4				
	135 kgs (300 lbs)	耐高溫輪 Hi-temp	1129-04-25-1	1129-04-25-2	1129-04-25-4				
	80 kgs (175 lbs)	橡膠輪 Rubber	1129-04-06-1	1129-04-06-2	1129-04-06-4				
	90 kgs (198 lbs)	塑料輪 PP	1129-04-29-1	1129-04-29-2	1129-04-29-4				












輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號 Item No.			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius	
			固定 Fixed	活動 Swivel	剎車 Brake				
100mm×36mm (4"x1-1/2")	160 kgs (352 lbs)	CPD輪 CPD	1129-04-71-1	1129-04-71-2	1129-04-71-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 136mm (5-3/8")  絲扣類總高 Threaded Stem OAH: 136mm (5-3/8")  空心/插桿類總高 Cylindrical Stem OAH: 132mm (5-13/64")	活動 91mm 雙煞 98mm 側煞 95mm  Swivel 91mm Swivel W/Total lock 98mm Swivel W/Side Brake 95mm	
	160 kgs (352 lbs)	藍色彈力輪 Blue Resilient Rubber Wheel	1129-04-50-1	1129-04-50-2	1129-04-50-4				
	140kgs (308 lbs)	超級人造膠 TPR on PP Core	1129-04-77-1	1129-04-77-2	1129-04-77-4				
	160kgs (352 lbs)	全效輪 Resolute	1129-04-76-1	1129-04-76-2	1129-04-76-4				
	200kgs (440 lbs)	鋁芯AQPU QPU on AL Core	1129-04-87-1	1129-04-87-2	1129-04-87-4				
125mm x 24.5mm (5" x 1")	70 kgs (155 lbs)	超級人造膠 TPR on PP Core	1129-R-05-75-1	1129-R-05-75-2	1129-R-05-75-4	滾珠 Ball Bearing			
	80 kgs (175 lbs)	全效輪 Resolute	1129-R-05-68-1	1129-R-05-68-2	1129-R-05-68-4				
125mm×32mm (5"×1-1/4")	130kgs (285 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-05-31-1	1129-05-31-2	1129-05-31-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 162mm (6-3/8")  絲扣類總高 Threaded Stem OAH: 162mm (6-3/8")  空心/插桿類總高 Single Bolt Hole/ Cylindrical Stem OAH: 156mm (6-9/64")	活動 101mm 雙煞 101mm 側煞 101mm  Swivel 101mm Swivel W/Total lock 101mm Swivel W/Side Brake 101mm	
	110kgs (240 lbs)	超級人造膠 TPR on PP Core	1129-05-75-1	1129-05-75-2	1129-05-75-4				
	100kgs (220lbs)	超級人造膠(大圓弧) TPR on PP Core (Donut)	1129-05-110-1	1129-05-110-2	1129-05-110-4				
	120kgs (265lbs)	全效輪(大圓弧) Resolute (Donut)	1129-05-111-1	1129-05-111-2	1129-05-111-4	中管 Plain Bearing			
	147 kgs (325 lbs)	全效輪 Resolute	1129-05-68-1	1129-05-68-2	1129-05-68-4				
	90 kgs (198 lbs)	導電輪 E-Conductive	1129-05-17-1	1129-05-17-2	1129-05-17-4				
	147 kgs (325 lbs)	W全效輪 W Resolute	1129-05-48-1	1129-05-48-2	1129-05-48-4	滾珠 Ball Bearing			
	180 kgs (400 lbs)	WHDR輪 WHDR	1129-05-66-1	1129-05-66-2	1129-05-66-4				
	110kgs (240 lbs)	W超級人造膠 WPPR	1129-05-47-1	1129-05-47-2	1129-05-47-4				
	200 kgs (440 lbs)	WMRC輪 WMRC	1129-05-45-1	1129-05-45-2	1129-05-45-4				
	150 kgs (330 lbs)	WPP輪 WPP	1129-05-46-1	1129-05-46-2	1129-05-46-4				
	200kgs (440 lbs)	鋁芯AQPU QPU on AL Core	1129-05-87-1	1129-05-87-2	1129-05-87-4				
	140 kgs (305 lbs)	尼龍輪 Nylon	1129-05-07-1	1129-05-07-2	1129-05-07-4				中管 Plain Bearing
	90 kgs (198 lbs)	橡膠輪 Rubber	1129-05-06-1	1129-05-06-2	1129-05-06-4				
	100 kgs (220 lbs)	塑料輪 PP	1129-05-29-1	1129-05-29-2	1129-05-29-4				
125mm×36mm (5"×1-1/2")	200 kgs (440 lbs)	CPD輪 CPD	1129-05-71-1	1129-05-71-2	1129-05-71-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 162mm (6-3/8")  絲扣類總高 Threaded Stem OAH: 162mm (6-3/8")  空心/插桿類總高 Single Bolt Hole/ Cylindrical Stem OAH: 156mm (6-9/64")	活動 101mm 雙煞 101mm 側煞 101mm  Swivel 101mm Swivel W/Total lock 101mm Swivel W/Side Brake 101mm	
	250 kgs (550 lbs)	藍色彈力輪 Blue Resilient Rubber Wheel	1129-05-50-1	1129-05-50-2	1129-05-50-4				
	160kgs (352 lbs)	超級人造膠 TPR on PP Core	1129-05-77-1	1129-05-77-2	1129-05-77-4				
	180kgs (400 lbs)	全效輪 Resolute	1129-05-76-1	1129-05-76-2	1129-05-76-4				





 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	 型號 Item No.			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定 Fixed	活動 Swivel	剎車 Brake			
150mm×32mm (6"×1-1/4")	110 kgs (240 lbs)	超級人造膠 TPR on PP Core	1129-06-75-1	1129-06-75-2	1129-06-75-4	滾珠 Ball Bearing	底板類總高 Plate Version OAH: 186mm (7-3/8")  絲扣類總高 Threaded Stem OAH: 186mm (7-3/8")  空心/插桿類總高 Single Bolt Hole/ Cylindrical Stem OAH: 181mm (7-1/8")	活動 113mm 雙煞 113mm 側煞 113mm  Swivel 113mm Swivel W/Total lock 113mm Swivel W/Side Brake 113mm
	147 kgs (325 lbs)	全效輪 Resolute	1129-06-68-1	1129-06-68-2	1129-06-68-4			
	147 kgs (325 lbs)	W全效輪 W Resolute	1129-06-48-1	1129-06-48-2	1129-06-48-4			
	200 kgs (440 lbs)	WHDR輪 WHDR	1129-06-66-1	1129-06-66-2	1129-06-66-4			
	110 kgs (240 lbs)	W超級人造膠 WPPR	1129-06-47-1	1129-06-47-2	1129-06-47-4			

