



1135 Series

全塑系列


Med-Glide Series Caster (All Plastic)

- ◉無污染 ◉超靜音 ◉防生鏽 ◉彈性佳
- ◉低阻力 ◉轉動靈活 ◉耐衝材質 ◉專利產品
- ◉產品輕量化且堅固耐用
- ◉可另選購有抗菌效果之全效輪或TPR輪
- ◉適用於醫療器材設備、傢俱置物架、食品工廠、學校、辦公室等場所。
- ◉另有不銹鋼材質的五金件可供選擇
- ◉可提供無磁腳輪


- High grade synthetic housing
Smooth and easy rolling, these casters noticeably reduce the effort to operate equipment
Highly effective Thread guards prevent failure from strings and other debris.
Specifically designed for healthcare and institutional applications where silence is essential.
Corrosion resistant with non-marking wheels
- Ball bearing swivel head
- Directional lock also available
- Stainless steel components are also available
- Magnetic Free Caster also available



▶▶ 特色區 Features



▶▶ 輪子選項 Wheel Options



▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

規格 Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
4" 5"	69X96mm	45X75mm(高級底板) *	M8
4" 5"	69X96mm	49X74.5mm(斜孔底板) *	M8

* 有固定架可供選擇 (Fixed Caster is available. Please consult the factory.)



» 插桿規格 CYLINDRICAL STEM SPECIFICATION

規格 Size	插桿直徑 X 長度 Diameter x Length	孔位高度 Hole Height	孔尺寸 Bore Size
4" 5"	21.6X56mm	—	C型環(Grip Ring)
4" 5"	21.5X44.5mm	25.4mm *	#10 X 24UNC+C型環(Grip Ring)
4" 5"	28X30mm	19mm *	M8
4" 5"	28X40mm	19mm *	M8

* 有固定架可供選擇 (Fixed Caster is available. Please consult the factory.)

» 絲扣規格 THREADED STEM SPECIFICATION

規格 Size	絲扣牙徑 X 長度 Threaded Size	規格 Size	絲扣牙徑 X 長度 Threaded Size
4" 5"	3/8-16UNCX32mm	4" 5"	M12X25mm
4" 5"	M12X25mm (不鏽鋼SS)	4" 5"	1/2-12UNCX25mm
4" 5"	1/2-20UNCX25mm (不鏽鋼SS)	4" 5"	M16X30mm

» 空鉚規格 SINGLE BOLT HOLE

規格 Size	孔徑 Centre Hole	規格 Size	孔徑 Centre Hole
4" 5"	10.5mm	4" 5"	12.5mm

 輪徑×輪寬 Diameter×Width	規 格 Specification	 載重 Load	 材質 Material	 品號 Item No.				 軸承 Bearing	 總高 Overall Height	 偏心距 Offset	 迴旋半徑 Swivel radius
				固定 Fixed	活動 Swivel	雙煞 Total Lock Brake	定向煞 Directional Lock				
100mmx31mm (4"x1-1/4")	四角底板 Plate	90kgs (198lbs)	全效輪 Resolute	11350400451013	11350400452013	11350400454013	11350400454213	滾珠軸承 Ball Bearing	146mm (5"-3/4")	34mm (1"-11/32")	活動 84mm 活煞 105.5mm Swivel 84mm Swivel W/Total Lock Brake 105.5mm
		90kgs (198lbs)	超級人造膠 TPR on PP Core	11350400261013	11350400262013	11350400264013	11350400264213				
	絲扣 Threaded Stem	90kgs (198lbs)	全效輪 Resolute	—	11350400455013	11350400456013	—		145mm (5"-45/65")		
		90kgs (198lbs)	超級人造膠 TPR on PP Core	—	11350400265013	11350400266013	—		144mm (5"-43/64")		
	空鉚 Single Bolt Hole	90kgs (198lbs)	全效輪 Resolute	—	11350400459213	11350400459413	—		144mm (5"-43/64")		
		90kgs (198lbs)	超級人造膠 TPR on PP Core	—	11350400269213	11350400269413	—				
	插桿 Cylindrical Stem	90kgs (198lbs)	全效輪 Resolute	11350400457313	11350400457013	11350400458013	11350400458213		144mm (5"-43/64")		
		90kgs (198lbs)	超級人造膠 TPR on PP Core	11350400267313	11350400267013	11350400268013	11350400268213				
125mmx31mm (5"x1-1/4")	四角底板 Plate	100kgs (220lbs)	全效輪 Resolute	11350500451013	11350500452013	11350500454013	11350500454213	滾珠軸承 Ball Bearing	175mm (6"-57/64")	44.5mm (1"-3/4")	活動 107mm 活煞 124.5mm Swivel 107mm Swivel W/Total Lock Brake 124.5mm
		100kgs (220lbs)	超級人造膠 TPR on PP Core	11350500261013	11350500262013	11350500264013	11350500264213				
		100kgs (220lbs)	鋁芯AQPU QPU on AL Core	1135-05-87-1	1135-05-87-2	1135-05-87-4	1135-05-87-9				
	絲扣 Threaded Stem	100kgs (220lbs)	全效輪 Resolute	—	11350500455013	11350500456013	—		174mm (6"-27/32")		
		100kgs (220lbs)	超級人造膠 TPR on PP Core	—	11350500265013	11350500266013	—				
		100kgs (220lbs)	鋁芯AQPU QPU on AL Core	—	1135-05-87-2	1135-05-87-4	—				
	空鉚 Single Bolt Hole	100kgs (220lbs)	全效輪 Resolute	—	11350500459213	11350500459413	—		173mm (6"-13/16")		
		100kgs (220lbs)	超級人造膠 TPR on PP Core	—	11350500269213	11350500269413	—				
		100kgs (220lbs)	鋁芯AQPU QPU on AL Core	—	1135-05-87-2	1135-05-87-4	—				
	插桿 Cylindrical Stem	100kgs (220lbs)	全效輪 Resolute	11350500457313	11350500457013	11350500458013	11350500458213		173mm (6"-13/16")		
		100kgs (220lbs)	超級人造膠 TPR on PP Core	11350500267313	11350500267013	11350500268013	11350500268213				
		100kgs (220lbs)	鋁芯AQPU QPU on AL Core	1135-05-87-1	1135-05-87-2	1135-05-87-4	1135-05-87-9				