



1152 Series 重型

B型抗阻系列 Anti-Friction Caster (B Type)


- 高負載且高抗阻，可用手推，適用於汽車廠、汽車裝配廠、玻璃廠、紡織廠等負載重的車間，可另附防纏絲及防塵蓋，屬得勝專利產品，可以有效防止腳輪因灰塵或纏絲而無法轉動，提高腳輪使用壽命。
- Heavy duty caster with less resistance to move the equipment more efficiently, safely and effortlessly. This product is designed to minimize the manual starting, rolling and swiveling forces required to move equipments while at the same time, it is also build to survive the harshest towing application throughout various industries. With patented thread guards and dust covers to prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing. Suitable for towing application and indoor transfer of material of finished goods, such as automobile, glass, textile, tyre industries, etc.

載重 Load
220-1500kg

省力超過30%
Saving force
required
by 30%




▶▶ 特色區 Features



輪子可附塑膠防塵蓋(供選擇)
Plastic Thread Guard(optinal)



輪子可附金屬防塵蓋(供選擇)
Metal Thread Guard(optinal)



AK煞
Swivel W/Center lock(AK Type)



輪子可附防纏絲蓋(供選擇)
Thread guard specially for
textile industry(optinal)



自動巡向輪(供選擇)
Self-Align (optinal)



PU輪面可以變化硬度
Different PU
tread hardness available



▶▶ 輪子選項 Wheel Options



鐵芯聚氨酯
PU on Cast



三星輪
Rubber on Cast



鐵芯NBR橡膠輪
NBR Rubber on Cast



尼龍輪
Nylon



WMRC輪
WMRC



QPU輪
QPU



滾珠軸承
Ball Bearing



APU輪
PU on AL Core



CPD輪
CPD



銑輪
Cast Iron



環保NBR橡膠輪
Non-marking Rubber on Cast



EQPU輪
EQPU



鐵芯聚氨酯 (2050A/2050B)
PU on Cast (2050A/2050B)



ZQPU輪(雙輪)
ZQPU (Dual Wheels)



VPU輪
VPU



EPU輪
EPU



VQPU輪
VQPU



鐵芯VXPU
XPU on Iron Core



鋁芯QQ橡膠輪
Recilent rubber on AL Core



環保牽引NBR
Non-marking NBR Rubber
on Cast



鐵芯AQP
QPU on AL Core







▶▶ 底板規格 TOP PLATE SIZE AND BOLT HOLE SPACING

腳輪尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安裝尼帽尺寸 Attaching Bolt Size
5" 6" 8"	110 x 140 mm (4-11/32" x 5-1/2")	75 x 110 mm(常規標準底板) (2-15/16" x 4-11/32")	12 mm (1/2")
	110 x 140 mm (4-11/32" x 5-1/2")	80 x 105 mm(歐洲底板) (3-5/32" x 4-1/8")	12 mm (1/2")
	130 x 130 mm (5-1/8" x 5-1/8")	105 x 105 mm (4-1/8" x 4-1/8")	9 mm (3/8")
	130 x 130 mm (5-1/8" x 5-1/8")	105 x 105 mm (4-1/8" x 4-1/8")	12 mm (1/2")
	130 x 165 mm (5-1/8" x 6-1/2")	100 x 130 mm (3-15/16" x 5-1/8")	12 mm (1/2")
	114 x 159 mm (4-1/2" x 6-1/4")	73.8 x 129.4 mm (2-29/32" x 5-3/32")	12 mm (1/2")
10"	130 x 167 mm (5-1/8" x 6-9/16")	85 x 140 mm (3-11/32" x 5-1/2")	12 mm (1/2")
12"	130 x 167 mm (5-1/8" x 6-9/16")	85 x 140 mm (3-11/32" x 5-1/2")	12 mm (1/2")









輪徑×輪寬 Diameter×Width	載重 Load	材質 Material	型號			軸承 Bearing	總高 Overall Height	迴旋半徑 Swivel radius
			固定	活動	煞車			
125mm x 40mm (5"x1-9/16")	340 kgs (750 lbs)	鐵芯聚氨酯 PU on Cast	1152-05-33-1	1152-05-33-2	1152-05-33-4	滾珠軸承 Ball Bearing	170mm (6-11/16")	活動 107 mm Swivel 107mm AK煞 158 mm Swivel W/AK Lock Brake 158mm
	220 kgs (485 lbs)	三星輪 Rubber on Cast	1152-05-03-1	1152-05-03-2	1152-05-03-4			
	300 kgs (660 lbs)	尼龍輪 Nylon	1152-05-07-1	1152-05-07-2	1152-05-07-4			
	300 kgs (660 lbs)	APU輪(圓弧) PU on AL Core (Round)	1152-05-108-1	1152-05-108-2	1152-05-108-4			
	350 kgs (770 lbs)	鋁芯AQP輪(圓弧) QPU on AL Core (Round)	1152-05-87-1	1152-05-87-2	1152-05-87-4			
	250 kgs (550 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1152-05-04-1	1152-05-04-2	1152-05-04-4			
	250 kgs (550 lbs)	CPD輪 CPD	1152-05-49-1	1152-05-49-2	1152-05-49-4			
	250 kgs (550 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1152-05-11-1	1152-05-11-2	1152-05-11-4			
	250 kgs (550 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1152-05-90-1	1152-05-90-2	1152-05-90-4			
	300 kgs (660 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1152-05-89-1	1152-05-89-2	1152-05-89-4			
	450 kgs (990 lbs)	QPU輪(圓弧) QPU (Round)	1152-05-80-1	1152-05-80-2	1152-05-80-4			
	500 kgs (1100 lbs)	QPU輪(平面) QPU (Flat)	1152-05-80-1	1152-05-80-2	1152-05-80-4			
	340 kgs (750 lbs)	EPU輪(圓弧) EPU (Round Shape)	1152-05-78-1	1152-05-78-2	1152-05-78-4			
	390 kgs (860 lbs)	EPU輪(平面) EPU (Flat Shape)	1152-05-78-1	1152-05-78-2	1152-05-78-4			
	450 kgs (990 lbs)	EQPU輪(圓弧) EQPU (Round Shape)	1152-05-81-1	1152-05-81-2	1152-05-81-4			
500 kgs (1100 lbs)	EQPU輪(平面) EQPU (Flat Shape)	1152-05-81-1	1152-05-81-2	1152-05-81-4				
125mm x 50mm (5" x 2")	400 kgs (880 lbs)	APU輪(平面) PU on AL Core (Flat)	1152-05-108-1	1152-05-108-2	1152-05-108-4			
	450 kgs (990 lbs)	鋁芯AQP輪(平面) QPU on AL Core (Flat)	1152-05-87-1	1152-05-87-2	1152-05-87-4			
	420 kgs (920 lbs)	QPU輪(平面) QPU (Flat)	1152-05-80-1	1152-05-80-2	1152-05-80-4			
	500 kgs (1100 lbs)	EQPU輪(圓弧) EQPU (Round)	1152-05-81-1	1152-05-81-2	1152-05-81-4			
	500 kgs (1100 lbs)	EPU輪(圓弧) EPU (Round)	1152-05-78-1	1152-05-78-2	1152-05-78-4			
125mm x 51mm (5" x 2")	450 kgs (990 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1152-05-101-1	1152-05-101-2	1152-05-101-4			
138mm x 36.5mm (5-7/16"x1-7/16")	700 kgs (1540 lbs)	鑄輪 Cast Iron	1152-06-14-1	1152-06-14-2	—	滾珠軸承 Ball Bearing	191mm (7-17/32")	活動 111 mm Swivel 111mm
150mm x 40mm (6"x1-9/16")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1152-06-04-1	1152-06-04-2	1152-06-04-4	滾珠軸承 Ball Bearing	197mm (7-3/4")	活動 119 mm Swivel 119mm AK煞 160 mm Swivel W/AK Lock Brake 160mm
	400 kgs (880 lbs)	尼龍輪 Nylon	1152-06-07-1	1152-06-07-2	1152-06-07-4			
	350 kgs (770 lbs)	CPD輪 CPD	1152-06-49-1	1152-06-49-2	1152-06-49-4			
	300 kgs (660 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1152-06-11-1	1152-06-11-2	1152-06-11-4			
	300 kgs (660 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1152-06-90-1	1152-06-90-2	1152-06-90-4			
	350 kgs (770 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1152-06-89-1	1152-06-89-2	1152-06-89-4			
	400 kgs (880 lbs)	WMRC輪 WMRC	1152-06-45-1	1152-06-45-2	1152-06-45-4			



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	型號			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定	活動	煞車			
150mm x 42mm (6"x1-5/8")	410 kgs (900 lbs)	鐵芯聚氨酯 PU on Cast	1152-06-33-1	1152-06-33-2	1152-06-33-4	滾珠軸承 Ball Bearing	197mm (7-3/4")	活動 119 mm Swivel 119mm AK煞 160 mm Swivel W/AK Lock Brake 160mm
	400 kgs (880 lbs)	APU輪(圓弧) PU on AL Core (Round)	1152-06-108-1	1152-06-108-2	1152-06-108-4			
	450 kgs (990 lbs)	鋁芯AQPU輪(圓弧) QPU on AL Core (Round)	1152-06-87-1	1152-06-87-2	1152-06-87-4			
	550 kgs (1200 lbs)	QPU輪(圓弧) QPU (Round)	1152-06-80-1	1152-06-80-2	1152-06-80-4			
	600 kgs (1320 lbs)	QPU輪(平面) QPU(Flat)	1152-06-80-1	1152-06-80-2	1152-06-80-4			
	500 kgs (1100 lbs)	VPU輪(圓弧) VPU (Round)	1152-06-82-1	1152-06-82-2	1152-06-82-4			
	670 kgs (1475 lbs)	VQPU輪(圓弧) VQPU (Round Shape)	1152-06-83-1	1152-06-83-2	1152-06-83-4			
	800 kgs (1760 lbs)	鐵芯VXPU輪(圓弧) XPU on Iron Core (Round)	1152-06-91-1	1152-06-91-2	1152-06-91-4			
	410 kgs (900 lbs)	EPU輪(圓弧) EPU (Round)	1152-06-78-1	1152-06-78-2	1152-06-78-4			
	460 kgs (1010 lbs)	EPU輪(平面) EPU (Flat)	1152-06-78-1	1152-06-78-2	1152-06-78-4			
	550 kgs (1200 lbs)	EQPU輪(圓弧) EQPU (Round)	1152-06-81-1	1152-06-81-2	1152-06-81-4			
	600 kgs (1320 lbs)	EQPU輪(平面) EQPU (Flat)	1152-06-81-1	1152-06-81-2	1152-06-81-4			
150mm x 45.5mm (6"x1-13/16")	260 kgs (570 lbs)	三星輪 Rubber on Cast	1152-06-03-1	1152-06-03-2	1152-06-03-4			
150mm x 50mm (6" x 2")	450 kgs (990 lbs)	APU輪(平面) PU on AL Core (Flat)	1152-06(50)-108-1	1152-06(50)-108-2	1152-06(50)-108-4			
	500 kgs (1100 lbs)	鋁芯AQPU輪(平面) QPU on AL Core (Flat)	1152-06(50)-87-1	1152-06(50)-87-2	1152-06(50)-87-4			
	525 kgs (1155 lbs)	QPU輪(平面) QPU(Flat)	1152-06(50)-80-1	1152-06(50)-80-2	1152-06(50)-80-4			
	600 kgs (1320 lbs)	EPU輪(圓弧) EPU (Round)	1152-06(50)-78-1	1152-06(50)-78-2	1152-06(50)-78-4			
	600 kgs (1320 lbs)	EQPU輪(圓弧) EQPU (Round)	1152-06(50)-81-1	1152-06(50)-81-2	1152-06(50)-81-4			
150mm x 51mm	550 kgs (1210 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1152-06-101-1	1152-06-101-2	1152-06-101-4			
180mm x 44mm (7" x 1-3/4")	450 kgs (990 lbs)	APU輪(圓弧) PU on AL Core (Round)	1152-07-108-1	1152-07-108-2	1152-07-108-4	滾珠軸承 Ball Bearing	238mm (9-3/8")	活動 154 mm Swivel 154mm AK煞 179 mm Swivel W/AK Lock Brake 179mm
	600 kgs (1320 lbs)	鋁芯AQPU輪(圓弧) QPU on AL Core (Round)	1152-07-87-1	1152-07-87-2	1152-07-87-4			
180mm x 50mm (7" x 2")	450 kgs (990 lbs)	鐵芯聚氨酯 PU on Cast	1152-07-33-1	1152-07-33-2	1152-07-33-4	滾珠軸承 Ball Bearing	238mm (9-3/8")	活動 154 mm Swivel 154mm AK煞 179 mm Swivel W/AK Lock Brake 179mm
	600 kgs (1320 lbs)	QPU輪(圓弧) QPU(Round)	1152-07-80-1	1152-07-80-2	1152-07-80-4			
	650 kgs (1430 lbs)	VPU輪(圓弧) VPU (Round)	1152-07-82-1	1152-07-82-2	1152-07-82-4			
	650 kgs (1430 lbs)	鐵芯VXPU輪(圓弧) XPU on Iron Core (Round)	1152-07-91-1	1152-07-91-2	1152-07-91-4			
	650 kgs (1430 lbs)	VQPU輪(圓弧) VQPU (Round Shape)	1152-07-83-1	1152-07-83-2	1152-07-83-4			
193mm x 46mm (7-3/5"x1-13/16")	300 kgs (660 lbs)	三星輪 Rubber on Cast	1152-08-03-1	1152-08-03-2	—	滾珠軸承 Ball Bearing	244.5mm (9-5/8")	活動 159 mm Swivel 159mm
200mm x 44mm (8"x1-3/4")	350 kgs (770 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1152-08-04-1	1152-08-04-2	1152-08-04-4	滾珠軸承 Ball Bearing	248mm (9-3/4")	活動 164 mm Swivel 164mm AK煞 184 mm Swivel W/AK Lock Brake 184mm
	350 kgs (770 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1152-08-11-1	1152-08-11-2	1152-08-11-4			
	350 kgs (770 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1152-08-90-1	1152-08-90-2	1152-08-90-4			
	400 kgs (880 lbs)	鋁芯QQ橡膠輪 Recilent rubber on AL Core	1152-08-89-1	1152-08-89-2	1152-08-89-4			
200mm x 45.5mm (8"x1-13/16")	550 kgs (1200 lbs)	純輪 Cast Iron	1152-08-14-1	1152-08-14-2	1152-08-14-4			



 輪徑×輪寬 Diameter×Width	 載重 Load	 材質 Material	型號			 軸承 Bearing	 總高 Overall Height	 迴旋半徑 Swivel radius
			固定	活動	煞車			
200mm x 50mm (8" x 2")	450 kgs (990 lbs)	鐵芯聚氨酯 PU on Cast	1152-08-33-1	1152-08-33-2	1152-08-33-4	滾珠軸承 Ball Bearing	248mm (9-3/4")	活動 164 mm Swivel 164mm AK煞 184 mm Swivel W/AK Lock Brake 184mm
	450 kgs (990 lbs)	尼龍輪 Nylon	1152-08-07-1	1152-08-07-2	1152-08-07-4			
	750 kgs (1650 lbs)	鐵芯聚氨酯(2050A/2050B) PU on Cast (2050A/2050B)	1152-08-62-1	1152-08-62-2	1152-08-62-4			
	400 kgs (880 lbs)	CPD輪 CPD	1152-08-49-1	1152-08-49-2	1152-08-49-4			
	450 kgs (990 lbs)	WMRC輪 WMRC	1152-08-45-1	1152-08-45-2	1152-08-45-4			
	500 kgs (1100 lbs)	APU輪(圓弧) PU on AL Core (Round)	1152-08-108-1	1152-08-108-2	1152-08-108-4			
	550 kgs (1200 lbs)	APU輪(平面) PU on AL Core (Flat)	1152-08-108-1	1152-08-108-2	1152-08-108-4			
	650 kgs (1430 lbs)	鋁芯AQPU輪(圓弧) QPU on AL Core (Round)	1152-08-87-1	1152-08-87-2	1152-08-87-4			
	700 kgs (1540 lbs)	鋁芯AQPU輪(平面) QPU on AL Core (Flat)	1152-08-87-1	1152-08-87-2	1152-08-87-4			
	670 kgs (1475 lbs)	QPU輪(圓弧) QPU (Round)	1152-08-80-1	1152-08-80-2	1152-08-80-4			
	720 kgs (1580 lbs)	QPU輪(平面) QPU (Flat)	1152-08-80-1	1152-08-80-2	1152-08-80-4			
	670 kgs (1475 lbs)	VPU輪(圓弧) VPU (Round)	1152-08-82-1	1152-08-82-2	1152-08-82-4			
	800 kgs (1760 lbs)	VQPU輪(圓弧) VQPU (Round)	1152-08-83-1	1152-08-83-2	1152-08-83-4			
	1100 kgs (2420 lbs)	鐵芯VXPU輪(圓弧) XPU on Iron Core (Round)	1152-08-91-1	1152-08-91-2	1152-08-91-4			
	650 kgs (1430 lbs)	EPU輪(圓弧) EPU (Round Shape)	1152-08-78-1	1152-08-78-2	1152-08-78-4			
	700 kgs (1540 lbs)	EPU輪(平面) EPU (Flat Shape)	1152-08-78-1	1152-08-78-2	1152-08-78-4			
	750 kgs (1650 lbs)	EQPU輪(圓弧) EQPU (Round Shape)	1152-08-81-1	1152-08-81-2	1152-08-81-4			
800 kgs (1760 lbs)	EQPU輪(平面) EQPU (Flat Shape)	1152-08-81-1	1152-08-81-2	1152-08-81-4				
200mm x 51mm (8" x 2")	650 kgs (1430 lbs)	ZQPU輪(雙輪) ZQPU (Dual Wheels)	1152-08-101-1	1152-08-101-2	1152-08-101-4			
250mm x 50mm (10" x 2")	400 kgs (880 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1152-10-04-1	1152-10-04-2	1152-10-04-4	滾珠軸承 Ball Bearing	305mm (12")	活動 193 mm Swivel 193 mm AK煞 205 mm Swivel W/AK Lock Brake 205mm
	400 kgs (880 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1152-10-11-1	1152-10-11-2	1152-10-11-4			
	600 kgs (1320 lbs)	鐵芯聚氨酯 PU on Cast	1152-10-33-1	1152-10-33-2	1152-10-33-4			
	800 kgs (1760 lbs)	尼龍輪 Nylon	1152-10-07-1	1152-10-07-2	1152-10-07-4			
250mm x 62mm (10"x2-7/16")	400 kgs (880 lbs)	鐵芯NBR橡膠輪 NBR Rubber on Cast	1152-10(62)-04-1	1152-10(62)-04-2	1152-10(62)-04-4			
	400 kgs (880 lbs)	環保NBR橡膠輪 Non-marking Rubber on Cast	1152-10(62)-11-1	1152-10(62)-11-2	1152-10(62)-11-4			
	600 kgs (1320 lbs)	鐵芯聚氨酯 PU on Cast	1152-10-33-1	1152-10-33-2	1152-10-33-4			
	400 kgs (880 lbs)	環保牽引NBR輪 Non-marking NBR Rubber on Cast	1152-10-90-1	1152-10-90-2	1152-10-90-4			
	900 kgs (1980 lbs)	QPU輪(圓弧) QPU (Round)	1152-10-80-1	1152-10-80-2	1152-10-80-4			
	900 kgs (1980 lbs)	QPU輪(平面) QPU (Flat)	1152-10-80-1	1152-10-80-2	1152-10-80-4			
	1000 kgs (2200 lbs)	VPU輪(圓弧) VPU (Round)	1152-10-82-1	1152-10-82-2	1152-10-82-4			
	1200 kgs (2640 lbs)	VQPU輪(圓弧) VQPU (Round)	1152-10-83-1	1152-10-83-2	1152-10-83-4			
	1500 kgs (3300 lbs)	鐵芯VXPU輪 XPU on Iron Core	1152-10-91-1	1152-10-91-2	1152-10-91-4			