

APU系列 重型輪 PU外包+鋁芯

	輪面硬度		92° shore A
	溫度範圍		-30°C to +70°C
	滾動順暢		優秀
	音量		良好
	保護地板		良好



輪面

由高品質聚氨酯製成。得勝硬度92°的PU輪不僅能提供良好的地板保護作用，而且低噪音。得勝PU輪有著優秀的抗水解特性，適用熱帶地區及潮濕的工作環境。

輪框

內框：鋁芯

特色

- 抗化學、溶劑及侵蝕
- 耐磨
- 抗微生物
- 適用環境溫度：-30°C ~ +70°C
- 在正常使用情況下，無需維修



品號	輪徑 (D)[mm]	輪寬 (T2)[mm]	載重 [kg(lbs)]	軸承內徑 Ø(d)[mm]	中寬 (T1)[mm]	輪面	軸承	
12035903130100	75	29	150 kgs (330lbs)	17	29	圓弧	精密滾珠 軸承	
12035903135300	75	30	150 kgs (330lbs)	12	32			
12035903135171	80	30	180 kgs (396lbs)	12	32			
12035903135271	80	30	180 kgs (396lbs)	15	32			
12035904135171	100	31	230 kgs (507lbs)	15	32			
12035904135271	100	31	230 kgs (507lbs)	17	32			
12035904155171	100	36	325 kgs (716lbs)	12	36			
12035904155271	100	36	325 kgs (716lbs)	15	36			
12035904155371	100	40	350 kgs (771lbs)	12	40			
12035904155471	100	40	350 kgs (771lbs)	15	40			
12035905135171	125	31	280 kgs (617lbs)	15	32			
12035905135271	125	31	280 kgs (617lbs)	17	32			
12035905135371	125	40	350 kgs (771lbs)	15	40			
12035905135471	125	40	350 kgs (771lbs)	17	40			
12037005180100	125	40	350 kgs (771lbs)	20	49			
12035906185171	150	42	450 kgs (992lbs)	17	42			
12035906185271	150	42	450 kgs (992lbs)	20	42			
12035956185171	160	42	500 kgs (1102lbs)	17	42			
12035956185271	160	42	500 kgs (1102lbs)	20	42			
12035907185171	180	44	600 kgs (1323lbs)	20	44			
12035907185271	180	44	600 kgs (1323lbs)	25	44			
12035908205171	200	50	800 kgs (1764lbs)	20	50			
12035908205271	200	50	800 kgs (1764lbs)	25	50			
12035902105100	50	25	100 kgs (220lbs)	17	25	平面		精密滾珠 軸承
12035904205171	100	50	300 kgs (661lbs)	17	50			
12035904205271	100	50	300 kgs (661lbs)	20	50			
12035905205171	125	50	450 kgs (992lbs)	17	50			
12035905205271	125	50	450 kgs (992lbs)	20	50			
12035906205171	150	50	500 kgs (1102lbs)	17	50			
12035906205271	150	50	500 kgs (1102lbs)	20	50			
12035956205171	160	50	550 kgs (1213lbs)	17	50			
12035956205271	160	50	550 kgs (1213lbs)	20	50			
12035908185100	200	44	700 kgs (1543lbs)	20	44			
12035908205371	200	50	800 kgs (1764lbs)	20	50			
12035908205471	200	50	800 kgs (1764lbs)	25	50			

