

藍色彈力全效輪

*顏色可依客人喜好客製

輪面硬度					68°±5° Shore A
溫度範圍					-20°C to +60°C
滾動順暢					非常優秀
音量					非常優秀
保護地板					非常優秀



輪面

為熱塑性橡膠彈性體 (TPR)，便於保護地面，無痕，操作舒適，承受大載重，滾動阻力和旋轉阻力小，耐許多侵蝕性物質的腐蝕。顏色：灰色。
硬度為 68°±5° Shore A°
與輪體的化學黏合不可分解。

特色

- 大載重，保護地面，正常使用免維護。
- 適用溫度範圍：-20° C至 +60° C。

輪體

採用優質耐衝擊聚丙烯。



品號	輪徑 (D)[mm]	輪寬 (T2)[mm]	載重 [kg(lbs)]	軸承內徑 Ø(d)[mm]	中寬 (T1)[mm]	軸承
12024523133200	80	32	120kgs (264lbs)	12	43.6	中管
12024523133174	80	32	120kgs (264lbs)	8	41	滾珠軸承
12024523133173	80	32	120kgs (264lbs)	10	41	滾珠軸承
12024523133172	80	32	120kgs (264lbs)	8	46	滾珠軸承
12024523133171	80	32	120kgs (264lbs)	10	46	滾珠軸承
12024504153174	100	34	150kgs (330lbs)	8	41	滾珠軸承
12024504153173	100	34	150kgs (330lbs)	10	41	滾珠軸承
12024504153172	100	34	150kgs (330lbs)	8	46	滾珠軸承
12024504153171	100	34	150kgs (330lbs)	10	46	滾珠軸承
12024504153176	100	34	150kgs (330lbs)	8	50	滾珠軸承
12024504153175	100	34	150kgs (330lbs)	10	50	滾珠軸承
12024505153174	125	36	180kgs (396lbs)	8	41	滾珠軸承
12024505153173	125	36	180kgs (396lbs)	10	41	滾珠軸承
12024505153172	125	36	180kgs (396lbs)	8	46	滾珠軸承
12024505153171	125	36	180kgs (396lbs)	10	46	滾珠軸承
12054505153176	125	36	180kgs (396lbs)	8	50	滾珠軸承
12024505153175	125	36	180kgs (396lbs)	10	50	滾珠軸承
12024536191171	160	48	300kgs (661lbs)	20	60	滾針軸承
12024536193171	160	48	300kgs (661lbs)	20	58	滾珠軸承
12024508191171	200	48	325kgs (716lbs)	20	60	滾針軸承
12024508193171	200	48	325kgs (716lbs)	20	58	滾珠軸承

