



HDR&WHDR輪

	輪面硬度		95°±5° Shore A
	溫度範圍		-20°C to +60°C
	滾動順暢		非常優秀
	音量		良好
	保護地板		良好



輪面

為熱塑性橡膠彈性體 (TPR)，便於保護地面，無痕，操作舒適，承受大載重，滾動阻力和旋轉阻力小，耐許多侵蝕性物質的腐蝕。顏色：灰色。
硬度為 95°±5° Shore A。
與輪體的化學黏合不可分解。

輪體

採用優質耐衝擊聚丙烯。

特色

- 大載重，保護地面，正常使用免維護。
- 適用溫度範圍：-20° C至 +60° C。



中輕型 HDR



品號	輪徑 (D) [mm]	輪寬 (T2) [mm]	載重 [kg(lbs)]	軸承內徑 Ø(d) [mm]	中寬 (T1) [mm]	輪面	軸承
1235030017	3" (75mm)	1" (27mm)	90kg / 200lbs	Ø 6mm	33mm	圓弧	滾珠軸承
1235030018	3" (75mm)	1-1/4" (31mm)	120kg / 265lbs	Ø 10mm	41mm		
1235040005	4" (100mm)	1-1/4" (31mm)	160kg / 350lbs	Ø 10mm	41mm		
1235050004	5" (125mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		
1235060016	6" (150mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		

中輕型 WHDR



品號	輪徑 (D) [mm]	輪寬 (T2) [mm]	載重 [kg(lbs)]	軸承內徑 Ø(d) [mm]	中寬 (T1) [mm]	輪面	軸承
1235030019	3" (75mm)	1-1/4" (31mm)	140kg / 310lbs	Ø 10mm	41mm	平面	滾珠軸承
1235040014	4" (100mm)	1-1/4" (31mm)	180kg / 400lbs	Ø 10mm	41mm		
1235050016	5" (125mm)	1-1/4" (31mm)	200kg / 440lbs	Ø 10mm	41mm		
1235060017	6" (150mm)	1-1/4" (31mm)	200kg / 440lbs	Ø 10mm	41mm		

重型 HDR

 品號	 輪徑 (D)[mm]	 輪寬 (T2)[mm]	 載重 [kg(lbs)]	 軸承內徑 Ø(d)[mm]	 中寬 (T1)[mm]	 輪面	 軸承	
1235040019	4" (100mm)	2" (50mm)	228kg / 500lbs	Ø 13mm	62mm	圓弧	精密 長珠 軸承	
1235050037	5" (125mm)	2" (50mm)	261kg / 575lbs	Ø 13mm	62mm			
1235060018	6" (150mm)	2" (50mm)	295kg / 650lbs	Ø 13mm	62mm			
1235080008	8" (200mm)	2" (50mm)	318kg / 700lbs	Ø 13mm	62mm			
1235040029	4" (100mm)	2" (50mm)	270kg / 600lbs	Ø 13mm	62mm	平面		
1235050038	5" (125mm)	2" (50mm)	340kg / 750lbs	Ø 13mm	62mm			
1235060019	6" (150mm)	2" (50mm)	408kg / 900lbs	Ø 13mm	62mm			
1235080009	8" (200mm)	2" (50mm)	430kg / 950lbs	Ø 13mm	62mm			

重型 WHDR



品號	輪徑 (D) [mm]	輪寬 (T2) [mm]	載重 [kg(lbs)]	軸承內徑 Ø(d) [mm]	中寬 (T1) [mm]	輪面	軸承
1235040030	4" (100mm)	2" (50mm)	270kg / 600lbs	Ø 13mm	62mm	平面	精密 長珠 軸承
1235050039	5" (125mm)	2" (50mm)	340kg / 750lbs	Ø 13mm	62mm		
1235060020	6" (150mm)	2" (50mm)	408kg / 900lbs	Ø 13mm	62mm		
1235080010	8" (200mm)	2" (50mm)	430kg / 950lbs	Ø 13mm	62mm		