

PU系列

物料搬運/手推車用聚氨酯輪(美式)

	輪面硬度		94°±3° Shore A
	溫度範圍		-30°C to +70°C
	滾動順暢		優秀
	音量		良好
	保護地板		非常優秀



輪面

優質熱塑性橡膠聚氨酯 (TPU)，便於保護地板，吸收震動，無痕，不染色，具有彈性，非常耐磨擦，滾動阻力小，耐許多侵蝕性物質的腐蝕。顏色灰色。硬度為 94°±3° Shore A。在高於+35° C的環境溫度下承載能力下降。

特色

- 耐磨，運轉低阻力，正常使用免維護。
- 適用溫度範圍：-30° C至 +70° C。

輪體

採用優質耐沖擊聚丙烯。



中輕型

 品號	 輪徑 (D) [mm]	 輪寬 (T2) [mm]	 載重 [kg(lbs)]	 軸承內徑 Ø(d) [mm]	 中寬 (T1) [mm]	 輪面	 軸承
12033103133300	3"(75mm)	1-1/4"(31mm)	90kgs / 200lbs	10	41	圓弧	中管
12033104133973	4"(100mm)	1-1/4"(31mm)	120kgs / 265lbs	8	41	圓弧	滾珠軸承
12033105133274	5"(125mm)	1-1/4"(31mm)	120kgs / 265lbs	8	41	圓弧	滾珠軸承
12033106133973	6"(150mm)	1-1/4"(31mm)	130kgs / 285lbs	8	41	圓弧	滾珠軸承