

PP



	輪面硬度		65°±5° Shore A
	溫度範圍		-10°C to +60°C
	滾動順暢		非常優秀
	音量		良好
	保護地板		良好

輪面

PP 化學名聚丙烯，耐熱性好，剛硬有韌性，抗疲勞，抗應力開裂，不受濕度環境影響，耐腐蝕，耐油，耐酸，耐鹼等有機溶劑，無氣味並可回收；輪子載重大，滾動阻力小。

PP適用溫度範圍：-10°C~+60°C。硬度為65°±5°share D

特色

- 運轉低阻力
- 適用溫度範圍：-10°C~+60°C
- 正常使用免維護



品號	輪徑 (D) [mm]	輪寬 (T2) [mm]	載重 [kg(lbs)]	軸承內徑 Ø(d) [mm]	中寬 (T1) [mm]	輪面
12022951080200	38	16.5	20kgs(44lbs)	6	20.5	圓弧
12022902006200	50	21	25kgs(55lbs)	6.2	24	
12022952081200	65	25	30kgs(66lbs)	6	30.5	
12022952004100	65	25	30kgs(66lbs)	8	30.5	
12022952130100	62.5	35	30kgs(66lbs)	10.2	39	
12022903131500	76	32	35kgs(77lbs)	10.2	39.5	
12022903137100	75	25	35kgs(77lbs)	8	30	
12022904151400	100	35	90kgs(198lbs)	13	35	
12022904154100	100	35	90kgs(198lbs)	13	35	
12022904100100	100	25	90kgs(198lbs)	8	30.5	
12022905201300	125	48	100kgs(220lbs)	10.2	54.5	
12022905130100	125	35	100kgs(220lbs)	13	39	平面