

三星橡膠輪系列

彈力橡膠外包+鐵芯/鑄鐵芯

	輪面硬度		80°± 5° shore A
	溫度範圍		-20°C to +120°C
	滾動順暢		優秀
	音量		非常優秀
	保護地板		非常優秀



輪面

由高品質的彈力橡膠製成，得勝鐵芯橡膠輪輪面硬度是85°±5°，具有極佳的操作舒適性，優秀的地板保護作用及避震功能。顏色：黑色。

輪框

內框：鐵芯/鑄鐵芯

特色

- 抗化學、溶劑及侵蝕
- 適用環境溫度：-25°C ~ +80°C
- 在正常使用情況下，無需維修



品號	輪徑 (D) [mm]	輪寬 (T2) [mm]	載重 [kg(lbs)]	軸承內徑 Ø(d) [mm]	中寬 (T1) [mm]	輪面	軸承
12040303136171	72	35	90kgs (198lbs)	12	35	弧形	精密滾珠 軸承
12040304151171	100	35	150kgs (330lbs)	15	35		
12040304152171	100	35	150kgs (330lbs)	17	35		
12040305152471	125	35	150kgs (330lbs)	15	35		
12040305152571	125	35	150kgs (330lbs)	17	35		
12040305151371	125	40	200kgs (440lbs)	15	40		
12040305152171	125	40	200kgs (440lbs)	17	40		
12040306186571	144	44	210kgs (463lbs)	17	44.5		
12040306181171	150	45.5	230kgs (507lbs)	17	44.5		
12040306306171	150	57	250kgs (551lbs)	17	57		
12040308181171	193	46	260kgs (573lbs)	17	46		
12040308182171	193	46	260kgs (573lbs)	20	46		

