



1106 Series 中型

仪器系列(TW)

Medical Caster

- 采用特别脚架荷重结构设计, 超大波盘结构转动灵活, 刹车制动效果良好, 刹车采用加纤塑料双踏板, 弹片采用高张力钢制成, 不会因为长期使用而变形。
- Special yoke design to swivel easily. High performance total lock brake to be activated easily and effectively. Brake pedals are made of fibre-filled plastic with brake mechanism made of high tensile steel to ensure minimum distortion during the long service life.

载重 Load
50-250 kg



» 特色区 Features



仪器新式固定架(咨询工厂)
Reinforced Rigid Fork(consult factory)



90度定向刹车架
90° Directional Lock



180度定向刹车架
180° Directional Lock



滚珠轴承
Ball Bearing

滚珠轴承
Ball Bearing



中管
Plain Bearing



尼龙双踏板
Total Lock Brake
with Dual Nylon Pedals



尼龙双踏板(长踏板)
Total Lock Brake (Long Pedal)



角铁底板
Angle Bar Plate

» 轮子选项 Wheel Options

高科技耐磨聚氨酯
PU on PP Core

铝芯橡胶轮
Rubber on Aluminum Core

超级人造胶(514)
TPR on PP Core

尼龙轮
Nylon

NPPR轮
NPPR

W超级人造胶
WPPR

WMRC轮
WMRC

CPD轮
CPD

超级人造胶(515)
TPR on PP Core

铝芯AQP
QPU on AL Core



橡胶轮
Rubber



塑料轮
PP



导电轮
E-Conductive



耐高温轮
Hi-temp



W全效轮
W Resolute Wheel



全效轮(514)
Resolute Wheel



WPP轮
WPP



蓝色弹力轮
Blue Resilient Rubber Wheel



WHDR轮
WHDR



全效轮 (515)
Resolute



超级人造胶(大圆弧)
TPR on PP Core (Donut)



全效轮(大圆弧)
Resolute (Donut)



» 底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

编号 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
1	69 x 96 mm (2-23/32" x 3-25/32")	45 x 75 mm (高级架底板) 1-3/4" x 3"	6.35 mm (1/4")
2	72 x 91 mm (2-13/16" x 3-19/32")	53 x 72 mm (医疗/仪器架底板) 2-1/8" x 2-7/8"	6.35 mm (1/4")
3	77 x 66.5 mm (3" x 2-5/8")	59 x 49 mm (TW) 2-5/16" x 1-15/16"	6.35 mm (1/4")
4	69 x 96 mm (2-23/32" x 3-25/32")	49 x 74.5 mm (斜孔底板) (1-15/16" x 2-15/16")	8 mm (5/16")
5	93 x 110 mm (3"-5/8" x 4-3/8")	70 x 85 mm (重型架底板) 2-5/8"~3" x 3"~3-5/8" (Heavy Duty Plate)	9.5 mm (3/8")

» 插杆规格 CYLINDRICAL STEM SPECIFICATION

编号 Suffix	插杆直径x长度 Diameter x Length	编号 Suffix	插杆直径x长度 Diameter x Length
3"~6"	11 x 38mm (TW)	3"~6"	21.9 x 56mm (TW) 0.862" diameter x 2-3/16"
3"~6"	27 x 63mm (TW) 1-1/16" diameter x 2-31/64"	3"~6"	28 x 45mm (TW) 1-7/64" diameter x 1-49/64"

» 丝扣规格 THREADED STEM SPECIFICATION

編號 Suffix	絲扣牙徑X長度 Threaded Size	編號 Suffix	絲扣牙徑X長度 Threaded Size
3"~6"	3/8-16UNC x 32mm (TW)	3"~6"	1/2-12UNC x 32mm (TW)
3"~6"	5/8-11UNC x 32mm (TW)	3"~6"	M12-1.75 x 32mm (TW)

» 空铆规格 SINGLE BOLT HOLE

编号 Suffix	孔径 Centre Hole	编号 Suffix	孔径 Centre Hole
3"~6"	10.5mm (TW)(for 3/8" & M10 shaft)	3"~6"	12.5mm (TW)(for M12 shaft)
3"~6"	13mm (TW)(for 1/2" shaft)		

» 角铁底板规格 ANGLE BAR PLATE SPECIFICATION

2孔规格 Two Holes Specification	3孔规格 Three Holes Specification



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius	
			固定 Fixed	活动 Swivel	刹车 Brake				
75mm x 24mm (3" x 1 ")	40 kgs (88 lbs)	超级人造胶 TPR on PP Core	1106-R-03-75-1	1106-R-03-75-2	1106-R-03-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 112mm (4-7/16")		
	50 kgs (110 lbs)	全效轮 Resolute	1106-R-03-68-1	1106-R-03-68-2	1106-R-03-68-4				
75mm x 32mm (3"-1-1/4")	90 kgs (198 lbs)	超级人造胶 TPR on PP Core	1106-03-75-1	1106-03-75-2	1106-03-75-4	中管 Plain Bearing	丝扣类总高 Threaded Stem OAH: 113mm (4-29/64") 插杆类总高 Cylindrical Stem OAH: 110mm (4-21/64") 两孔角铁底板总高 Two holes angle bar plate OAH: 110mm (4-21/64") 三孔角铁底板总高 Three holes angle bar plate OAH: 139mm (5-15/32")	活动 74mm 双煞(一般踏板) 107mm 双煞(长踏板) 123mm Swivel 74mm Swivel W/Total lock(regular pedal) 107mm Swivel W/Total lock(long pedal) 123mm	
	160 kgs (352 lbs)	铝芯AQP QPU on AL Core	1106-03-87-1	1106-03-87-2	1106-03-87-4	滚珠 Ball Bearing			
	90 kgs (198 lbs)	W超级人造胶 WPPR	1106-03-47-1	1106-03-47-2	1106-03-47-4				
	90 kgs (198 lbs)	全效轮 Resolute	1106-03-68-1	1106-03-68-2	1106-03-68-4				
	110 kgs (250 lbs)	W全效轮 W Resolute	1106-03-48-1	1106-03-48-2	1106-03-48-4				
	80 kgs (175 lbs)	导电轮 E-Conductive	1106-03-17-1	1106-03-17-2	1106-03-17-4				
	160 kgs (352 lbs)	WMRC轮 WMRC	1106-03-45-1	1106-03-45-2	1106-03-45-4				
	70 kgs (155 lbs)	橡胶轮 Rubber	1106-03-06-1	1106-03-06-2	1106-03-06-4				中管 Plain Bearing
	90 kgs (198 lbs)	塑料轮 PP	1106-03-29-1	1106-03-29-2	1106-03-29-4				
100mm x 24mm (4" x 1")	50 kgs (110 lbs)	超级人造胶 TPR on PP Core	1106-R-04-75-1	1106-R-04-75-2	1106-R-04-75-4	滚珠 Ball Bearing			
	55 kgs (121 lbs)	全效轮 Resolute	1106-R-04-68-1	1106-R-04-68-2	1106-R-04-68-4				
100mmx32mm (4"x1-1/4")	120 kgs (265 lbs)	高科技耐磨聚氨酯 PU on PP Core	1106-04-31-1	1106-04-31-2	1106-04-31-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 137mm (5-25/64") 丝扣类总高 Threaded Stem OAH: 138mm (5-7/16") 插杆类总高 Cylindrical Stem OAH: 135mm (5-5/16") 两孔角铁底板总高 Two holes angle bar plate OAH: 136mm (5-23/64") 三孔角铁底板总高 Three holes angle bar plate OAH: 155mm (6-7/64")	活动 89mm 双煞(一般踏板) 106mm 双煞(长踏板) 122mm 侧煞 95mm Swivel 89mm Swivel W/Total lock(regular pedal) 106mm Swivel W/Total lock(long pedal) 122mm Swivel W/Side Brake 95mm	
	100 kgs (220 lbs)	超级人造胶 TPR on PP Core	1106-04-75-1	1106-04-75-2	1106-04-75-4				中管 Plain Bearing
	80kgs (175lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1106-04-110-1	1106-04-110-2	1106-04-110-4				
	90kgs (198lbs)	全效轮(大圆弧) Resolute (Donut)	1106-04-111-1	1106-04-111-2	1106-04-111-4				
	125kgs (275 lbs)	全效轮 Resolute	1106-04-68-1	1106-04-68-2	1106-04-68-4	滚珠 Ball Bearing			
	80 kgs (176 lbs)	导电轮 E-Conductive	1106-04-17-1	1106-04-17-2	1106-04-17-4				
	135kgs (300 lbs)	W全效轮 W Resolute	1106-04-48-1	1106-04-48-2	1106-04-48-4				
	180kgs (400 lbs)	WHDR轮 WHDR	1106-04-66-1	1106-04-66-2	1106-04-66-4				
	100kgs (220 lbs)	W超级人造胶 WPPR	1106-04-47-1	1106-04-47-2	1106-04-47-4				
	180kgs (396 lbs)	WMRC轮 WMRC	1106-04-45-1	1106-04-45-2	1106-04-45-4				
	130kgs (285 lbs)	WPP轮 WPP	1106-04-46-1	1106-04-46-2	1106-04-46-4				
	135 kgs (300 lbs)	铝芯橡胶轮 Rubber on Aluminum Core	1106-04-22-1	1106-04-22-2	1106-04-22-4				
	200kgs (440 lbs)	铝芯AQP QPU on AL Core	1106-04-87-1	1106-04-87-2	1106-04-87-4				
	70kgs (154lbs)	NPPR轮 NPPR	1106-04-67-1	1106-04-67-2	1106-04-67-4				中管 Plain Bearing
	120 kgs (265 lbs)	尼龙轮 Nylon	1106-04-07-1	1106-04-07-2	1106-04-07-4				
	135 kgs (300 lbs)	耐高温轮 Hi-temp	1106-04-25-1	1106-04-25-2	1106-04-25-4				
	80 kgs (175 lbs)	橡胶轮 Rubber	1106-04-06-1	1106-04-06-2	1106-04-06-4				
	90 kgs (198 lbs)	塑料轮 PP	1106-04-29-1	1106-04-29-2	1106-04-29-4				





 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius	
			固定 Fixed	活动 Swivel	刹车 Brake				
100mmx36mm (4"x1-1/2")	160 kgs (352 lbs)	CPD轮 CPD	1106-04-71-1	1106-04-71-2	1106-04-71-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 137mm (5-25/64") 丝扣类总高 Threaded Stem OAH: 138mm (5-7/16") 插杆类总高 Cylindrical Stem OAH: 135mm (5-5/16") 两孔角铁底板总高 Two holes angle bar plate OAH: 136mm (5-23/64") 三孔角铁底板总高 Three holes angle bar plate OAH: 155mm (6-7/64")	活动 89mm 双煞(一般踏板) 106mm 双煞(长踏板) 122mm 侧煞 95mm Swivel 89mm Swivel W/Total lock(regular pedal) 106mm Swivel W/Total lock(long pedal) 122mm Swivel W/Side Brake 95mm	
	160 kgs (352 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1106-04-50-1	1106-04-50-2	1106-04-50-4				
	140kgs (308lbs)	超级人造胶 TPR on PP Core	1106-04-77-1	1106-04-77-2	1106-04-77-4				
	160kgs (352lbs)	全效轮 Resolute	1106-04-76-1	1106-04-76-2	1106-04-76-4				
	200kgs (440 lbs)	铝芯AQPU QPU on AL Core	1106-04-87-1	1106-04-87-2	1106-04-87-4				
125mm x 24.5mm (5" x 1")	70 kgs (155 lbs)	超级人造胶 TPR on PP Core	1106-R-05-75-1	1106-R-05-75-2	1106-R-05-75-4	滚珠 Ball Bearing			
	80 kgs (175 lbs)	全效轮 Resolute	1106-R-05-68-1	1106-R-05-68-2	1106-R-05-68-4				
125mmx32mm (5"x1-1/4")	130 kgs (285 lbs)	高科技耐磨聚氨酯 PU on PP Core	1106-05-31-1	1106-05-31-2	1106-05-31-4	滚珠 Ball Bearing 中管 Plain Bearing	底板类总高 Plate Version OAH: 162mm (6-3/8") 丝扣类总高 Threaded Stem OAH: 163mm (6-27/64") 插杆类总高 Cylindrical Stem OAH: 160mm (6-19/64") 两孔角铁底板总高 Two holes angle bar plate OAH: 160mm (6-19/64") 三孔角铁底板总高 Three holes angle bar plate OAH: 188mm (7-13/32")	活动 101mm 双煞(一般踏板) 109mm 双煞(长踏板) 125mm 侧煞 101mm Swivel 101mm Swivel W/Total lock(regular pedal) 109mm Swivel W/Total lock(long pedal) 125mm Swivel W/Side Brake 101mm	
	110 kgs (240 lbs)	超级人造胶 TPR on PP Core	1106-05-75-1	1106-05-75-2	1106-05-75-4				
	100kgs (220lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1106-05-110-1	1106-05-110-2	1106-05-110-4				
	120kgs (265lbs)	全效轮(大圆弧) Resolute (Donut)	1106-05-111-1	1106-05-111-2	1106-05-111-4				
	147 kgs (325 lbs)	全效轮 Resolute	1106-05-68-1	1106-05-68-2	1106-05-68-4	滚珠 Ball Bearing			
	90 kgs (198 lbs)	导电轮 E-Conductive	1106-05-17-1	1106-05-17-2	1106-05-17-4				
	147 kgs (325 lbs)	W全效轮 W Resolute	1106-05-48-1	1106-05-48-2	1106-05-48-4				
	180 kgs (400 lbs)	WHDR轮 WHDR	1106-05-66-1	1106-05-66-2	1106-05-66-4				
	110 kgs (240 lbs)	W超级人造胶 WPPR	1106-05-47-1	1106-05-47-2	1106-05-47-4				
	200 kgs (440 lbs)	WMRC轮 WMRC	1106-05-45-1	1106-05-45-2	1106-05-45-4				
	150 kgs (330 lbs)	WPP轮 WPP	1106-05-46-1	1106-05-46-2	1106-05-46-4				
	200kgs (440 lbs)	铝芯AQPU QPU on AL Core	1106-05-87-1	1106-05-87-2	1106-05-87-4				
	140 kgs (305 lbs)	尼龙轮 Nylon	1106-05-07-1	1106-05-07-2	1106-05-07-4				中管 Plain Bearing
	90 kgs (198 lbs)	橡胶轮 Rubber	1106-05-06-1	1106-05-06-2	1106-05-06-4				
	100 kgs (220 lbs)	塑料轮 PP	1106-05-29-1	1106-05-29-2	1106-05-29-4				
125mmx36mm (5"x1-1/2")	200 kgs (440 lbs)	CPD轮 CPD	1106-05-71-1	1106-05-71-2	1106-05-71-4	滚珠 Ball Bearing			
	250 kgs (550 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1106-05-50-1	1106-05-50-2	1106-05-50-4				
	160kgs (352lbs)	超级人造胶 TPR on PP Core	1106-05-77-1	1106-05-77-2	1106-05-77-4				
	180kgs (400lbs)	全效轮 Resolute	1106-05-76-1	1106-05-76-2	1106-05-76-4				





 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
150mmx32mm (6"x1-1/4")	110 kgs (240 lbs)	超级人造胶 TPR on PP Core	1106-06-75-1	1106-06-75-2	1106-06-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 187mm (7-23/64")	活动 113mm 双煞(一般踏板) 113mm 双煞(长踏板) 125mm 侧煞 113mm Swivel 113mm Swivel W/Total lock(regular pedal) 113mm Swivel W/Total lock(long pedal) 125mm Swivel W/Side Brake 113mm
	147 kgs (325 lbs)	全效轮 Resolute	1106-06-68-1	1106-06-68-2	1106-06-68-4		丝扣类总高 Threaded Stem OAH: 188mm (7-13/32")	
	147 kgs (325 lbs)	W全效轮 W Resolute	1106-06-48-1	1106-06-48-2	1106-06-48-4		插杆类总高 Cylindrical Stem OAH: 185mm (7-9/32")	
	200 kgs (440 lbs)	WHDR轮 WHDR	1106-06-66-1	1106-06-66-2	1106-06-66-4		两孔角铁底板总高 Two holes angle bar plate OAH: 184mm (7-1/4")	
	110 kgs (240 lbs)	W超级人造胶 WPPR	1106-06-47-1	1106-06-47-2	1106-06-47-4		三孔角铁底板总高 Three holes angle bar plate OAH: 204mm (8-1/32")	

