



1115-1 Series

经济弹簧轮系列

Economical Spring-loaded Caster


载重 Load
200 - 500 KG

- 属得胜专利产品, 避震, 超重负载, 多款供选择。


採用热处理上下珠道, 增加荷重与产品寿命, 品质、工艺明显优于市场上同类产品。

- DERSHENG patented products, shock-absorbing, heavy-duty, diversified selection.


Made of heat-treated raceways to extend service life and durability, outperforming most competitors.




特色区 Features



AK煞 (For 4", 5", 6", 8")
Swivel W/Center Lock (AK type)



轮子可附金属防尘盖 (供选择)
Metal Thread Guard (optional)



轮子可附塑料防尘盖 (供选择)
Plastic Thread Guard (optional)



PU轮面可以变化硬度
Different PU
tread hardness available

轮子选项 Wheel Options




铁芯聚氨酯
PU on Cast



韩款PU轮
PU on Cast



牵引NBR
NBR Rubber on Cast



QPU轮
QPU



EQPU轮
EQPU



滚珠轴承
Ball Bearing

底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

脚轮尺寸 Caster Size	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装帽尺寸 Attaching Bolt Size
4, 5, 6	100 x 115 mm (4" x 4-1/2")	75x80mm (2-5/8"~3"x3~5/8")	9.5mm (3/8")
	110 x 140mm (4-11/32" x 5-1/2")	75 x 110mm (常规标准底板) (2-15/16" x 4-11/32")	12 mm (1/2")
	110 x 137mm (4-11/32" x 5-13/32")	78 x 105mm (欧洲直孔孔距) (3-5/32" x 4-1/8")	12 mm (1/2")
	110 x 140mm (4-11/32" x 5-1/2")	78 x 105mm (欧洲斜孔孔距) (3-5/32" x 4-1/8")	12 mm (1/2")
	114 x 159 mm (4-1/2" x 6-1/4")	73.8 x 129.4 mm (2-29/32" x 5-3/32")	12 mm (1/2")



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
100mm x 34mm (4" x 1-3/8")	250 kgs (550 lbs)	铁芯聚氨酯 PU on Cast	1115-04-33-1(1)	1115-04-33-1(2)	1115-04-33-1(3)	滚珠轴承 Ball Bearing	173mm (6-13/16")	活动 97mm AK制 155mm Swivel 97mm Swivel W/AK Lock Brake 155mm
100mm x 37mm (4" x 1-1/2")	200 kgs (440 lbs)	牵引NBR轮 NBR Rubber on Cast	1115-04-041(1)	1115-04-04-1(2)	1115-04-04-1(3)			
100mm x 34mm (4" x 1-3/8")	300 kgs (660 lbs)	QPU轮 QPU	1115-04-53-1(1)	1115-04-53-1(2)	1115-04-53-1(3)			
125mm x 45mm (5" x 1-3/4")	350 kgs (770 lbs)	韩款PU轮 PU on Cast	1115-05-33-1(1)	1115-05-33-1(2)	1115-05-33-1(3)	滚珠轴承 Ball Bearing	185mm (7-9/32")	活动 109mm AK制 171mm Swivel 109mm Swivel W/AK Lock Brake 171mm
125mm x 40mm (5" x 1-5/8")	250 kgs (550 lbs)	铁芯聚氨酯 PU on Cast	1115-05-33-1(1)	1115-05-33-1(2)	1115-05-33-1(3)			
125mm x 40mm (5" x 1-5/8")	300 kgs (660 lbs)	牵引NBR轮 NBR Rubber on Cast	1115-05-04-1(1)	1115-05-04-1(2)	1115-05-04-1(3)			
125mm x 40mm (5" x 1-5/8")	400 kgs (880 lbs)	QPU轮 QPU	1115-05-53-1(1)	1115-05-53-1(2)	1115-05-53-1(3)	滚珠轴承 Ball Bearing	207mm (8-5/32")	活动 107mm AK制 169mm Swivel 107mm Swivel W/K Lock Brake 169mm
125mm x 40mm (5" x 1-5/8")	450 kgs (991 lbs)	EQPU轮 EQPU	1115-05-55-1(1)	1115-05-55-1(2)	1115-05-55-1(3)			
150mm x 45mm (6" x 1-3/4")	420 kgs (925 lbs)	韩款PU轮 PU on Cast	1115-06-33-1(1)	1115-06-33-1(2)	1115-06-33-1(3)	滚珠轴承 Ball Bearing	198mm (7-25/32")	活动 122mm AK制 192mm Swivel 122mm Swivel W/AK Lock Brake 192mm
150mm x 42mm (6" x 1-5/8")	400 kgs (880 lbs)	铁芯聚氨酯 PU on Cast	1115-06-33-1(1)	1115-06-33-1(2)	1115-06-33-1(3)			
150mm x 42mm (6" x 1-5/8")	300 kgs (660 lbs)	牵引NBR轮 NBR Rubber on Cast	1115-06-04-1(1)	1115-06-04-1(2)	1115-06-04-1(3)			
150mm x 42mm (6" x 1-5/8")	500 kgs (1100 lbs)	QPU轮 QPU	1115-06-53-1(1)	1115-06-53-1(2)	1115-06-53-1(3)	滚珠轴承 Ball Bearing	220mm (8-21/32")	活动 120mm AK制 190mm Swivel 120mm Swivel W/AK Lock Brake 190mm
150mm x 42mm (6" x 1-5/8")	500 kgs (1100 lbs)	EQPU轮 EQPU	1115-06-55-1(1)	1115-06-55-1(2)	1115-06-55-1(3)			