



1129 Series 中型

医疗系列(CN)

Medical Caster

- 采用特别脚架荷重结构设计, 超大波盘结构转动灵活, 刹车制动效果良好, 刹车采用尼龙加纤双踏板或铝踏板, 弹片全部采用不锈钢制成, 不会因长期使用而变形、生锈。
- Special yoke design to swivel easily. High performance total lock brake to be actiated easily and effectively. Brake pedals are made of fibre-filled plastic on strength-enhanced aluminum alloy. Stainless steel brake chips are of good rust resistance.

载重 Load
50-250 kg



» 特色區 Features



90度定向刹车架
90° Directional Lock



180度定向刹车架
180° Directional Lock



尼龙双踏板
Total Lock Brake
with Dual Nylon Pedals



铝刹
Total Lock Brake
with Aluminum Alloy Pedal



波盘防尘盖
Swivel Dust Cover



防尘护套
Housing Cover



滚珠轴承
Ball Bearing

滚珠轴承
Ball Bearing



中管
Plain Bearing

» 轮子选项 Wheel Options



高科技耐磨聚氨酯
PU on PP Core



铝芯橡胶轮
Rubber on Aluminum Core



超级人造胶 (514)
TPR on PP Core



尼龙轮
Nylon



NPPR轮
NPPR



W超级人造胶
WPPR



WMRC轮
WMRC



CPD轮
CPD



超级人造胶 (515)
TPR on PP Core



铝芯AQPU
QPU on AL Core



橡胶轮
Rubber



塑料轮
PP



导电轮
E-Conductive



耐高温轮
Hi-temp



W全效轮
W Resolute Wheel



全效轮 (514)
Resolute Wheel



WPP轮
WPP



蓝色弹力轮
Blue Resilient Rubber Wheel



WHDR轮
WHDR



全效轮 (515)
Resolute



超级人造胶 (大圆弧)
TPR on PP Core (Donut)



全效轮 (大圆弧)
Resolute (Donut)



» 底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

编号 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
1	64 x 64 mm (2-1/2"x 2-1/2")	48 x 48 mm (只有3"适用) 1-7/8"x1-7/8"(3"Caster only)	6 mm (3/16")
2	69 x 96 mm (2-23/32"x 3-25/32")	45 x 75 mm (高级架底板) 1-3/4"x 3"	6.35 mm (1/4")
3	72 x 91 mm (2-13/16"x 3-19/32")	53 x 72 mm (医疗/仪器架底板) 2-1/8"x 2-7/8"	6.35 mm (1/4")
4	80 x 105 mm (3-1/8"x 4-1/8")	60 x 85 mm (美规底板) 2-3/8"x 3-7/16"(American Plate)	8 mm (5/16")
5	85 x 105 mm (3-5/16"x 4-1/8")	60 x 80 mm (欧规孔距) 2-3/8"x 3-1/8"(European Plate)	8 mm (5/16")
6	93 x 110 mm (3-5/8" x 4-3/8")	70 x 85 mm (重型架底板) 2-5/8"~3" x 3"~3-5/8" (Heavy Duty Plate)	9.5 mm (3/8")

» 插杆规格 CYLINDRICAL STEM SPECIFICATION

编号 Suffix	插杆直径x长度 Diameter x Length	编号 Suffix	插杆直径x长度 Diameter x Length
3"	11 x 22mm (CN) 7/16" diameter x 7/8"	3"	11 x 50mm (CN) 7/16" diameter x 1-31/32"
4"~6"	21.6 x 56mm (CN) 0.845" diameter x 2-3/16" (For 3"~5" Casters)	4"~6"	22.8 x 45mm (CN) 0.897" diameter x 1-3/4"
4"~6"	27.2 x 45mm (CN) 1-5/64" diameter x 1-3/4"	4"~6"	28 x 30mm (CN) 1-7/64" diameter x 1-3/16"

» 丝扣规格 THREADED STEM SPECIFICATION

编号 Suffix	丝扣牙径 x 长度 Threaded Size	编号 Suffix	丝扣牙径 x 长度 Threaded Size
3"	3/8-16UNC x 25mm (CN)	3"	M10 x 15mm (CN)
3"	M10 x 25mm (CN)	3"	M12 x 25mm (CN)
4"~6"	3/8-16UNC x 25mm (CN)	4"~6"	M10 x 35mm (CN)
4"~6"	M12 x 29mm (CN)	4"~6"	1/2-12UNC x 27.5mm (CN)
4"~6"	1/2-13UNC x 25mm (CN)	4"~6"	M16 x 30mm (CN)

» 空铆规格 SINGLE BOLT HOLE

编号 Suffix	孔径 Centre Hole	编号 Suffix	孔径 Centre Hole
3"	10.2mm (CN)	4"~6"	10.5mm (CN)
4"~6"	12.5mm (CN)		



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius	
			固定 Fixed	活动 Swivel	刹车 Brake				
75mmx27mm (3"x1")	70 kgs (155 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-03-31-1	1129-03-31-2	1129-03-31-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 106mm (4-1/8") 丝扣类总高 Threaded Stem OAH: 110mm (4-21/64") 空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 104mm (4-3/32")	活动 67mm 双刹 91mm Swivel 67mm Swivel W/Total lock 91mm	
	70 kgs (155 lbs)	超级人造胶 TPR on PP Core	1129-03-75-1	1129-03-75-2	1129-03-75-4	中管 Plain Bearing			
	56 kgs (125 lbs)	全效轮 Resolute	1129-03-68-1	1129-03-68-2	1129-03-68-4	滚珠 Ball Bearing			
	60 kgs (132 lbs)	NPPR轮 NPPR	1129-03-67-1	1129-03-67-2	1129-03-67-4				
	80 kgs (175 lbs)	导电轮 E-Conductive	1129-03-17-1	1129-03-17-2	1129-03-17-4	中管 Plain Bearing			
	70 kgs (155 lbs)	尼龙轮 Nylon	1129-03-07-1	1129-03-07-2	1129-03-07-4				
	50 kgs (110 lbs)	橡胶轮 Rubber	1129-03-06-1	1129-03-06-2	1129-03-06-4				
	60 kgs (132 lbs)	塑料轮 PP	1129-03-29-1	1129-03-29-2	1129-03-29-4				
100mm x 24mm (4" x 1")	50 kgs (110 lbs)	超级人造胶 TPR on PP Core	1129-R-04-75-1	1129-R-04-75-2	1129-R-04-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 136mm (5-3/8") 丝扣类总高 Threaded Stem OAH: 136mm (5-3/8") 空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 132mm (5-13/64")	活动 91mm 双刹 98mm 侧刹 95mm Swivel 91mm Swivel W/Total lock 98mm Swivel W/Side Brake 95mm	
	55 kgs (121 lbs)	全效轮 Resolute	1129-R-04-68-1	1129-R-04-68-2	1129-R-04-68-4	滚珠 Ball Bearing 中管 Plain Bearing			
100mmx32mm (4"x1-1/4")	120kgs (265 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-04-31-1	1129-04-31-2	1129-04-31-4				滚珠 Ball Bearing 中管 Plain Bearing
	100kgs (220 lbs)	超级人造胶 TPR on PP Core	1129-04-75-1	1129-04-75-2	1129-04-75-4				
	80kgs (175lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1129-04-110-1	1129-04-110-2	1129-04-110-4				
	90kgs (198lbs)	全效轮(大圆弧) Resolute (Donut)	1129-04-111-1	1129-04-111-2	1129-04-111-4	滚珠 Ball Bearing			
	125kgs (275 lbs)	全效轮 Resolute	1129-04-68-1	1129-04-68-2	1129-04-68-4				
	80 kgs (176 lbs)	导电轮 E-Conductive	1129-04-17-1	1129-04-17-2	1129-04-17-4				
	135kgs (300 lbs)	W全效轮 W Resolute	1129-04-48-1	1129-04-48-2	1129-04-48-4				
	180kgs (400 lbs)	WHDR轮 WHDR	1129-04-66-1	1129-04-66-2	1129-04-66-4				
	100kgs (220 lbs)	W超级人造胶 WPPR	1129-04-47-1	1129-04-47-2	1129-04-47-4				
	180kgs (396 lbs)	WMRC轮 WMRC	1129-04-45-1	1129-04-45-2	1129-04-45-4				
	130kgs (285 lbs)	WPP轮 WPP	1129-04-46-1	1129-04-46-2	1129-04-46-4				
	135 kgs (300 lbs)	铝芯橡胶轮 Rubber on Aluminum Core	1129-04-22-1	1129-04-22-2	1129-04-22-4				
	200kgs (440 lbs)	铝芯AQP QPU on AL Core	1129-04-87-1	1129-04-87-2	1129-04-87-4				
	70kgs (154 lbs)	NPPR轮 NPPR	1129-04-67-1	1129-04-67-2	1129-04-67-4				中管 Plain Bearing
	120 kgs (265 lbs)	尼龙轮 Nylon	1129-04-07-1	1129-04-07-2	1129-04-07-4				
	135 kgs (300 lbs)	耐高温轮 Hi-temp	1129-04-25-1	1129-04-25-2	1129-04-25-4				
	80 kgs (175 lbs)	橡胶轮 Rubber	1129-04-06-1	1129-04-06-2	1129-04-06-4				
	90 kgs (198 lbs)	塑料轮 PP	1129-04-29-1	1129-04-29-2	1129-04-29-4				





 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
100mmx36mm (4"x1-1/2")	160 kgs (352 lbs)	CPD轮 CPD	1129-04-71-1	1129-04-71-2	1129-04-71-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 136mm (5-3/8")	活动 91mm 双刹 98mm 侧刹 95mm
	160 kgs (352 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1129-04-50-1	1129-04-50-2	1129-04-50-4		丝扣类总高 Threaded Stem OAH: 136mm (5-3/8")	Swivel 91mm Swivel W/Total lock 98mm Swivel W/Side Brake 95mm
	140kgs (308 lbs)	超级人造胶 TPR on PP Core	1129-04-77-1	1129-04-77-2	1129-04-77-4		空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 132mm (5-13/64")	
	160kgs (352 lbs)	全效轮 Resolute	1129-04-76-1	1129-04-76-2	1129-04-76-4			
	200kgs (440 lbs)	铝芯AQPU QPU on AL Core	1129-04-87-1	1129-04-87-2	1129-04-87-4			
125mm x 24.5mm (5" x 1")	70 kgs (155 lbs)	超级人造胶 TPR on PP Core	1129-R-05-75-1	1129-R-05-75-2	1129-R-05-75-4	滚珠 Ball Bearing		
	80 kgs (175 lbs)	全效轮 Resolute	1129-R-05-68-1	1129-R-05-68-2	1129-R-05-68-4			
125mmx32mm (5"x1-1/4")	130kgs (285 lbs)	高科技耐磨聚氨酯 PU on PP Core	1129-05-31-1	1129-05-31-2	1129-05-31-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 162mm (6-3/8") 丝扣类总高 Threaded Stem OAH: 162mm (6-3/8") 空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 156mm (6-9/64")	活动 101mm 双刹 101mm 侧刹 101mm Swivel 101mm Swivel W/Total lock 101mm Swivel W/Side Brake 101mm
	110kgs (240 lbs)	超级人造胶 TPR on PP Core	1129-05-75-1	1129-05-75-2	1129-05-75-4			
	100kgs (220lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1129-05-110-1	1129-05-110-2	1129-05-110-4			
	120kgs (265lbs)	全效轮(大圆弧) Resolute (Donut)	1129-05-111-1	1129-05-111-2	1129-05-111-4			
	147 kgs (325 lbs)	全效轮 Resolute	1129-05-68-1	1129-05-68-2	1129-05-68-4	滚珠 Ball Bearing		
	90 kgs (198 lbs)	导电轮 E-Conductive	1129-05-17-1	1129-05-17-2	1129-05-17-4			
	147 kgs (325 lbs)	W全效轮 W Resolute	1129-05-48-1	1129-05-48-2	1129-05-48-4			
	180 kgs (400 lbs)	WHDR轮 WHDR	1129-05-66-1	1129-05-66-2	1129-05-66-4			
	110kgs (240 lbs)	W超级人造胶 WPPR	1129-05-47-1	1129-05-47-2	1129-05-47-4			
	200 kgs (440 lbs)	WMRC轮 WMRC	1129-05-45-1	1129-05-45-2	1129-05-45-4			
	150 kgs (330 lbs)	WPP轮 WPP	1129-05-46-1	1129-05-46-2	1129-05-46-4			
	200kgs (440 lbs)	铝芯AQPU QPU on AL Core	1129-05-87-1	1129-05-87-2	1129-05-87-4			
	140 kgs (305 lbs)	尼龙轮 Nylon	1129-05-07-1	1129-05-07-2	1129-05-07-4	中管 Plain Bearing		
	90 kgs (198 lbs)	橡胶轮 Rubber	1129-05-06-1	1129-05-06-2	1129-05-06-4			
	100 kgs (220 lbs)	塑料轮 PP	1129-05-29-1	1129-05-29-2	1129-05-29-4			
125mmx36mm (5"x1-1/2")	200 kgs (440 lbs)	CPD轮 CPD	1129-05-71-1	1129-05-71-2	1129-05-71-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 162mm (6-3/8")	活动 101mm 双刹 101mm 侧刹 101mm
	250 kgs (550 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1129-05-50-1	1129-05-50-2	1129-05-50-4		丝扣类总高 Threaded Stem OAH: 162mm (6-3/8")	Swivel 101mm Swivel W/Total lock 101mm Swivel W/Side Brake 101mm
	160kgs (352 lbs)	超级人造胶 TPR on PP Core	1129-05-77-1	1129-05-77-2	1129-05-77-4		空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 156mm (6-9/64")	
	180kgs (400 lbs)	全效轮 Resolute	1129-05-76-1	1129-05-76-2	1129-05-76-4			





 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
150mmx32mm (6"x1-1/4")	110 kgs (240 lbs)	超级人造胶 TPR on PP Core	1129-06-75-1	1129-06-75-2	1129-06-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 186mm (7-3/8")	活动 113mm 双刹 113mm 侧刹 113mm
	147 kgs (325 lbs)	全效轮 Resolute	1129-06-68-1	1129-06-68-2	1129-06-68-4		丝扣类总高 Threaded Stem OAH: 186mm (7-3/8")	Swivel 113mm Swivel W/Total lock 113mm Swivel W/Side Brake 113mm
	147 kgs (325 lbs)	W全效轮 W Resolute	1129-06-48-1	1129-06-48-2	1129-06-48-4		空心/插杆类总高 Single Bolt Hole/ Cylindrical Stem OAH: 181mm (7-1/8")	
	200 kgs (440 lbs)	WHDR轮 WHDR	1129-06-66-1	1129-06-66-2	1129-06-66-4			
	110 kgs (240 lbs)	W超级人造胶 WPPR	1129-06-47-1	1129-06-47-2	1129-06-47-4			

