

精密系列脚轮

- 使用精密滚珠轴承，晃动间隙小且转动顺畅
- 外型美观，双防尘设计
- 5"精密脚轮可附加心型装饰盖，外型更加柔美和美观
- 配合我司全效轮、PPR等系列，行走噪音小，适合静音环境使用



底板斜孔

品名规格	轮径	轮宽	总高	偏心距	底 板	底板孔距	荷 重
精密活动架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	96x69mm	75x45mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	96x69mm	75x45mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	96x69mm	75x45mm	120kgs / 264lbs
精密活利架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	96x69mm	75x45mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	96x69mm	75x45mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	96x69mm	75x45mm	120kgs / 264lbs
精密90度定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	96x69mm	75x45mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	96x69mm	75x45mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	96x69mm	75x45mm	120kgs / 264lbs
精密180度定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	96x69mm	75x45mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	96x69mm	75x45mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	96x69mm	75x45mm	120kgs / 264lbs
精密360度定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	96x69mm	75x45mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	96x69mm	75x45mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	96x69mm	75x45mm	120kgs / 264lbs

插心

品名规格	轮径	轮宽	总高	偏心距	插 桿	荷 重
精密活动架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 28x30	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 28x30	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 28x30	120kgs / 264lbs
精密活利架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 28x30	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 28x30	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 28x30	120kgs / 264lbs
精密180度定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 28x30	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 28x30	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 28x30	120kgs / 264lbs

(本荷重为安装全效轮之荷重，若装其他轮子荷重将会不同)



螺
丝

品名规格	轮径	轮宽	总高	偏心距	螺 丝	荷 重
精密活动架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	1/2"x29mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	1/2"x29mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	1/2"x29mm	120kgs / 264lbs
精密活刹架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	1/2"x29mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	1/2"x29mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	1/2"x29mm	120kgs / 264lbs
精密180度 定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	1/2"x29mm	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	1/2"x29mm	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	1/2"x29mm	120kgs / 264lbs

空
心
铆
钉

品名规格	轮径	轮宽	总高	偏心距	空心铆钉	荷 重
精密活动架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 12.5	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 12.5	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 12.5	120kgs / 264lbs
精密活刹架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 12.5	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 12.5	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 12.5	120kgs / 264lbs
精密180度 定向架	4"(100mm)	1-1/4"(32mm)	140.5mm	43.4mm	Ø 12.5	100kgs / 220lbs
	5"(125mm)	1-1/4"(32mm)	164.5mm	38.6mm	Ø 12.5	110kgs / 242lbs
	6"(150mm)	1-1/4"(32mm)	192.0mm	39.0mm	Ø 12.5	120kgs / 264lbs

〈 本荷重为安装全效轮之荷重，若装其他轮子荷重将会不同 〉