



1139 Series 中型

39系列(大陆)美规脚架系列


Medium Duty General Purposes Caster (American Style)

- 脚架采特别结构设计，荷重高、转动灵活，有侧煞制动及双煞制动可供选择。
- Pressed steel caster horn/ housing design to swivel easily under load.
Good performance side brake and total lock brake for options.

载重 Load
70 - 250 kg



特色区 Features



铁双刹
Total Lock Brake
with steel Pedals



侧煞
Side Lock Brake



波盘防尘盖
Swivel Dust Cover



滚珠轴承
Ball Bearing

滚珠轴承
Ball Bearing

中管
Plain Bearing

轮子选项 Wheel Options



底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

编号 Suffix	底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
1	62 x 92 mm (2-3/8" x 3-5/8")	45x75 mm (高级架底板) 1 -3/4"x3"	6.35 mm (1/4")



» 插杆规格 CYLINDRICAL STEM SPECIFICATION

編號 Suffix	插杆直径x长度 Diameter x Length	孔位高度 Hole Height	孔尺寸 Bore Size
1	方21.4X63mm(square)	43mm	5/16"-18UNC
2	21.6X56mm	—	C型环 (Grip Ring)
3	22.1X56mm	—	C型环 (Grip Ring)

» 丝扣规格 THREADED STEM SPECIFICATION

编号 Suffix	丝扣牙径 x 长度 Threaded Size	编号 Suffix	丝扣牙径 x 长度 Threaded Size	编号 Suffix	丝扣牙径 x 长度 Threaded Size
1	3/8-16UNCx25 **	2	M12x25 *	3	M12x25 **
4	1/2-13UNCx25 **	5	M16x25 *		

* 丝扣底部六角台阶 (Hexagon Head)

** 丝扣底部圆头台阶 (Round Head)

 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
75mm x 24mm (3" x 1")	40 kgs (88 lbs)	超级人造胶 TPR on PP Core	1139-R-03-75-1	1139-R-03-75-2	1139-R-03-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 105mm (4-1/8") 圆头丝扣类总高 Round Head Threaded Stem OAH: 101mm (3-31/32") 六角丝扣类总高 Hexagon Head Threaded Stem OAH: 105mm (4-1/8") 插杆类总高 Cylindrical Stem OAH: 101mm (3-31/32")	活动 76mm 侧刹 82mm 双刹 114mm Swivel 76mm Swivel W/Side Brake 82mm Swivel W/Total lock 114mm
	50 kgs (110 lbs)	全效轮 Resolute	1139-R-03-68-1	1139-R-03-68-2	1139-R-03-68-4			
75mmx32mm (3"x1-1/4")	90kgs (198lbs)	超级人造胶 TPR on PP Core	1139-03-75-1	1139-03-75-2	1139-03-75-4	滚珠 Ball Bearing		
	90kgs (198lbs)	全效轮 Resolute	1139-03-68-1	1139-03-68-2	1139-03-68-4			
	80kgs (175lbs)	导电轮 E-Conductive	1139-03-17-1	1139-03-17-2	1139-03-17-4			
	160kgs (352lbs)	WMRC轮 WMRC	1139-03-45-1	1139-03-45-2	1139-03-45-4			
	100kgs (220lbs)	WPP轮 WPP	1139-03-46-1	1139-03-46-2	1139-03-46-4			
	90kgs (198lbs)	W超级人造胶 WPPR	1139-03-47-1	1139-03-47-2	1139-03-47-4			
	110kgs (250lbs)	W全效轮 W Resolute	1139-03-48-1	1139-03-48-2	1139-03-48-4			
	140kgs (310lbs)	WHDR轮 WHDR	1139-03-66-1	1139-03-66-2	1139-03-66-4			
	160kgs (352lbs)	铝芯AQPU QPU on AL Core	1139-03-87-1	1139-03-87-2	1139-03-87-4			
	100kgs (220lbs)	尼龙轮 Nylon	1139-03-07-1	1139-03-07-2	1139-03-07-4	中管 Plain Bearing		
	70kgs (155lbs)	橡胶轮 Rubber	1139-03-06-1	1139-03-06-2	1139-03-06-4			
	90kgs (198lbs)	塑料轮 PP	1139-03-29-1	1139-03-29-2	1139-03-29-4			



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
100mm x 24mm (4" x 1")	50kgs (110lbs)	超级人造胶 TPR on PP Core	1139-R-04-75-1	1139-R-04-75-2	1139-R-04-75-4	滚珠 Ball Bearing		
	55kgs (121lbs)	全效轮 Resolute	1139-R-04-68-1	1139-R-04-68-2	1139-R-04-68-4			
100mmx32mm (4"x1-1/4")	120kgs (265lbs)	高科技耐磨聚氨酯 PU on PP Core	1139-04-31-1	1139-04-31-2	1139-04-31-4	滚珠 Ball Bearing 中管 Plain Bearing	底板类总高 Plate Version OAH: 130mm (5-1/8")	活动 88mm 侧刹 88mm 双刹 114mm Swivel 88mm Swivel W/Side Brake 88mm Swivel W/Total lock 114mm
	100kgs (220lbs)	超级人造胶 TPR on PP Core	1139-04-75-1	1139-04-75-2	1139-04-75-4			
	80kgs (175lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1139-04-110-1	1139-04-110-2	1139-04-110-4			
	90kgs (198lbs)	全效轮(大圆弧) Resolute (Donut)	1139-04-111-1	1139-04-111-2	1139-04-111-4			
	125kgs (275lbs)	全效轮 Resolute	1139-04-68-1	1139-04-68-2	1139-04-68-4	滚珠 Ball Bearing	圆头丝扣类总高 Round Head Threaded Stem OAH: 126mm (4-61/64") 六角丝扣类总高 Hexagon Head Threaded Stem OAH: 130mm (5-1/8") 插杆类总高 Cylindrical Stem OAH: 126mm (4-61/64")	
	80kgs (176lbs)	导电轮 E-Conductive	1139-04-17-1	1139-04-17-2	1139-04-17-4			
	180kgs (396 lbs)	WMRC轮 WMRC	1139-04-45-1	1139-04-45-2	1139-04-45-4			
	130kgs (285lbs)	WPP轮 WPP	1139-04-46-1	1139-04-46-2	1139-04-46-4			
	100kgs (220lbs)	W超级人造胶 WPPR	1139-04-47-1	1139-04-47-2	1139-04-47-4			
	135kgs (300lbs)	W全效轮 W Resolute	1139-04-48-1	1139-04-48-2	1139-04-48-4			
	180kgs (400lbs)	WHDR轮 WHDR	1139-04-66-1	1139-04-66-2	1139-04-66-4			
	135kgs (300lbs)	铝芯橡胶轮 Rubber on Aluminum Core	1139-04-22-1	1139-04-22-2	1139-04-22-4			
	200kgs (440lbs)	铝芯AQPU QPU on AL Core	1139-04-87-1	1139-04-87-2	1139-04-87-4			
100mmx32mm (4"x1-1/4")	70kgs (154lbs)	NPPR轮 NPPR	1139-04-67-1	1139-04-67-2	1139-04-67-4	中管 Plain Bearing	底板类总高 Plate Version OAH: 130mm (5-1/8") 圆头丝扣类总高 Round Head Threaded Stem OAH: 126mm (4-61/64")	
	120kgs (265lbs)	尼龙轮 Nylon	1139-04-07-1	1139-04-07-2	1139-04-07-4			
	80kgs (176lbs)	橡胶轮 Rubber	1139-04-06-1	1139-04-06-2	1139-04-06-4			
	90kgs (198lbs)	塑料轮 PP	1139-04-29-1	1139-04-29-2	1139-04-29-4			
	135kgs (300lbs)	耐高温轮 Hi-temp	1139-04-25-1	1139-04-25-2	1139-04-25-4			
100mmx36mm (4"x1-1/2")	160kgs (352 lbs)	CPD轮 CPD	1139-04-71-1	1139-04-71-2	1139-04-71-4	滚珠 Ball Bearing	六角丝扣类总高 Hexagon Head Threaded Stem OAH: 130mm (5-1/8") 插杆类总高 Cylindrical Stem OAH: 126mm (4-61/64")	
	160kgs (352 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1139-04-50-1	1139-04-50-2	1139-04-50-4			
	140kgs (308 lbs)	超级人造胶 TPR on PP Core	1139-04-77-1	1139-04-77-2	1139-04-77-4			
	160kgs (352 lbs)	全效轮 Resolute	1139-04-76-1	1139-04-76-2	1139-04-76-4			
	250kgs (550lbs)	铝芯AQPU QPU on AL Core	1139-04-87-1	1139-04-87-2	1139-04-87-4			



 轮径x轮宽 DiameterxWidth	 载重 Load	 材质 Material	 型号 Item No.			 轴承 Bearing	 总高 Overall Height	 回旋半径 Swivel radius
			固定 Fixed	活动 Swivel	刹车 Brake			
125mm x 24.5mm (5" x 1")	70kgs (155lbs)	超级人造胶 TPR on PP Core	1139-R-05-75-1	1139-R-05-75-2	1139-R-05-75-4	滚珠 Ball Bearing	底板类总高 Plate Version OAH: 158mm (6-1/5") 圆头丝扣类总高 Round Head Threaded Stem OAH: 154mm (6-1/16") 六角丝扣类总高 Hexagon Head Threaded Stem OAH: 158mm (6-1/5") 插杆类总高 Cylindrical Stem OAH: 154mm (6-1/16")	活动 101mm 侧刹 101mm 双刹 114mm Swivel 101mm Swivel W/Side Brake 101mm Swivel W/Total lock 114mm
	80kgs (175lbs)	全效轮 Resolute	1139-R-05-68-1	1139-R-05-68-2	1139-R-05-68-4			
125mmx32mm (5"x1-1/4")	130kgs (285lbs)	高科技耐磨聚氨酯 PU on PP Core	1139-05-31-1	1139-05-31-2	1139-05-31-4	滚珠 Ball Bearing 中管 Plain Bearing		
	110kgs (240lbs)	超级人造胶 TPR on PP Core	1139-05-75-1	1139-05-75-2	1139-05-75-4			
	100kgs (220lbs)	超级人造胶(大圆弧) TPR on PP Core (Donut)	1139-05-110-1	1139-05-110-2	1139-05-110-4			
	120kgs (265lbs)	全效轮(大圆弧) Resolute (Donut)	1139-05-111-1	1139-05-111-2	1139-05-111-4	滚珠 Ball Bearing		
	147kgs (325lbs)	全效轮 Resolute	1139-05-68-1	1139-05-68-2	1139-05-68-4			
	90kgs (198lbs)	导电轮 E-Conductive	1139-05-17-1	1139-05-17-2	1139-05-17-4			
	200kgs (440lbs)	WMRC轮 WMRC	1139-05-45-1	1139-05-45-2	1139-05-45-4			
	150kgs (330lbs)	WPP轮 WPP	1139-05-46-1	1139-05-46-2	1139-05-46-4			
	110kgs (240lbs)	W超级人造胶 WPPR	1139-05-47-1	1139-05-47-2	1139-05-47-4			
	147kgs (325lbs)	W全效轮 W Resolute	1139-05-48-1	1139-05-48-2	1139-05-48-4			
	200kgs (440lbs)	WHDR轮 WHDR	1139-05-66-1	1139-05-66-2	1139-05-66-4	中管 Plain Bearing		
	230kgs (506lbs)	铝芯AQPU QPU on AL Core	1139-05-87-1	1139-05-87-2	1139-05-87-4			
	140kgs (305lbs)	尼龙轮 Nylon	1139-05-07-1	1139-05-07-2	1139-05-07-4			
	90kgs (198lbs)	橡胶轮 Rubber	1139-05-06-1	1139-05-06-2	1139-05-06-4			
	100kgs (220lbs)	塑料轮 PP	1139-05-29-1	1139-05-29-2	1139-05-29-4			
125mmx36mm (5"x1-1/2")	200kgs (440 lbs)	CPD轮 CPD	1139-05-71-1	1139-05-71-2	1139-05-71-4	滚珠 Ball Bearing		
	250kgs (550 lbs)	蓝色弹力轮 Blue Resilient Rubber Wheel	1139-05-50-1	1139-05-50-2	1139-05-50-4			
	160kgs (352lbs)	超级人造胶 TPR on PP Core	1139-05-77-1	1139-05-77-2	1139-05-77-4			
	180kgs (400lbs)	全效轮 Resolute	1139-05-76-1	1139-05-76-2	1139-05-76-4			