


APU系列 重型輪 PU外包+铝芯

	轮面硬度		92° shore A
	温度范围		-30°C to +70°C
	滚动顺畅		优秀
	音量		良好
	保护地板		良好



轮面

由高品质聚氨酯制成。得胜硬度92°的PU轮不仅能提供良好的地板保护作用，而且低噪音。得胜PU轮有着优秀的抗水解特性，适用热带地区及潮湿的工作环境。

轮框

内框：铝芯

特色

- 抗化学、溶剂及侵蚀
- 耐磨
- 抗微生物
- 适用环境温度：-30°C ~ +70°C
- 在正常使用情况下，无需维修



品号	轮径 (D) [mm]	轮宽 (T2) [mm]	载重 [kg (lbs)]	轴承内径 Ø(d) [mm]	中宽 (T1) [mm]	轮面	轴承
12035903130100	75	29	150 kgs (330lbs)	17	29	圆弧	精密滚珠 轴承
12035903135300	75	30	150 kgs (330lbs)	12	32		
12035903135171	80	30	180 kgs (396lbs)	12	32		
12035903135271	80	30	180 kgs (396lbs)	15	32		
12035904135171	100	31	230 kgs (507lbs)	15	32		
12035904135271	100	31	230 kgs (507lbs)	17	32		
12035904155171	100	36	325 kgs (716lbs)	12	36		
12035904155271	100	36	325 kgs (716lbs)	15	36		
12035904155371	100	40	350 kgs (771lbs)	12	40		
12035904155471	100	40	350 kgs (771lbs)	15	40		
12035905135171	125	31	280 kgs (617lbs)	15	32		
12035905135271	125	31	280 kgs (617lbs)	17	32		
12035905135371	125	40	350 kgs (771lbs)	15	40		
12035905135471	125	40	350 kgs (771lbs)	17	40		
12037005180100	125	40	350 kgs (771lbs)	20	49		
12035906185171	150	42	450 kgs (992lbs)	17	42		
12035906185271	150	42	450 kgs (992lbs)	20	42		
12035956185171	160	42	500 kgs (1102lbs)	17	42		
12035956185271	160	42	500 kgs (1102lbs)	20	42		
12035907185171	180	44	600 kgs (1323lbs)	20	44		
12035907185271	180	44	600 kgs (1323lbs)	25	44		
12035908205171	200	50	800 kgs (1764lbs)	20	50	平面	精密滚珠 轴承
12035908205271	200	50	800 kgs (1764lbs)	25	50		
12035902105100	50	25	100 kgs (220lbs)	17	25		
12035904205171	100	50	300 kgs (661lbs)	17	50		
12035904205271	100	50	300 kgs (661lbs)	20	50		
12035905205171	125	50	450 kgs (992lbs)	17	50		
12035905205271	125	50	450 kgs (992lbs)	20	50		
12035906205171	150	50	500 kgs (1102lbs)	17	50		
12035906205271	150	50	500 kgs (1102lbs)	20	50		
12035956205171	160	50	550 kgs (1213lbs)	17	50		
12035956205271	160	50	550 kgs (1213lbs)	20	50		
12035908185100	200	44	700 kgs (1543lbs)	20	44		
12035908205371	200	50	800 kgs (1764lbs)	20	50		
12035908205471	200	50	800 kgs (1764lbs)	25	50		

