

蓝色弹力全效轮

*颜色可依客人喜好客製

	轮面硬度		68°±5° Shore A
	温度范围		-20°C to +60°C
	滚动顺畅		非常优秀
	音量		非常优秀
	保护地板		非常优秀



轮面

为热塑性橡胶弹性体(TPR),便于保护地面,无痕,操作舒适,承受大载重,滚动阻力和旋转阻力小,耐许多侵蚀性物质的腐蚀。颜色:灰色。
硬度为 68°±5° Shore A。
与轮体的化学黏合不可分解。

轮体

採用优质耐冲击聚丙烯。

特色

- 大载重,保护地面,正常使用免维护。
- 适用温度范围:-20° C至 +60° C。



品号	轮径 (D)[mm]	轮宽 (T2)[mm]	载重 [kg(lbs)]	轴承内径 Ø(d)[mm]	中宽 (T1)[mm]	轴承
12024523133200	80	32	120kgs (264lbs)	12	43.6	中管
12024523133174	80	32	120kgs (264lbs)	8	41	滚珠轴承
12024523133173	80	32	120kgs (264lbs)	10	41	滚珠轴承
12024523133172	80	32	120kgs (264lbs)	8	46	滚珠轴承
12024523133171	80	32	120kgs (264lbs)	10	46	滚珠轴承
12024504153174	100	34	150kgs (330lbs)	8	41	滚珠轴承
12024504153173	100	34	150kgs (330lbs)	10	41	滚珠轴承
12024504153172	100	34	150kgs (330lbs)	8	46	滚珠轴承
12024504153171	100	34	150kgs (330lbs)	10	46	滚珠轴承
12024504153176	100	34	150kgs (330lbs)	8	50	滚珠轴承
12024504153175	100	34	150kgs (330lbs)	10	50	滚珠轴承
12024505153174	125	36	180kgs (396lbs)	8	41	滚珠轴承
12024505153173	125	36	180kgs (396lbs)	10	41	滚珠轴承
12024505153172	125	36	180kgs (396lbs)	8	46	滚珠轴承
12024505153171	125	36	180kgs (396lbs)	10	46	滚珠轴承
12054505153176	125	36	180kgs (396lbs)	8	50	滚珠轴承
12024505153175	125	36	180kgs (396lbs)	10	50	滚珠轴承
12024536191171	160	48	300kgs (661lbs)	20	60	滚针轴承
12024536193171	160	48	300kgs (661lbs)	20	58	滚珠轴承
12024508191171	200	48	325kgs (716lbs)	20	60	滚针轴承
12024508193171	200	48	325kgs (716lbs)	20	58	滚珠轴承

