


PU系列

物料搬运/手推车用聚氨酯轮(美式)

	轮面硬度		94°±3°Shore A
	温度范围		-30°C to +70°C
	滚动顺畅		优秀
	音量		良好
	保护地板		非常优秀



轮面

优质热塑性橡胶聚氨酯 (TPU) , 便于保护地板, 吸收震动, 无痕, 不染色, 具有弹性, 非常耐磨擦, 滚动阻力小, 耐许多侵蚀性物质的腐蚀。颜色灰色。硬度为 94°±3° Shore A。在高于+35° C的环境温度下承载能力下降。

特色

- 耐磨, 运转低阻力, 正常使用免维护。
- 适用温度范围: -30° C至 +70° C。

轮体

採用优质耐冲击聚丙烯。



中輕型

 品号	 轮径 (D)【mm】	 轮宽 (T2)【mm】	 载重 【kg(lbs)】	 轴承内径 Ø(d)【mm】	 中宽 (T1)【mm】	 轮面	 轴承
12033103133300	3"(75mm)	1-1/4"(31mm)	90kgs / 200lbs	10	41	圆弧	中管
12033104133973	4"(100mm)	1-1/4"(31mm)	120kgs / 265lbs	8	41	圆弧	滚珠轴承
12033105133274	5"(125mm)	1-1/4"(31mm)	120kgs / 265lbs	8	41	圆弧	滚珠轴承
12033106133973	6"(150mm)	1-1/4"(31mm)	130kgs / 285lbs	8	41	圆弧	滚珠轴承