

三星橡胶轮系列

弹力橡胶外包+铁芯/铸铁芯

	轮面硬度		80°± 5° shore A
	温度范围		-20°C to +120°C
	滚动顺畅		优秀
	音量		非常优秀
	保护地板		非常优秀



轮面

由高品质的弹力橡胶制成，得胜铁芯橡胶轮轮面硬度是 $85^{\circ} \pm 5^{\circ}$ ，具有极佳的操作舒适性，优秀的地板保护作用及避震功能。颜色：黑色。

轮框

内框：铁芯/铸铁芯

特色

- 抗化学、溶剂及侵蚀
- 适用环境温度：-25°C ~ +80°C
- 在正常使用情况下，无需维修



品号	轮径 (D) [mm]	轮宽 (T2) [mm]	载重 [kg (lbs)]	轴承内径 Ø(d) [mm]	中宽 (T1) [mm]	轮面	轴承
12040303136171	72	35	90kgs (198lbs)	12	35	弧形	精密滚珠 轴承
12040304151171	100	35	150kgs (330lbs)	15	35		
12040304152171	100	35	150kgs (330lbs)	17	35		
12040305152471	125	35	150kgs (330lbs)	15	35		
12040305152571	125	35	150kgs (330lbs)	17	35		
12040305151371	125	40	200kgs (440lbs)	15	40		
12040305152171	125	40	200kgs (440lbs)	17	40		
12040306186571	144	44	210kgs (463lbs)	17	44.5		
12040306181171	150	45.5	230kgs (507lbs)	17	44.5		
12040306306171	150	57	250kgs (551lbs)	17	57		
12040308181171	193	46	260kgs (573lbs)	17	46		
12040308182171	193	46	260kgs (573lbs)	20	46		

