



1102-P Series

B Type Pneumatic Caster

- Swivel easily under heavy load;
ideal for heavy-duty workshop trucks
in automobile, glass, textile industries, etc.



» Features



Center Lock Brake

» Wheel Options



Pneumatic with
painted steel rim



Pneumatic with
plastic rim



Pneumatic with
plated steel rim



Solid Rubber wheel
with painted steel rim



Flat Free Tire



W Resolute Rubber



Resolute Rubber



NBR Rubber on Cast



Solid Rubber wheel
with painted steel rim




















Ball Bearing

» TOP PLATE SIZE AND BOLT HOLE SPACING

Caster Size	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
8" caster	110 x 140mm (4-1/3" x 5-1/2")	75~80 x 110mm (3-1/8" x 4-5/16")	12.7mm (1/2")
10" caster, 12" caster	130 x 172mm (5-1/8" x 6-3/4")	100 x 140mm (3-15/16" x 5-1/2")	12.7mm (1/2")



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius	輪子樣式
			Fixed	Swivel	Brake				
200mm x 53mm (8" x 2-1/8")	120 kgs (265 lbs)	Solid Rubber	1102-P-08-02-1	1102-P-08-02-2	1102-P-08-02-4	Ball Bearing	248mm (9-3/4")	Swivel 160.5mm Swivel W/Brake 160.5mm	
202mm x 51mm (8" x 2")	180 kgs (400 lbs)	Resolute Rubber	1102-P-08-53-1	1102-P-08-53-2	1102-P-08-53-4	Ball Bearing	249mm (9-13/16")	Swivel 161.5mm Swivel W/Brake 161.5mm	
208mm x 55mm (8-3/16" x 2-9/16")	100 kgs (220 lbs)	Flat Free Tire	1102-P-08-05-1	1102-P-08-05-2	1102-P-08-05-4	Ball Bearing	252mm (9-15/16")	Swivel 164.5mm Swivel W/Brake 164.5mm	
216mm x 65mm (8-1/2" x 2-9/16")	150 kgs (330 lbs)	Pneumatic	1102-P-08-01-1	1102-P-08-01-2	1102-P-08-01-4	Ball Bearing	256mm (10-1/16")	Swivel 168.5mm Swivel W/Brake 168.5mm	
246mm x 74mm (10" x 2-15/16")	230 kgs (505 lbs)	W Resolute Rubber	1102-P-10-95-1	1102-P-10-95-2	1102-P-10-95-4	Ball Bearing	314mm (12-3/8")	Swivel 195.5mm Swivel W/Brake 195.5mm	
250mm x 74mm (10" x 2-15/16")	180 kgs (395 lbs)	Solid Rubber	1102-P-10-02-1	1102-P-10-02-2	1102-P-10-02-4	Ball Bearing	316mm (12-7/16")	Swivel 197.5mm Swivel W/Brake 197.5mm	
252mm x 71mm (10" x 2-13/16")	300 kgs (660 lbs)	NBR Rubber on Cast	1102-P-10-04-1	1102-P-10-04-2	1102-P-10-04-4	Ball Bearing	317mm (12-1/2")	Swivel 198.5mm Swivel W/Brake 198.5mm	
260mm x 85mm (10-1/4" x 3-3/8")	150 kgs (330 lbs)	Flat Free Tire	1102-P-10-05-1	1102-P-10-05-2	1102-P-10-05-4	Ball Bearing	321mm (12-5/8")	Swivel 202.5mm Swivel W/Brake 202.5mm	
270mm x 86mm (10-5/8" x 3-3/8")	200 kgs (440 lbs)	Pneumatic	1102-P-10-01-1	1102-P-10-01-2	1102-P-10-01-4	Ball Bearing	326mm (12-7/8")	Swivel 207.5mm Swivel W/Brake 207.5mm	
307mm x 85mm (12-1/8" x 3-3/8")	250 kgs (550 lbs)	Pneumatic	1102-P-12-01-1	1102-P-12-01-2	1102-P-12-01-4	Ball Bearing	363.5mm (14-5/6")	Swivel 224.5mm Swivel W/Brake 224.5mm	
308mm x 76mm (12-1/8" x 3")	350 kgs (770 lbs)	NBR Rubber on Cast	1102-P-12-04-1	1102-P-12-04-2	1102-P-12-04-4	Ball Bearing	363.5mm (14-5/6")	Swivel 224.5mm Swivel W/Brake 224.5mm	