



# 1115-L Series TW Institutional Spring-loaded Caster

- Institutional version of spring-loaded caster. Ideal for chip industry and tool cart.



## Features



Total Lock Brake  
with Aluminum Alloy Pedal



Thread guard

## Wheel Options



E-Conductive



TPR on PP Core



W Resolute Wheel



Resolute



QPU on AL Core



Ball Bearing

## TOP PLATE SIZE AND BOLT HOLE SPACING

Caster Size	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
4", 5"	91 x 91 mm (3-9/16"x 3-9/16")	68 x 68 mm (2-11/16"x 2-11/16")	10 mm (3/8")

Diameter*Width	Load	Material	Item No.			Bearing	Overall Height	Swivel radius
			Fixed	Swivel	Brake			
100mm×32mm (4"×1-1/4")	60 kgs (130 lbs)	E-Conductive	—	1115-04-17-2-L	1115-04-17-4-L	Ball Bearing	155.5mm (6-1/8")	Swivel 82.5mm Swivel W/Center lock 105mm
	90 kgs (198 lbs)	TPR on PP Core	—	1115-04-75-2-L	1115-04-75-4-L			
	130 kgs (286 lbs)	W Resolute Wheel	—	1115-04-48-2-L	1115-04-48-4-L			
	120 kgs (264 lbs)	Resolute	—	1115-04-68-2-L	1115-04-68-4-L			
	140 kgs (308 lbs)	<b>QPU on AL Core</b>	—	<b>1115-04-87-2-L</b>	<b>1115-04-87-4-L</b>			
125mm×32mm (5"×1-1/4")	70 kgs (150 lbs)	E-Conductive	—	1115-05-17-2-L	1115-05-17-4-L	Ball Bearing	193 mm (7-5/8")	Swivel 91.5mm Swivel W/Center lock 105 mm
	100 kgs (200 lbs)	TPR on PP Core	—	1115-05-75-2-L	1115-05-75-4-L			
	147 kgs (323 lbs)	W Resolute Wheel	—	1115-05-48-2-L	1115-05-48-4-L			
	140 kgs (308 lbs)	Resolute	—	1115-05-68-2-L	1115-05-68-4-L			
	150 kgs (330 lbs)	<b>QPU on AL Core</b>	—	<b>1115-05-87-2-L</b>	<b>1115-05-87-4-L</b>			