



1116-55-LI Series

Light Duty Stainless Steel Caster

- Stainless steel housing is of high temperature resistant and corrosion/rust resistant, ideal for textile industry, chemical industry, food processing industry and bakery.

Load
40-70kg



» Features



Side Lock Brake

» Wheel Options

PP



Nylon



Resolute



中管

» TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	58 x 70 mm (2-1/4" x 2-3/4")	38.5 x 55 mm (1-1/2" x 2-3/16")	8mm (5/16")

Diameter×Width (2" x 7/8")	Load	Material	Item No.			Bearing	Overall Height	Swivel radius
			Fixed	Swivel	Brake			
50mm x 22mm (2" x 7/8")	40 kgs(88 lbs)	Resolute	1116-LI-02-68-1	1116-LI-02-68-2	—	Plain Bearing	70mm (2-3/4")	Swivel 49mm
50mm x 24.5mm (2" x 15/16")	70 kgs(154 lbs)	Nylon	1116-LI-02-07-1	1106-LI-02-07-2	1106-LI-02-07-4	Plain Bearing	70mm (2-3/4")	Swivel 49mm Swivel W/Side Brake 61.5mm
	50 kgs(110 lbs)	PP	1116-LI-02-29-1	1106-LI-02-29-2	1106-LI-02-29-4			
62.5mm x 23.5mm (2-1/2" x 15/16")	50 kgs(110 lbs)	Resolute	1116-LI-25-93-1	1116-LI-25-93-2	1116-LI-25-93-4	Plain Bearing	84.5mm (3-5/16")	Swivel 56.5mm Swivel W/Side Brake 63mm
62.5mm x 26mm (2-1/2" x 1-1/16")	70 kgs(154 lbs)	Nylon	1116-LI-25-07-1	1116-LI-25-07-2	1116-LI-25-07-4			
	50 kgs(110 lbs)	PP	1116-LI-25-29-1	1116-LI-25-29-2	1116-LI-25-29-4			