

**1124 Series****1-1/2" Wide General Purposes Caster (American Style)**

- Swivel easily under heavy load, for workshop carts. Patented thread guards prevent swivel failure caused by build-up of strings between the wheel and fork legs, as well as the dust in the wheel bearing.

Load
140-400 kg

**» Features**

Side Lock Brake



Center Lock Brake



Thread guard

Different PU
tread hardness available**» Wheel Options**

NBR Rubber on Cast



PU on Cast



Rubber on Cast

Non-marking
Rubber on Cast

W Resolute



WCPD



QPU



Nylon



Cast Iron



CPD



Resolute



WMRC



EPU



EQPU



QPU on AL Core



King Kong Wheel



Ball Bearing

» TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	100 x 115 mm (4"x 4-1/2")	70 x 85 mm (2-5/8"~3"x3"-3-5/8")	9.5 mm (3/8")
2	108 x 84 mm (4-1/4"x 3-5/16")	87.5 x 63.5 mm (3-7/16x 2-1/2")	M8 (5/16")
3	115 x 159 mm (4-1/2"x 6-1/4")	75 x 130 mm (2-7/16"-3-3/8" x4-15/16"-5-1/4")	12.7 mm (1/2")



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
50mm x 45mm (2" x 1-3/4")	* 275 kgs(606 lbs)	King Kong Wheel	11240200711013	11240200712013	—	Ball Bearing	82mm (3-1/4")	Swivel 51mm (2")
93mm x 28mm (3-21/32" x 1-3/32")	175 kgs(385 lbs)	Cast Iron	1124-04-14-1	1124-04-14-2	—	Ball Bearing	138.5mm	Swivel 71.5mm
100mm x 32mm (4" x 1-1/4")	200 kgs(440 lbs)	Nylon	1124-04-07-1	1124-04-07-2	1124-04-07-4	Ball Bearing	142mm (5-5/8")	Swivel 75mm Swivel W/Side Brake 75mm Swivel W/Center lock 115mm
	150 kgs(330 lbs)	CPD	1124-04-49-1	1124-04-49-2	1124-04-49-4			
100mm x 34mm (4" x 1-1/3")	200 kgs(440 lbs)	PU on Cast	1124-04-33-1	1124-04-33-2	1124-04-33-4			
	300 kgs(660 lbs)	QPU	1124-04-80-1	1124-04-80-2	1124-04-80-4			
	150 kgs(330 lbs)	NBR Rubber on Cast	1124-04-04-1	1124-04-04-2	1124-04-04-4			
	150 kgs(330 lbs)	Non-marking Rubber on Cast	1124-04-11-1	1124-04-11-2	1124-04-11-4			
100mm x 35mm (4" x 1-1/8")	150 kgs(330 lbs)	Rubber on Cast	1124-04-03-1	1124-04-03-2	1124-04-03-4			
100mm x 36mm (4" x 1-7/16")	325 kgs(715 lbs)	QPU on AL Core (Round)	1124-04-87-1	1124-04-87-2	1124-04-87-4			
100mm x 37.5mm (4" x 1-1/2")	140 kgs(308 lbs)	W Resolute	1124-04-64-1	1124-04-64-2	1124-04-64-4			
100mm x 40mm (4" x 1-9/16")	350 kgs(770 lbs)	QPU on AL Core (Round)	1124-04(40)-87-1	1124-04(40)-87-2	1124-04(40)-87-4			
122mm x 36mm (4-13/16" x 1-7/16")	250 kgs(550 lbs)	Cast Iron	1124-05-14-1	1124-05-14-2	—	Ball Bearing	165.5mm	Swivel 91.5mm
125mm x 37.5mm (5" x 1-1/2")	250 kgs(550 lbs)	W Resolute	1124-05-64-1	1124-05-64-2	1124-05-64-4	Ball Bearing	167mm (6-1/2")	Swivel 93mm Swivel W/Side Brake 93mm Swivel W/Center lock 112mm
125mm x 40mm (5" x 1-9/16")	250 kgs(550 lbs)	PU on Cast	1124-05-33-1	1124-05-33-2	1124-05-33-4			
	350 kgs(770 lbs)	QPU	1124-05-80-1	1124-05-80-2	1124-05-80-4			
	350 kgs(770 lbs)	QPU on AL Core (Round)	1124-05-87-1	1124-05-87-2	1124-05-87-4			
	250 kgs(550 lbs)	EPU	1124-05-78-1	1124-05-78-2	1124-05-78-4			
	300 kgs(660 lbs)	EQPU	1124-05-81-1	1124-05-81-2	1124-05-81-4			
	200 kgs(440 lbs)	Rubber on Cast	1124-05-03-1	1124-05-03-2	1124-05-03-4			
	200 kgs(440 lbs)	NBR Rubber on Cast	1124-05-04-1	1124-05-04-2	1124-05-04-4			
	200 kgs(440 lbs)	Non-marking Rubber on Cast	1124-05-11-1	1124-05-11-2	1124-05-11-4			
125mm x 41mm (5" x 1-5/8")	250 kgs(550 lbs)	Nylon	1124-05-07-1	1124-05-07-2	1124-05-07-4			
	200 kgs(440 lbs)	CPD	1124-05-49-1	1124-05-49-2	1124-05-49-4			
138mm x 42mm (5-7/16" x 1-5/8")	300 kgs(660 lbs)	Cast Iron	1124-06-14-1	1124-06-14-2	—	Ball Bearing	184mm	Swivel 104mm
150mm x 37.5mm (6" x 1-1/2")	180 kgs(396 lbs)	W Resolute	1124-06-64-1	1124-06-64-2	1124-06-64-4	Ball Bearing	190mm (7-1/2")	Swivel 110mm Swivel W/Side Brake 110mm Swivel W/Center lock 160mm
150mm x 40mm (6" x 1-9/16")	250 kgs(550 lbs)	NBR Rubber on Cast	1124-06-04-1	1124-06-04-2	1124-06-04-4			
	250 kgs(550 lbs)	Non-marking Rubber on Cast	1124-06-11-1	1124-06-11-2	1124-06-11-4			
	350 kgs(770 lbs)	Nylon	1124-06-07-1	1124-06-07-2	1124-06-07-4			
	250 kgs(550 lbs)	CPD	1124-06-49-1	1124-06-49-2	1124-06-49-4			
	350 kgs(770 lbs)	WMRC	1124-06-45-1	1124-06-45-2	1124-06-45-4			
	250 kgs(550 lbs)	WCPD	1124-06-79-1	1124-06-79-2	1124-06-79-4			

* 50mm x 45mm (2" x 1-3/4") Static load capacity:550kg (1212.5 lbs)



 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
150mm x 42mm (6" x 1-5/8")	350 kgs(770 lbs)	PU on Cast	1124-06-33-1	1124-06-33-2	1124-06-33-4	Ball Bearing	190mm (7-1/2")	Swivel 110mm Swivel W/Side Brake 110mm Swivel W/Center lock 160mm
	400 kgs(880 lbs)	QPU	1124-06-80-1	1124-06-80-2	1124-06-80-4			
	350 kgs(770 lbs)	EPU	1124-06-78-1	1124-06-78-2	1124-06-78-4			
	400 kgs(880 lbs)	EQPU	1124-06-81-1	1124-06-81-2	1124-06-81-4			
	400 kgs(880 lbs)	QPU on AL Core (Round)	1124-06-87-1	1124-06-87-2	1124-06-87-4			
150mm x 45.5mm (6" x 1-13/16")	220 kgs(485 lbs)	Rubber on Cast	1124-06-03-1	1124-06-03-2	1124-06-03-4			
200mm x 44mm (8" x 1-3/4")	300 kgs(660 lbs)	NBR Rubber on Cast	1124-08-04-1	1124-08-04-2	1124-08-04-4	Ball Bearing	240mm (9-1/2")	Swivel 145mm Swivel W/Side Brake 145mm Swivel W/Center lock 162.5mm
	300 kgs(660 lbs)	Non-marking Rubber on Cast	1124-08-11-1	1124-08-11-2	1124-08-11-4			
200mm x 45mm (8" x 1-13/16")	350 kgs(770 lbs)	Cast Iron	1124-08-14-1	1124-08-14-2	1124-08-14-4			
200mm x 50mm (8" x 2")	400 kgs(880 lbs)	PU on Cast	1124-08-33-1	1124-08-33-2	1124-08-33-4			
	400 kgs(880 lbs)	QPU	1124-08-80-1	1124-08-80-2	1124-08-80-4			
	400 kgs(880 lbs)	EPU	1124-08-78-1	1124-08-78-2	1124-08-78-4			
	400 kgs(880 lbs)	EQPU	1124-08-81-1	1124-08-81-2	1124-08-81-4			
	260 kgs(570 lbs)	Rubber on Cast	1124-08-03-1	1124-08-03-2	1124-08-03-4			
	300 kgs(660 lbs)	NBR Rubber on Cast	1124-08-04-1	1124-08-04-2	1124-08-04-4			
	300 kgs(660 lbs)	Non-marking Rubber on Cast	1124-08-11-1	1124-08-11-2	1124-08-11-4			
	400 kgs(880 lbs)	Nylon	1124-08-07-1	1124-08-07-2	1124-08-07-4			
	300 kgs(660 lbs)	CPD	1124-08-49-1	1124-08-49-2	1124-08-49-4			
	180 kgs(396 lbs)	Resolute	1124-08-53-1	1124-08-53-2	1124-08-53-4			
	400 kgs(880 lbs)	WMRC	1124-08-45-1	1124-08-45-2	1124-08-45-4			
	300 kgs(660 lbs)	WCPD	1124-08-79-1	1124-08-79-2	1124-08-79-4			
	400 kgs(880 lbs)	QPU on AL Core (Round)	1124-08-87-1	1124-08-87-2	1124-08-87-4			
	400 kgs(880 lbs)	QPU on AL Core (Flat)	1124-08-87-1	1124-08-87-2	1124-08-87-4			