





1156

Series

56 Series Central Locking Caster

- Housing made of pressed steel. Precision ball bearings in both swivel head and wheel. Resolute wheel offers cushion ride, silent drive and debris rejection functions. Housing cover made of synthetic material.



Brake type	Wheel diameter (mm)	Width of Tread (mm)	Stem diameter (mm)	Stem length (mm)	Offset (mm)	Overall height (mm)	Load capacity (kg)	Swivel radius (mm)	Hole height (mm)	Hole diameter (mm)	Angle	Wheel Tread Material	ITEM NO.
Swivel caster with total lock	125	31	28	96	35	158.5	120	98	78.5	11.2	A	Resolute Rubber	11560500458033
	125	31	28	96	35	158.5	120	98	78.5	11.2	B		11560500458233
	125	31	32	50	35	158.5	120	98	34	11.2	A		11560500458133
	125	31	32	50	35	158.5	120	98	34	11.2	B		11560500458333
Swivel caster with total and directional lock	125	31	28	96	35	158.5	120	98	78.5	11.2	A	Resolute Rubber	11560500458023
	125	31	28	96	35	158.5	120	98	78.5	11.2	B		11560500458223
	125	31	32	50	35	158.5	120	98	34	11.2	A		11560500458123
	125	31	32	50	35	158.5	120	98	34	11.2	B		11560500458323
Swivel caster with total lock	150	31	28	96	40	183	150	115	78.5	11.2	A	Resolute Rubber	11560600458033
	150	31	28	96	40	183	150	115	78.5	11.2	B		11560600458233
	150	31	32	50	40	183	150	115	34	11.2	A		11560600458133
	150	31	32	50	40	183	150	115	34	11.2	B		11560600458333
Swivel caster with total and directional lock	150	31	28	96	40	183	150	115	78.5	11.2	A	Resolute Rubber	11560600458023
	150	31	28	96	40	183	150	115	78.5	11.2	B		11560600458223
	150	31	32	50	40	183	150	115	34	11.2	A		11560600458123
	150	31	32	50	40	183	150	115	34	11.2	B		11560600458323
Swivel caster with total lock	200	31	28	96	60	229	150	160	78.5	11.2	A	Resolute Rubber	11560800458033
	200	31	28	96	60	229	150	160	78.5	11.2	B		11560800458233
	200	31	32	50	60	229	150	160	34	11.2	A		11560800458133
	200	31	32	50	60	229	150	160	34	11.2	B		11560800458333
Swivel caster with total and directional lock	200	31	28	96	60	229	150	160	78.5	11.2	A	Resolute Rubber	11560800458023
	200	31	28	96	60	229	150	160	78.5	11.2	B		11560800458223
	200	31	32	50	60	229	150	160	34	11.2	A		11560800458123
	200	31	32	50	60	229	150	160	34	11.2	B		11560800458333