

## 162 Series Super Heavy Duty Casters (Single Wheel)

O Ultimate super heavy duty caster built to meet the most demanding industrial application. Equipped with Dersheng's Xtremethane PU wheel, this caster is designed to carry heavy load for a long period of product life.





#### » Features



#### **Tampered Bearing**

The tampered bearing used in the horn provides strength to carry extra load, and absorb shock impact. Also, the tampered bearing is easy to be disassembled for maintence or replacement purpose.



Swivel W/KD Lock Brake



Metal Thread Guard (optional)

### → Wheel Options



XPU on Iron Core



XPU on Iron Core



**Tampered Bearing** 





# Note: Top Plate Size Bolt Hole Spacing Attaching Bolt Size 6" 8" 10" 175 x 140mm (6-7/8" x 5-1/2") 140 x 105mm (5-1/2" x 4-1/8") 16 mm (5/8") 10" 12" 255 x 200mm (10-1/16" x 7-7/8") 210 x 160mm (8-1/4" x 6-5/16") 20 mm (3/4")

$\bigcap$	kg	<b>©</b>	tem No.				<u>ম</u>	Ţ
Diameter×Width	Load	Material	Fixed	Swivel	Brake	Bearing	Overall Height	Swive I radius
150mm x 42mm (6" x 1-5/8")	650 kgs (1435 lbs)	XPU on Iron Core(Round)	1162-06-91-1	1162-06-91-2	1162-06-91-4	Tampered Bearing	230mm (9-1/16")	Swivel 126mm Swivel W/KD lock brake 132mm
200mm x 50mm (8" x 2")	1000 kgs (2200 lbs)	XPU on Iron Core(Round)	1162-08-91-1	1162-08-91-2	1162-08-91-4	Tampered Bearing	280mm (11-1/32")	Swivel 163mm Swivel W/KD lock brake 163mm
200mm x 66mm (8" x 2-9/16")	1300 kgs (2870 lbs)	XPU on Iron Core(Round)	1162-08-96-1	1162-08-96-2	1162-08-96-4	Tampered Bearing	280mm (11-1/32")	Swivel 165mm Swivel W/KD lock brake 165mm
250mm x 62mm (10" x 2-7/16")	1600 kgs (3530 lbs)	XPU on Iron Core(Round)	1162-10-91-1	1162-10-91-2	1162-10-91-4	Tampered Bearing	330mm (13")	Swivel 189mm Swivel W/KD lock brake 189mm
250mm x 80mm (10" x 3-1/8")	2000 kgs (4410 lbs)	XPU on Iron Core(Flat)	1162-10-91(80)-1	1162-10-91(80)-2	1162-10-91(80)-4	Tampered Bearing	330mm (13")	Swivel 198mm Swivel W/KD lock brake 198mm
300mm x 90mm (12" x 3-17/32")	2700 kgs (6000 lbs)	XPU on Iron Core(Flat)	1162-12-91-1	1162-12-91-2	1162-12-91-4	Tampered Bearing	380mm (14-31/32")	Swivel 222mm Swivel W/KD lock brake 222mm