



## Soild Rubber Wheel

O Heavy-duty with a cushion ride, ideal for uneven ground condition.









## >> Wheel Options







Solid Rubber wheel with plated steel rim



Flat Free Tire



Soild Rubber Wheel (EZ Roll)



PU Foam Tire



Ball Bearing

Size	Wheel diamete	Width	Material	Rim	Hub Length	Load	Bearing	(Bore Size)	Item No.	輪子樣式
8" (250-4)	198mm	51mm	Soild Rubber Wheel(Q)	Steel rim (painted)	50mm (2" centered)	100 kgs (220 lbs)	Ball Bearing	17mm	1243080015	
	200mm	53mm	Soild Rubber Wheel	Steel rim (painted)	55mm (2-1/5" centered) 57.5mm (2-1/4" centered)	120 kgs (264 lbs)	Ball Bearing	17mm	1243080077	
				Steel rim (zinc-plated)					1243080019	
				Plastic rim					1243080068	
	200mm	53mm	Soild Rubber Wheel (EZ Roll)	Steel rim (zinc-plated)	55mm (2-1/5" centered)	120 kgs (264 lbs)	Ball Bearing	17mm	1243080079	
	208mm	53.5 mm	Flat Free Tire	Steel rim (zinc-plated)		100 kgs (220 lbs)	Ball Bearing	17mm	1243080067	The state of the s





Size	Wheel diamete	Width	Material	Rim	Hub Length	Load	Bearing	(Bore Size)	Item No.	輪子樣式
10" (350-4)	250mm	68mm	Soild Rubber Wheel (EZ Roll)	Steel rim (painted)	65mm (2-9/16" centered)	180 kgs (396 lbs)	Ball Bearing	17mm -	1243100070	
				Steel rim (zinc-plated)					1243100069	
	255mm	85mm	Flat Free Tire	Steel rim (zinc-plated)	65mm (2-9/16" centered)	150 kgs (330 lbs)	Ball Bearing	17mm	1243100049	
	257mm	79.5mm	Soild Resilient Rubber Wheel	Steel rim (painted)	65mm (2-9/16" centered)	180 kgs (396 lbs)	Ball Bearing	17mm	1243100076	
				Steel rim (zinc-plated)			Ball Bearing	17mm	1243100051	
	263mm	87mm	PU Foam Tire	Steel rim (zinc-plated)	65mm (2-9/16" centered)	150 kgs (330 lbs)	Ball Bearing	17mm	1243100058	