

RA Series

HEAVY DUTY WHEEL

with Rubber tread,
with Aluminum wheel core

	Tread & tyre hardness	75 ± 5 shore A
	Temperature resistance	-25 °C to +80 °C
	Rolling resistance	good
	Operating noise	very good
	Floor surface preservation	very good



Tread

Made of high quality elastic rubber, Dersheng's rubber on aluminum core wheel features 75° ± 5° shore A hardness, high operational comfort, great floor preservation and good shock absorption. Color black.

Other features

Good resistant to chemical, solvent and many other aggressive substances.

Working temperature: -25°C to +80°C.

Maintenance-free under normal conditions

Wheel centre/rim

Made of casting aluminum.

 Item No	 Wheel Diameter (D) [mm]	 Wheel Width (T2) [mm]	 Load Capacity [kg(lbs)]	 Axle Bore Ø(d) [mm]	 Hub Length (T1) [mm]	 Bearing Type
12046804135171	100	31	150kgs (330lbs)	15	32	 Ball bearing
12046804155171	100	40	200kgs (440lbs)	12	40	
12046804155271	100	40	200kgs (440lbs)	15	40	
12046805135171	125	31	200kgs (440lbs)	15	32	
12046805155171	125	40	250kgs (551lbs)	15	40	
12046805155271	125	40	250kgs (551lbs)	17	40	
12046806185171	150	40	280kgs (617lbs)	15	40	
12046806185271	150	40	280kgs (617lbs)	17	40	
12046856185171	160	42	300kgs (661lbs)	17	42	
12046856185271	160	42	300kgs (661lbs)	20	42	
12046808185171	200	44	400kgs (881lbs)	20	44	
12046808185271	200	44	400kgs (881lbs)	25	44	

