











Resolute Wheel Series

	Tread & tyre hardness		68°±5° Shore A
	Temperature resistance		-20°C to +60°C
	Rolling resistance		excellent
	Operating noise		excellent
	Floor surface preservation		excellent



Heavy
duty

Load

181-306kg

Heavy
duty

Load

136-272kg

Light-medium
duty

Load

56-147kg

Tread

Made of high-quality thermoplastic rubber (TPR). Resolute wheels offer good floor preservation, easy to maneuver, low noise operation, shock-absorbing, low rolling resistance, and good resistant to chemical, solvent and many other aggressive substances. Wheel color: grey
Hardness: 68°±5° Shore A
The chemical bond with the wheel center/rim cannot be decomposed.

Wheel centre/rim

Made of High-quality impact-resistant polypropylene

Other features

- Quiet rolling, shock-absorbing, low rolling resistance, maintenance-free under normal conditions.
- Working temperature:-20°C to +60°C.













Light-medium duty

Item No	Wheel Diameter (D) [mm]	Wheel Width (T2) [mm]	Load Capacity [kg(lbs)]	Axle Bore Ø(d) [mm]	Hub Length (T1) [mm]	Tread Profile	Bearing Type
1235030015	3" (75mm)	1" (27mm)	56kg / 125lbs	Ø 6 mm	33 mm	Round	Ball bearing
1235030016	3" (75mm)	1-1/4" (31mm)	90kg / 200lbs	Ø 10mm	41mm		
1235040025	4" (100mm)	1-1/4" (31mm)	125kg / 275lbs	Ø 10mm	41mm		
1235050032	5" (125mm)	1-1/4" (31mm)	147kg / 325lbs	Ø 10mm	41mm		
1235060010	6" (150mm)	1-1/4" (31mm)	147kg / 325lbs	Ø 10mm	41mm		



Heavy duty

 Item No	 Wheel Diameter (D) [mm]	 Wheel Width (T2) [mm]	 Load Capacity [kg(lbs)]	 Axle Bore Ø(d) [mm]	 Hub Length (T1) [mm]	 Tread Profile	 Bearing Type	
1235040031	4" (100mm)	2" (50mm)	136kg / 300lbs	Ø 13mm	62mm	Round	Annular ball bearing	
1235050040	5" (125mm)	2" (50mm)	170kg / 375lbs	Ø 13mm	62mm			
1235060021	6" (150mm)	2" (50mm)	204kg / 450lbs	Ø 13mm	62mm			
1235080012	8" (200mm)	2" (50mm)	272kg / 600lbs	Ø 13mm	62mm			
1235040028	4" (100mm)	2" (50mm)	181kg / 400lbs	Ø 13mm	62mm	Flat		
1235050035	5" (125mm)	2" (50mm)	227kg / 500lbs	Ø 13mm	62mm			
1235060015	6" (150mm)	2" (50mm)	272kg / 600lbs	Ø 13mm	62mm			
1235080013	8" (200mm)	2" (50mm)	306kg / 675lbs	Ø 13mm	62mm			